

EUROLITE Set 4x LED SLS-7 HCL Floor white + Case

4x flat LED spotlight with RGBAW+UV color mixing in white including case

Art. No.: 2000658

GTIN: 4026397670950



Features:

- Slim design for space-saving applications
- Enjoy perfect solid and pastel colors plus ultra violet thanks to 6-color mixing
- DMX and power terminals intelligently designed for easy wiring
- 7 LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect; UV effect
- Integrated show programs
- Direct color selection for 19 preset colors
- The device is cooled by cooling fan
- Control via IR remote control; stand-alone; sound to light via microphone; DMX; master/slave function
- Fixtures available for Light Captain; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light J; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- With a beam angle of 17°
- With double bracket
- 4 digit 7-segment LED display
- Rubber feet
- Mains input and output for power linking up to 8 units
- Available in various colors
- For application areas such as: Clubs/dancing school; decoration; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels; advertisement/Shop window
- Application possibility: Standing; suspended; on stand
- <p>ROADINGER TDV-1 Universal Case Pick
- <h2 class="featureSatz">Universal case with flexible foam dividers</h2>With dividers
- High-quality workmanship with plastic 3 mm, black, imprinted

Logistic

EAN / GTIN: 4026397670950

Weight: 10,50 kg

Length: 0.82 m

Width: 0.41 m

Height: 0.45 m

- Interior with foam padding
- Aluminum profile frames 12mm with rounded edges
- Rugged carrying handle
- 3 chrome tip-over locks
- 2 high-quality spring locks with shut-off function
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 8.97 kg

EUROLITE LED SLS-7 HCL Floor white

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	20 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Fuse:	T 0.5 A
Lamp type:	LED lamp
LED type:	7 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	2; 3; 4; 6; 10
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	IR remote control; stand-alone; sound to light via microphone; DMX; master/slave function
Fixtures available for:	Light Captain; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light J; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Beam angle:	17°
Beam angle (1/2 peak):	17°
Housing color:	White
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
Transport aid:	Rubber feet
Material:	ABS Acrylonitrile butadiene styrene
Dimensions:	Width: 22 cm Depth: 11 cm Height: 21 cm
Weight:	1.38 kg

Noise classification:	Class 2 (slight noise)
Photobiological safety:	Risk Group 0
Diameter mounting holes:	5 x Ø11mm
Material:	Metal, 2 mm
Color:	White
Cable construction:	3 x 0.75 mm ² H05VV-F
Cable length:	Approx. 1.2 m
Color:	White
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

ROADINGER TDV-1 Universal Case Pick

Maximum load:	25 kg
Aluminum profile frames:	12 mm
Carrying handle:	1 pc/pcs
Stop hinge:	3 pc/pcs
Lock:	Spring lock: 2 pc/pcs with shut-off function
Material:	Plastic, 3 mm
Color:	Black, imprinted
Inside dimensions:	52 cm x 28.5 cm x 20 cm
Dimensions:	Width: 54 cm Depth: 31 cm Height: 26 cm
Weight:	3.45 kg

Scope of delivery:

4 x EUROLITE LED SLS-7 HCL Floor white

- 1 x light effect
- 1 x power cord
- 1 x remote control
- 1 x battery
- 1 x user manual

1 x ROADINGER TDV-1 Universal Case Pick

- 1 x case