

EUROLITE Set 2x LED BAR-6 QCL RGB+UV Bar + Soft Bag

2x Light effect bar (60 cm) with RGB+UV color mixing including soft bag

Art. No.: 20000660

GTIN: 4026397670998



Features:

- 6 LEDs 4 W high-power 4in1 QCL RGB/UV (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect; UV effect
- Integrated show programs
- Direct color selection for 20 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Fixtures available for LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; decoration; mobile djs / entertainer; party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation
- Application possibility: Suspended; wall mounting
- <p>EUROLITE SB-205 Soft Bag
- <h2 class="featureSatz">Universal softbag</h2>Ideal for e.g. LED bars with 50 cm length and accessories
- With divider
- With 2 device compartments
- High-quality workmanship with nylon , black
- Interior with foam padding

Logistic

EAN / GTIN: 4026397670998

Weight: 5,00 kg

Length: 0.61 m

Width: 0.31 m

Height: 0.42 m

- 2 carrying straps

Technical specifications:

Weight:	3.80 kg
---------	---------

EUROLITE LED BAR-6 QCL RGB+UV Bar	
Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	14 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug included
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	6 x 4 W high-power 4in1 QCL RGB/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	2; 4; 5; 9; 6
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Beam angle (1/2 peak):	20°
Beam angle (1/10 peak):	33°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 60 cm Depth: 6.5 cm Height: 10.3 cm
Weight:	1.75 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Cable construction:	3 x 0.75 mm² H05VV-F
Cable length:	Approx. 1.1 m
Diameter mounting holes:	1 x Ø20mm; 1 x Ø11mm; 1 x Ø8mm; 2 x Ø7mm

Material:	Metal, 2 mm
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE SB-205 Soft Bag

Maximum load:	25 kg
Carrying strap:	2 pc/pcs
Material:	Nylon, water repellent
Color:	Black
Dimensions:	Width: 57.5 cm Depth: 17 cm Height: 12 cm
Weight:	0.30 kg

Scope of delivery:

- 1 x bar
- 1 x power cord
- 2 x mounting bracket
- 2 x knurled screw
- 2 x washer
- 1 x user manual