

EUROLITE Set 4x LED BAR-12 UV Bar + Case

4x Light effect bar (1 m) with UV LEDs including flightcase

Art. No.: 2000662

GTIN: 4026397671018



List price: 950.81 €

incl. 19% VAT.

Features:

EUROLITE LED BAR-12 UV Bar

LED bar (1m) with 12 x 1 watt ultra violet (UV) LED

- 12 powerful LEDs 1 W high-power ultra violet (UV)
- Dimmer electronic
- UV effect
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 14°
- With Mounting bracket
- 4 digit 7-segment LED display
- Silent operation
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; Party room; restaurants, bars and hotels
- Application possibility: Suspended; Wall mounting

Package contents

- 1 x light effect, 1 x power cord, 2 x mounting bracket, 2 x knurled screw, 2 x washer, 1 x user manual

Logistic

EAN / GTIN: 4026397671018

Weight: 26,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.60 m

Bulky product

ROADINGER Flightcase EC-B252 4x LED BAR-252 RGB

Carrying case

- High-quality workmanship with birch multiplex 7 mm, black, laminated

- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- Rugged carrying handle
- 3 chrome tip-over locks
- 2 high-quality butterfly locks
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 21,50 kg

EUROLITE LED BAR-12 UV Bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	25 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	IEC connector (F) mounting version
Lamp type:	LED lamp
LED:	12 x 1 W high-power ultra violet (UV)
DMX channels:	1; 2
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Projection:	Flicker-free
Beam angle:	14°
Beam angle (1/2 peak):	14°
Beam angle (1/10 peak):	24°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 1 m Depth: 8,5 cm Height: 11,5 cm
Weight:	2,65 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Power cord	
Cable construction:	3 x 0,75 mm ² H05VV-F
Cable length:	Approx. 1,1 m
Mounting bracket	

Diameter mounting holes:	1 x Ø20mm; 1 x Ø11mm; 1 x Ø8mm; 2 x Ø7mm
Material:	Metal, 2 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase EC-B252 4x LED BAR-252 RGB

Maximum load:	25 kg
Aluminum profile frames:	30 mm
Carrying handle:	1 pc/pcs
Stop hinge:	3 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Material:	Birch multiplex, 7 mm
Color:	Black, laminated; dark brown, laminated
Inside dimensions:	1,08 m x 44 cm x 7,5 cm
Device compartment:	1,08 m x 6,5 cm x 7,5 cm
Dimensions:	Width: 1,17 m Depth: 48 cm Height: 17 cm
Weight:	10,90 kg