

EUROLITE Set 2x LED BAR-12 QCL RGB+UV Bar + Soft Bag

2x light effect bar (1 m) with RGB+UV color mixing including soft bag

Art. No.: 2000663

GTIN: 4026397671025



List price: 391.51 €

incl. 19% VAT.

Features:

EUROLITE LED BAR-12 QCL RGB+UV Bar

LED bar (1m) with 12 x 4 watt 4in1 QCL RGB/UV LED

- 12 powerful LEDs 4 W high-power 4in1 QCL RGB/UV (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect; UV effect
- Integrated show programs
- Direct color selection for 20 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 20°
- With Mounting bracket
- 4 digit 7-segment LED display
- Silent operation
- Preprogrammed in LED PC-Control 512; EASY SHOW 2; Light Captain; EASY SHOW 3
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; Party room; restaurants, bars and hotels; small rental
- Application possibility: Suspended; Wall mounting
- For further information about this product, please refer to the Data Sheet under "Downloads"

Package contents

- 1 x bar, 1 x user manual, 1 x power cord, 2 x mounting bracket, 2 x screw, 2 x washer

Logistic

EAN / GTIN: 4026397671025

Weight: 8,00 kg

Length: 1.10 m

Width: 0.50 m

Height: 0.30 m

EUROLITE SB-12 Soft Bag

Practical black soft bag for LED bars (1 m length), adjustable divider

- Ideal for 1 or 2 LED bars with 1 meter length
- Made of easy-care nylon
- With divider
- With 2 Device compartments
- High-quality workmanship with textile , black
- Interior with foam padding
- 2 carrying straps
- 1 shoulder strap

Technical specifications:

Weight: 6,27 kg

EUROLITE LED BAR-12 QCL RGB+UV Bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	25 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED:	12 x 4 W high-power 4in1 QCL RGB/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	2; 4; 5; 6; 9
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	LED PC-Control 512; EASY SHOW 2; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	20°
Beam angle (1/2 peak):	20°
Beam angle (1/10 peak):	33°
Wavelength:	Ultra violet (UV) 399 nm
Housing color:	Black
Attachment system:	Mounting bracket

Display type:	4 digit 7-segment LED display
Material:	Aluminum; metal
Dimensions:	Length: 1 m Depth: 6,5 cm Height: 10,3 cm
Weight:	2,85 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Power cord	
Cable construction:	3 x 0,75 mm ² H05VV-F
Cable length:	1,2 m
Mounting bracket	
Diameter mounting holes:	1 x Ø20mm; 1 x Ø11mm; 2 x Ø7mm
Material:	Metal, 2 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE SB-12 Soft Bag

Maximum load:	20 kg
Carrying strap:	2 pc/pcs
Transport aid:	1 x shoulder strap
Material:	Textile
Color:	Black
Dimensions:	Width: 1,07 m Depth: 17 cm Height: 18 cm
Weight:	570 g