

OMNITRONIC Set WMT-1M UHF Transmitter + WMR-1M UHF Receiver

UHF Transmitter including UHF Receiver

Art. No.: 20000667 GTIN: 4026397523249





Logistic

EAN / GTIN: 4026397523249 Weight: 1,00 kg Length: 0.30 m Width: 0.22 m Heigth: 0.21 m

The article is no longer in our assortment.

Features:

OMNITRONIC WMT-1M UHF Transmitter, mono

Wireless mono audio transmission system, 823-832 MHz

- Wireless audio transmission system with UHF PLL technology
- For wireless transmission of audio line and microphone signals with one transmitter and one or more receivers
- Duplex gap 823-832 MHz
- Parallel use of up to 4 transmitters possible
- Compatible with MOM-10BT4 system
- 16 channels selectable
- Audio line input (3.5 mm jack) and microphone input (mini XLR)
- Volume level control
- Operation via 2 batteries or rechargeable batteries size AA
- Built-in charging function via micro USB port with LED indicator
- Supports operation and simultaneous charging
- Robust metal fixing clip
- Incl. USB charging cable and 3.5 mm audio cable
- License-free and approved in large parts of the EU
- Operating range up to 50m
- UHF 823 832 MHz License-free and approved in large parts of Europe

Package contents

- 1 x receiver, 1 x jack cable, 1 x USB cable, 2 x battery, 1 x user manual, 1 x declaration of conformity

OMNITRONIC WMR-1M UHF-Receiver, mono

Wireless mono audio transmission system, 823-832 MHz

- Wireless audio transmission system with UHF PLL technology
- For wireless transmission of audio line and microphone signals with one transmitter and one or more receivers
- Duplex gap 823-832 MHz
- Compatible with MOM-10BT4 system
- Parallel use of up to 4 transmitters possible
- 16 channels selectable
- Audio line output and earphone connection via 3.5 mm jack
- Volume control
- Built-in charging function via micro USB port with LED indicator
- Supports operation and simultaneous charging
- Robust metal fixing clip
- Incl. USB charging cable and 3.5 mm audio cable
- License-free and approved in large parts of the EU (please check on a country-by-country basis)
- Operating range up to 50m
- UHF 823 832 MHz License-free and approved in large parts of Europe
- Package contents
- 1 x receiver, 1 x jack cable, 1 x USB cable, 2 x battery, 1 x user manual, 1 x declaration of conformity

Technical specifications:

Weight:

0,41 kg

OMNITRONIC WMT-1M UHF Transmitter, mono

| included Battery/battery pack Battery: 2 x Mignon (AA) included S/N ratio: >90 dB Range: Range up to 50m Frequency band: UHF 823 - 832 MHz Frequency stability: ± 0,01 % RF power output: 10 mW Modulation: FM Frequency selection: 16 switchable frequencies Pilot frequency: 32,768 kHz Control elements: Power switch, level control, frequency selector switch Status LED: Power Connections: Input: microphone via 1 x mini XLR (M) 3-pin mounting version 1 V Input: AUX via 1 x 3.5 mm jack (stereo) 3,5 V Switch: On/off switch Material: Plastic | Power supply: | 5V DC |
|---|----------------------|---|
| included Battery/battery pack Battery: 2 x Mignon (AA) included S/N ratio: >90 dB Range: Range up to 50m Frequency band: UHF 823 - 832 MHz Frequency stability: ± 0,01 % RF power output: 10 mW Modulation: FM Frequency selection: 16 switchable frequencies Pilot frequency: 32,768 kHz Control elements: Power switch, level control, frequency selector switch Status LED: Power Connections: Input: microphone via 1 x mini XLR (M) 3-pin mounting version 1 V Input: AUX via 1 x 3.5 mm jack (stereo) 3,5 V Switch: On/off switch | | 3V DC |
| Battery:2 x Mignon (AA) includedSAttery:2 x Mignon (AA) includedS/N ratio:>90 dBRange:Range up to 50mFrequency band:UHF 823 - 832 MHzFrequency stability:± 0,01 %RF power output:10 mWModulation:FMFrequency selection:16 switchable frequenciesPilot frequency:32,768 kHzControl elements:Power switch, level control, frequency selector switchStatus LED:PowerConnections:Input: microphone via 1 x mini XLR (M) 3-pin mounting version 1 V Input: AUX via 1 x 3.5 mm jack (stereo) 3,5 VSwitch:On/off switchMaterial:PlasticColor:Black | Power connection: | |
| S/N ratio: >90 dB Range: Range up to 50m Frequency band: UHF 823 - 832 MHz Frequency stability: ± 0,01 % RF power output: 10 mW Modulation: FM Frequency selection: 16 switchable frequencies Pilot frequency: 32,768 kHz Control elements: Power switch, level control, frequency selector switch Status LED: Power Connections: Input: microphone via 1 x mini XLR (M) 3-pin mounting version 1 V Input: AUX via 1 x 3.5 mm jack (stereo) 3,5 V Switch: On/off switch Material: Plastic Color: Black | | Battery/battery pack |
| Range:Range up to 50mFrequency band:UHF 823 - 832 MHzFrequency stability:± 0,01 %RF power output:10 mWModulation:FMFrequency selection:16 switchable frequenciesPilot frequency:32,768 kHzControl elements:Power switch, level control, frequency selector switchStatus LED:PowerConnections:Input: microphone via 1 x mini XLR (M) 3-pin mounting version 1 V Input: AUX via 1 x 3.5 mm jack (stereo) 3,5 VSwitch:On/off switchMaterial:PlasticColor:Black | Battery: | 2 x Mignon (AA) included |
| Frequency band: UHF 823 - 832 MHz Frequency stability: ± 0,01 % RF power output: 10 mW Modulation: FM Frequency selection: 16 switchable frequencies Pilot frequency: 32,768 kHz Control elements: Power switch, level control, frequency selector switch Status LED: Power Connections: Input: microphone via 1 x mini XLR (M) 3-pin mounting version 1 V Input: AUX via 1 x 3.5 mm jack (stereo) 3,5 V Switch: On/off switch Material: Plastic Color: Black | S/N ratio: | >90 dB |
| Frequency stability:± 0,01 %RF power output:10 mWModulation:FMFrequency selection:16 switchable frequenciesPilot frequency:32,768 kHzControl elements:Power switch, level control, frequency selector switchStatus LED:PowerConnections:Input: microphone via 1 x mini XLR (M) 3-pin mounting version 1 VInput: AUX via 1 x 3.5 mm jack (stereo) 3,5 VSwitch:On/off switchMaterial:PlasticColor:Black | Range: | Range up to 50m |
| RF power output: 10 mW Modulation: FM Frequency selection: 16 switchable frequencies Pilot frequency: 32,768 kHz Control elements: Power switch, level control, frequency selector switch Status LED: Power Connections: Input: microphone via 1 x mini XLR (M) 3-pin mounting version 1 V Input: AUX via 1 x 3.5 mm jack (stereo) 3,5 V Switch: On/off switch Material: Plastic Color: Black | Frequency band: | UHF 823 - 832 MHz |
| Modulation: FM Frequency selection: 16 switchable frequencies Pilot frequency: 32,768 kHz Control elements: Power switch, level control, frequency selector switch Status LED: Power Connections: Input: microphone via 1 x mini XLR (M) 3-pin mounting version 1 V Input: AUX via 1 x 3.5 mm jack (stereo) 3,5 V Switch: On/off switch Material: Plastic Color: Black | Frequency stability: | ± 0,01 % |
| Frequency selection: 16 switchable frequencies Pilot frequency: 32,768 kHz Control elements: Power switch, level control, frequency selector switch Status LED: Power Connections: Input: microphone via 1 x mini XLR (M) 3-pin mounting version 1 V Input: AUX via 1 x 3.5 mm jack (stereo) 3,5 V Switch: On/off switch Material: Plastic Color: Black | RF power output: | 10 mW |
| Pilot frequency: 32,768 kHz Control elements: Power switch, level control, frequency selector switch Status LED: Power Connections: Input: microphone via 1 x mini XLR (M) 3-pin mounting version 1 V Input: AUX via 1 x 3.5 mm jack (stereo) 3,5 V Switch: On/off switch Material: Plastic Color: Black | Modulation: | FM |
| Control elements: Power switch, level control, frequency selector switch Status LED: Power Connections: Input: microphone via 1 x mini XLR (M) 3-pin mounting version 1 V Input: AUX via 1 x 3.5 mm jack (stereo) 3,5 V Switch: On/off switch Material: Plastic Color: Black | Frequency selection: | 16 switchable frequencies |
| switch Status LED: Power Connections: Input: microphone via 1 x mini XLR (M) 3-pin mounting version 1 V Input: AUX via 1 x 3.5 mm jack (stereo) 3,5 V Switch: On/off switch Material: Plastic Color: Black | Pilot frequency: | 32,768 kHz |
| Connections: Input: microphone via 1 x mini XLR (M) 3-pin mounting version 1 V Input: AUX via 1 x 3.5 mm jack (stereo) 3,5 V Switch: On/off switch Material: Plastic Color: Black | Control elements: | |
| mounting version 1 V Input: AUX via 1 x 3.5 mm jack (stereo) 3,5 V Switch: On/off switch Material: Plastic Color: Black | Status LED: | Power |
| Switch: On/off switch Material: Plastic Color: Black | Connections: | |
| Material: Plastic Color: Black | | Input: AUX via 1 x 3.5 mm jack (stereo) 3,5 V |
| Color: Black | Switch: | On/off switch |
| | Material: | Plastic |
| Dimensions: Width: 6,7 cm | Color: | Black |
| | Dimensions: | Width: 6,7 cm |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo. Depth: 3,0 cm Height: 11,2 cm

0,20 kg

| Weight: | |
|---------|--|
|---------|--|

OMNITRONIC WMR-1M UHF-Receiver, mono

| Power supply: | 5V DC |
|----------------------|--|
| | 3V DC |
| Power connection: | Mains input via micro USB (F) mounting version included |
| | Battery/battery pack |
| Battery: | 2 x Mignon (AA) included |
| S/N ratio: | >80 dB |
| Range: | Range up to 50m |
| Frequency band: | UHF 823 - 832 MHz |
| Frequency stability: | ± 0,01 % |
| Modulation: | FM |
| Frequency selection: | 16 switchable frequencies |
| Pilot frequency: | 32,768 kHz |
| Connector type: | 3.5 mm jack (mono) mounting version |
| Control elements: | Level control, power switch, frequency selector switch |
| Status LED: | Signal, power |
| Connections: | Output: line via 1 x 3.5 mm jack (mono) mounting version 1 V |
| | Output: headphones via 1 x 3.5 mm jack (stereo) mounting version |
| Switch: | On/off switch |
| Material: | Plastic |
| Color: | Black |
| Dimensions: | Width: 6,7 cm |
| | Depth: 3,0 cm |
| | Height: 11,2 cm |
| Weight: | 0,21 kg |
| | |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.