

## EUROLITE AKKU Mobile Bundle

4 battery-powered spotlights incl. soft bag, DMX controller incl. flightcase and wireless DMX system

Art. No.: 2000668

GTIN: 4026397606607



**List price: 1724.31 €**

incl. 19% VAT.

### Features:

#### EUROLITE AKKU PAR 6 QCL

Battery-powered LED spotlight with RGBW color mixing, incl. IR remote control

- Battery operation up to 12h depending on program used
- 6 powerful LEDs 4 W high-power 4in1 QCL RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable
- Strobe effect
- Direct color selection for 25 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); IR remote control
- Flicker-free
- With a beam angle of 18°
- With double bracket
- 4 digit 7-segment LED display
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; Stage
- Mains input and output for power linking up to 8 units
- Cordless, flexible and versatile
- Integrated automatic charging of the battery and status indicator
- Preprogrammed in Light J; LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
- Silent operation
- Application possibility: Standing; suspended; on stand

#### Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x xLR cable, 1 x remote control, 1 x battery

### Logistic

EAN / GTIN: 4026397606607

Weight: 20,50 kg

Length: 0.60 m

Width: 0.80 m

Height: 1.00 m

Bulky product

### **EUROLITE QuickDMX USB Wireless Transmitter/Receiver**

Wireless miniature DMX transceiver 2.4 GHz, phantom powered

- User-friendly USB plug with swivel antenna
- Wireless DMX eliminates extensive cabling between DMX controller and the DMX-controlled units in lighting installations
- Due to GFSK modulation with 78 channels, interference-free operation also alongside other QuickDMX transceiver and wireless devices in the 2.4 GHz band (e.g. Wi-Fi and Bluetooth)
- LED indication for functions
- Transceiver, to be used as transmitter or receiver
- Requires 5 V phantom power for operation
- Can receive and process up to 512 DMX channels
- Can transmit up to 512 DMX channels
- Control via DMX; QuickDMX; plug and play
- Operating range up to 400m with line-of-sight
- Up to 6 transmitters can be operated in parallel without interference

#### **Package contents**

- 1 x device, 1 x user manual, 1 x declaration of conformity

### **EUROLITE QuickDMX Wireless Transmitter/Receiver**

Wireless DMX system 2.4 GHz

- Auto-switching transceiver
- Wireless DMX eliminates extensive cabling between DMX controller and the DMX-controlled units in lighting installations
- Due to GFSK modulation with 78 channels, interference-free operation also alongside other QuickDMX transceiver and wireless devices in the 2.4 GHz band (e.g. Wi-Fi and Bluetooth)
- 1 to 512 QuickDMX receivers can be controlled by each transmitter
- LED indication for functions
- Can receive and process up to 512 DMX channels
- Can transmit up to 512 DMX channels
- Control via DMX; QuickDMX; plug and play
- Operating range up to 400m
- Up to 6 transmitters can be operated in parallel without interference

#### **Package contents**

- 1 x device, 1 x user manual, 1 x external mains adapter, 1 x USB cable, 1 x antenna, 1 x declaration of conformity

### **EUROLITE SB-4 Soft Bag L**

Black soft bag for up to 4 devices, 320 x 320 x 200 mm

- Practical transport bag offers enough space for several lighting effects and accessories
- With Dividers
- With 2 Outside pockets
- With 4 Device compartments
- High-quality workmanship with nylon, black, water repellent
- Interior with foam padding<BR>cover with foam padding
- 2 carrying straps

#### **Package contents**

- 1 x bag

### **EUROLITE DMX LED Color Chief Controller**

DMX lighting desk with innovative control concept for LED spotlights

- Easy control of LED spotlights with up to 6 colors, light bars as well as simple lighting effects
- For 8 devices or device groups, each with up to 4 segments
- Quick and easy programming
- Additional fixtures can be configured manually
- 8 color effects directly selectable
- 3 additional channels available per fixture (e.g. for rotations)
- Color wheel selection and simulation
- 24 memory spaces for scenes and chases
- Several chases and scenes can be run simultaneously

- USB port for storing program data
  - Sound control via audio signal or TAP button
  - Master dimming, fade time and run time easily adjustable
  - Programmable 24 scenes/chases distributed over 1 page(s )
  - Can transmit up to 240 DMX channels
  - Control via DMX; Sound to light via RCA (F) mounting version; Sound to light via Microphone
  - (19") 48.3 cm rack installation 3 U
  - Desktop console housing
  - For application areas such as: Clubs/dancing school; Party room; Trade fair and shop fitting; mobile djs / entertainer; restaurants, bars and hotels
  - Silent operation
  - Firmware can be updated
- Package contents**
- 1 x controller, 1 x user manual, 1 x external mains adapter

### ROADINGER Mixer Case Pro MCA-19, 4U, bk

#### Rack case

- Upward tilted profile rails for top-operated units
- High-quality workmanship with plywood multi-layer glued 7 mm, black, laminated
- Interior with foam padding
- Removable cover
- Aluminum profile frames 30mm with rounded edges
- Rugged carrying handle
- 2 high-quality butterfly locks with shut-off function
- Rubber feet
- With profile rails suitable for 19" units
- 4 U
- For further information about this product, please refer to the Data Sheet under "Downloads"

### Technical specifications:

---

Weight: 18,69 kg

---

### EUROLITE AKKU PAR 6 QCL

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Battery/battery pack Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version
Battery pack type:	1 x lithium ion 14,8 V, 4400 mAh, 65,12 Wh
Battery pack:	Battery operation up to 12h depending on program used Recharging time 3,5h
Lamp type:	LED lamp
LED:	6 x 4 W high-power 4in1 QCL RGBW (homogenous color mix)
DMX channels:	6; 11
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version

Cooling:	Passive convection cooling
Control:	DMX; stand-alone; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); IR remote control
Preprogrammed in:	Light J; LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
Projection:	Flicker-free
Beam angle:	18°
Beam angle (1/2 peak):	18°
Beam angle (1/10 peak):	36°
Housing color:	Black
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 17,7 cm Depth: 14,3 cm Height: 21,1 cm
Weight:	2,52 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### **EUROLITE QuickDMX USB Wireless Transmitter/Receiver**

Power supply:	5 V DC
IP classification:	IP20
Power connection:	Mains input via USB A (M) connectable version
DMX channels:	Input 512 Output 512
DMX output:	1 x USB, type A
Control:	DMX; QuickDMX; plug and play
Range:	Range up to 400m with line-of-sight
Carrier frequency:	2,4 GHz
Parallel mode:	Max. 6 transmitter
Modulation:	GFSK
Color:	Black
Dimensions:	Width: 8,6 cm Depth: 4 cm Height: 1,1 cm
Weight:	10 g

### **EUROLITE QuickDMX Wireless Transmitter/Receiver**

Power supply:	100-240 V AC, 50/60 Hz 5 V DC 500 mA
IP classification:	IP20
Power connection:	Mains input via USB C (W) mounting version power supply cord for USB A mains connection (provided)
DMX channels:	Input 512 Output 512
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	DMX; QuickDMX; plug and play
Range:	Range up to 400m
Carrier frequency:	2,4 GHz
Parallel mode:	Max. 6 transmitter
Modulation:	GFSK
Color:	Black
Dimensions:	Width: 21,2 cm Depth: 10 cm Height: 7,5 cm
Weight:	290 g

### **EUROLITE SB-4 Soft Bag L**

Maximum load:	25 kg
Carrying strap:	2 pc/pcs
Material:	Nylon
Color:	Black, water repellent
Compartment dimensions:	15 cm x 15 cm x 20 cm
Inside dimensions:	31 cm x 34 cm x 20 cm
Dimensions:	Width: 32 cm Depth: 41 cm Height: 20 cm
Weight:	520 g

### **EUROLITE DMX LED Color Chief Controller**

Power supply:	100-240 V AC, 50/60 Hz 9 V DC 800 mA
Power consumption:	10 W
IP classification:	IP20
Power connection:	Mains input via Coaxial power connector (M) mounting version power supply cord with AC adapter (provided)

Programs:	Programmable 24 scenes/chases distributed over 1 page(s)
DMX channels:	Output 240
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	DMX; Sound to light via RCA (F) mounting version; Sound to light via Microphone
Housing color:	Black
Available storage media:	USB devices (FAT 32)
USB port:	Typ A
Color:	Black
PC connect:	, firmware can be updated
Housing design:	(19") 48.3 cm rack installation 3 U Desktop console housing
Dimensions:	Width: 48,3 cm Depth: 13,35 cm Height: 8,5 cm
Weight:	2,25 kg
Noise classification:	Class 0 (no noise at all)

#### **ROADINGER Mixer Case Pro MCA-19, 4U, bk**

Maximum load:	25 kg
Removable covers:	1 pc/pcs
Aluminum profile frames:	30 mm
Carrying handle:	1 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs with shut-off function
Transport aid:	Rubber feet
Material:	Plywood multi-layer glued, 7 mm
Color:	Black, laminated; dark brown, laminated
Inside dimensions:	44,6 cm x 23,8 cm x 10,5 cm
Front panel width:	19"
Mounting height:	Approx. 18 cm (4 U)
Mounting depth:	105 mm
Housing design:	4 U
Dimensions:	Width: 54 cm Depth: 27 cm Height: 23,5 cm
Weight:	5,50 kg