

## EUROLITE Set LED IP PAR 7x8W QCL Spot + 2x Diffuser cover (15x60° and 40°): 2000670

Weather-proof spotlight with 7 QCL LEDs and RGBW color mixing incl. 2x diffuser cover

GTIN: 4026397362312



**List price: 320.11 €**

incl. 19% VAT.

### Features:

#### EUROLITE LED IP PAR 7x8W QCL spot

Weather-proof (IP65) spotlight with 7 x 8 W LED and 4in1 QCL RGBW color mixing

- 7 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Direct color selection for 25 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; IR remote control
- Flicker-free
- With a beam angle of 15°
- With double bracket
- LCD display
- Suitable for outdoor use IP65
- Silent operation
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
- Mains input and output for power linking up to 8 units
- With pressure compensation membrane
- For application areas such as: Installation; Stage; Rental; architecture
- Application possibility: Standing; suspended; on stand

#### Package contents

- 1 x device, 1 x power cord, 1 x remote control, 1 x battery, 1 x user manual

### Logistic

EAN / GTIN: 4026397362312

Weight: 5,20 kg

Length: 0.41 m

Width: 0.31 m

Height: 0.28 m

## EUROLITE Diffuser Cover 15x60° for IP PAR-7<p class='attributgroup'>Package contents

- 1 x diffusor cover

## EUROLITE Diffuser Cover 40° for IP PAR-7<p class='attributgroup'>Package contents

- 1 x diffusor cover

### Technical specifications:

---

Weight: 4,27 kg

---

### EUROLITE LED IP PAR 7x8W QCL spot

|                        |  |
|------------------------|--|
| Power supply:          | 100-240 V AC, 50/60 Hz   |
| Power consumption:     | 55 W   |
| IP classification:     | IP65   |
| Power connection:      | Mains input via IP T-Con (M) mounting version power supply cord with safety plug   |
| Power output:          | IP T-Con (F) mounting version  |
| Lamp type:             | LED lamp   |
| LED:                   | 7 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)  |
| Flash rate:            | 0 - 20 Hz  |
| DMX channels:          | 3; 4; 5; 6; 10   |
| DMX input:             | 1 x 3-pin XLR (M) mounting version IP  |
| DMX output:            | 1 x 3-pin XLR (F) mounting version IP  |
| Cooling:               | Passive convection cooling   |
| Control:               | DMX; stand-alone; IR remote control  |
| Preprogrammed in:      | LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3 |
| Projection:            | Flicker-free   |
| Beam angle:            | 15°  |
| Beam angle (1/2 peak): | 15°  |
| Housing color:         | Black  |
| Attachment system:     | Double bracket   |
| Display type:          | LCD display  |
| Material:              | Aluminum casting   |
| Dimensions:            | Width: 25,5 cm<br>Depth: 15,3 cm<br>Height: 28,1 cm  |
| Weight:                | 4,07 kg  |

|                          |   |
|--------------------------|---|
| Noise classification:    | Class 0 (no noise at all)                               |
| Photobiological safety:  | Risk Group 0  |
| Power cord               |   |
| Cable construction:      | 3 x 1,0 mm <sup>2</sup> H05RN-F                         |
| Cable length:            | Approx. 1,2 m   |
| Mounting bracket         |   |
| Diameter mounting holes: | 3 x Ø11mm   |
| Material:                | Metal, 2,5 mm   |
| Remote control           |   |
| Battery:                 | 1 x Button cell 3.0 V CR2025 lithium manganese built-in |
| Legal specifications     |   |
| Special product:         | Not designed for household room illumination            |
| Intended use:            | Show effect lighting                                    |

#### **EUROLITE Diffuser Cover 15x60° for IP PAR-7**

|             |  |
|-------------|--|
| Dimensions: | Height: 6,5 mm<br>Diameter: Ø 18,50 cm |
| Weight:     | 100 g                                  |

#### **EUROLITE Diffuser Cover 40° for IP PAR-7**

|             |  |
|-------------|--|
| Dimensions: | Height: 6,5 mm<br>Diameter: Ø 18,50 cm |
| Weight:     | 100 g                                  |