

## EUROLITE Set LED IP PAR 12x9W SCL Spot + 2x Diffuser cover (15x60° and 40°) 20000673

Weather-proof spotlight with 12 SCL-LEDs and RGBA/CW/WW+UV color mixing incl. 2x diffuser cover GTIN: 4026397362343



**List price: 593.81 €**

incl. 19% VAT.

### Features:

#### EUROLITE LED IP PAR 12x9W SCL Spot

Weather-proof (IP65) spotlight with 12 x 9 W LED and 7in1 SCL RGB/CW/WW/A/UV color mixing

- 12 powerful LEDs 9 W COB (chip-on-board) 7in1 SCL RGB/CW/WW/A/UV (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Direct color selection for 28 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; IR remote control; stand-alone
- Flicker-free
- With a beam angle of 15°
- With double bracket
- LCD display
- Suitable for outdoor use IP65
- Silent operation
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
- Mains input and output for power linking up to 8 units
- With pressure compensation membrane
- For application areas such as: Installation; Stage; Rental; architecture
- Application possibility: Standing; suspended; on stand

#### Package contents

- 1 x device, 1 x power cord, 1 x remote control, 1 x battery, 1 x user manual

### Logistic

EAN / GTIN: 4026397362343

Weight: 6,60 kg

Length: 0.41 m

Width: 0.31 m

Height: 0.28 m

## EUROLITE Diffuser Cover 15x60° for IP PAR-12<p class='attributgroup'>Package contents

- 1 x diffusor cover

## EUROLITE Diffuser Cover 40° for IP PAR-12<p class='attributgroup'>Package contents

- 1 x diffusor cover

### Technical specifications:

---

Weight: 5,43 kg

---

### EUROLITE LED IP PAR 12x9W SCL Spot

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	75 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Power output:	IP T-Con (F) mounting version
Lamp type:	LED lamp
LED:	12 x 9 W COB (chip-on-board) 7in1 SCL RGB/CW/WW/A/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 5; 7; 9; 13
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	DMX; IR remote control; stand-alone
Preprogrammed in:	LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	15°
Beam angle (1/2 peak):	15°
Beam angle (1/10 peak):	29°
Housing color:	Black
Attachment system:	Double bracket
Display type:	LCD display
Material:	Aluminum casting
Dimensions:	Width: 28,5 cm Depth: 15,3 cm Height: 31,35 cm

---

Weight:	5,20 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Power cord	
Cable construction:	3 x 1,0 mm <sup>2</sup> H05RN-F
Cable length:	Approx. 1,2 m
Mounting bracket	
Diameter mounting holes:	3 x Ø11mm
Material:	Metal, 2,5 mm
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### **EUROLITE Diffuser Cover 15x60° for IP PAR-12**

Dimensions:	Height: 7 mm Diameter: Ø 22,20 cm
Weight:	110 g

#### **EUROLITE Diffuser Cover 40° for IP PAR-12**

Dimensions:	Height: 6,5 mm Diameter: Ø 22,20 cm
Weight:	120 g