

EUROLITE Set 4x LED IP Tourlight 120 WW + Case

4x weather-proof LED spot with warm white 100 W LED including PRO flightcase

Art. No.: 2000675

GTIN: 4026397360424



List price: 2378.81 €

incl. 19% VAT.

Features:

EUROLITE LED IP Tourlight 120 WW

Weather-proof LED spotlight (IP65) with warm white 100 W LED, CRI >95

- Ideal for architectural and front lighting at open air events
- 1 powerful LED 100 W COB (chip-on-board) warm white (WW)
- The device is cooled by temperature-controlled fan
- Control via DMX; Master/slave function
- Flicker-free
- With a beam angle of 12°
- Very high color rendering index (CRI)
- With Omega bracket; with double bracket
- Suitable for outdoor use IP65
- Exact 16 bit resolution at Dimmer
- Dimmer curves with adjustable response; Dimmer speed (step response) adjustable
- Strobe effect
- Preprogrammed in LED PC-Control 512; Light Captain
- Mains input and output for power linking up to 8 units
- For application areas such as: Installation; Stage; theater; architecture
- Silent operation
- Application possibility: Standing; suspended; on stand

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x omega bracket, 1 x cover

Logistic

EAN / GTIN: 4026397360424

ROADINGER Flightcase 4x LED IP Tourlight 120

Trunk case, PRO version

- For optimal security
- With accessory compartment
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Branded hardware
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 36,25 kg

EUROLITE LED IP Tourlight 120 WW

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	110 W
IP classification:	IP65
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IP T-Con (F) mounting version
Lamp type:	LED lamp
LED:	1 x 100 W COB (chip-on-board) warm white (WW)
Color temperature:	3200K
Flash rate:	1 - 20 Hz
DMX channels:	1; 3
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Cooling:	Temperature-controlled fan
Control:	DMX; Master/slave function
Preprogrammed in:	LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle:	12°
Beam angle (1/2 peak):	12°
Beam angle (1/10 peak):	26°
Color rendering index (CRI):	96 Ra
Housing color:	Black
Attachment system:	Omega bracket Double bracket
Dimensions:	Width: 27 cm Depth: 27 cm Height: 30,5 cm
Weight:	5,90 kg
Noise classification:	Class 0 (no noise at all)

Legal specifications

Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x LED IP Tourlight 120

Maximum load:	50 kg
Aluminum profile frames:	30 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Device compartment:	28 cm x 19 cm x 30,5 cm
Middle compartment:	10,5 cm x 41 cm x 30,5 cm
Inside dimensions:	66,5 cm x 41 cm x 30,5 cm
Dimensions:	Width: 74 cm Depth: 40 cm Height: 45 cm
Weight:	12,65 kg
