

EUROLITE Set 4x Multiflood Pro IP SMD RGBW Strobe/Wash + Case

4x weather-proof 3in1 LED effect light with RGBW color mixing incl. PRO flightcase

Art. No.: 2000678

GTIN: 4026397360936



List price: 5234.81 €

incl. 19% VAT.

Features:

EUROLITE Multiflood Pro IP SMD RGBW Strobe/Wash

Weather-proof (IP65) 3in1 LED effect light with RGBW color mixing

- 1320 powerful LEDs 0,4 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
6 segments controlled separately
- 36 integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; Sound to light
- With Mounting bracket; with Omega bracket
- Monochrome LCD display
- Suitable for outdoor use IP65
- Dimmer curves adjustable; color blend stepless; Dimmer electronic
- Strobe effect; Wash effect; Blinder effect
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
- With pressure compensation membrane
- For application areas such as: Stage; Rental; architecture
- Application possibility: Standing; suspended
- For further information about this product, please refer to the Data Sheet under "Downloads"

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 2 x omega bracket, 1 x xLR cable

ROADINGER Flightcase 4x Multiflood Pro

Trunk case with castors, PRO version

Logistic

EAN / GTIN: 4026397360936

- With 4 Device compartments
- High-quality workmanship with birch multiplex 7 mm, black, laminated
- Interior with foam padding
- Cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 high-quality butterfly locks
- 4 castors with 2 locking brakes
- Branded hardware

Technical specifications:

Weight: 75,15 kg

EUROLITE Multiflood Pro IP SMD RGBW Strobe/Wash

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	315 W
IP classification:	IP65
Protection class:	Protection class I
Lamp type:	LED lamp
LED:	1320 x 0,4 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	4; 5; 7; 13; 15; 31
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Cooling fan
Control:	Stand-alone; DMX; Sound to light
Preprogrammed in:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
Beam angle (1/2 peak):	120°
Attachment system:	Mounting bracket 2x Omega bracket
Display type:	Monochrome LCD display
Dimensions:	Width: 49 cm Depth: 16 cm Height: 28,5 cm
Weight:	13,70 kg
Noise classification:	Class 4 (loud noises)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x Multiflood Pro

Maximum load:	60 kg
Aluminum profile frames:	30 mm
Case handle:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm; birch multiplex
Color:	Black, laminated; dark brown, laminated
Device compartment:	16 cm x 32,5 cm x 51 cm
Middle compartment:	10 cm x 34 cm x 51 cm
Inside dimensions:	74 cm x 34 cm x 51 cm
Dimensions:	Length: 89 cm Width: 38 cm Height: 72,5 cm
Weight:	20,35 kg