

EUROLITE Set 4x Multiflood Pro IP SMD RGBW Strobe/Wash + Case

4x weather-proof 3in1 LED effect light with RGBW color mixing incl. PRO flightcase

Art. No.: 20000678

GTIN: 4026397360936



Features:

- 1320 LEDs 0.4 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
6 segments controlled separately
- Dimmer curves adjustable; color blend stepless; Dimmer electronic
- Strobe effect; wash effect; Blinder effect
- 36 integrated show programs
- Direct color selection for 16 preset colors
- The device is cooled by cooling fan
- Control via stand-alone; DMX
- Fixtures available for LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
- With mounting bracket; with omega bracket
- Monochrome LCD display
- Suitable for outdoor use IP65
- With pressure compensation membrane
- For application areas such as: Architecture; stage; clubs/dancing school; rental
- Application possibility: Standing; suspended
- <p>ROADINGER Flightcase 4x Multiflood Pro
- <h2 class="featureSatz">Trunk case with castors, HIGHLINE version</h2>With 4 device compartments
- High-quality workmanship with birch multiplex 9.8 mm, black, laminated
- Interior with foam padding
- Cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 4 chrome tip-over locks

Logistic

EAN / GTIN: 4026397360936

- 2 high-quality butterfly locks
- 4 x castors with 2 locking brakes
- Branded hardware
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	90.15 kg
---------	----------

EUROLITE Multiflood Pro IP SMD RGBW Strobe/Wash

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	315 W
IP classification:	IP65
Protection class:	Protection class I
Lamp type:	LED lamp
LED type:	1320 x 0.4 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	4; 5; 7; 13; 15; 31
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Cooling fan
Control:	Stand-alone; DMX
Fixtures available for:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
Beam angle (1/2 peak):	120°
Attachment system:	Mounting bracket 2x omega bracket
Display type:	Monochrome LCD display
Dimensions:	Width: 49 cm Depth: 16 cm Height: 28.5 cm
Weight:	13.70 kg
Noise classification:	Class 4 (loud noises)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x Multiflood Pro

Maximum load:	100 kg
Aluminum profile frames:	30 mm
Case handle:	4 pc/pcs
Stop hinge:	4 pc/pcs

Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes
Use of brands:	Branded hardware
Material:	Birch multiplex, 9.8 mm; birch multiplex
Color:	Black, laminated; dark brown, laminated
Device compartment:	21.5 cm x 55.5 cm x 28 cm
Accessory compartment:	11.5 cm x 53.5 cm x 28 cm
Inside dimensions:	105.5 cm x 56 cm x 37 cm
Dimensions:	Width: 110 cm
	Depth: 61 cm
	Height: 53 cm
Weight:	35.35 kg

Scope of delivery:

- 1 x spotlight
- 1 x user manual
- 1 x power cord
- 2 x omega bracket
- 1 x XLR cable