

## EUROLITE Set 4x LED Super Strobe ABL + Case

4x 3in1 LED effect light with RGB color mixing including PRO flightcase

Art. No.: 2000679

GTIN: 4026397360943



**List price: 1724.31 €**

incl. 19% VAT.

### Features:

#### EUROLITE LED Super Strobe ABL

LED lighting effect with threefold effects

- Flat metal housing with integrated wall holders
- 216 powerful LEDs 0,5 W SMD 5730 cold white (CW)
- 144 powerful LEDs SMD 5050 3in1 TCL RGB (homogenous color mix) <BR> LEDs controlled separately
- Strobe effect; Wash effect; Blinder effect
- 17 integrated show programs
- Control via Master/slave function; DMX; stand-alone; Sound to light
- Flicker-free
- With Mounting bracket
- 4 digit 7-segment LED display
- Dimmer electronic; color blend stepless
- Mains input and output for power linking up to 8 units
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; Light Captain
- For application areas such as: Clubs/dancing school; Stage; restaurants, bars and hotels; mobile djs / entertainer
- Very quiet working noise
- Application possibility: Suspended; on stand

#### Package contents

- 1 x light effect, 1 x mounting bracket, 1 x power cord, 2 x knurled screw, 2 x washer, 1 x user manual

### Logistic

EAN / GTIN: 4026397360943

Weight: 27,40 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

### ROADINGER Flightcase 4x LED Super Strobe

Trunk case, PRO version

- For optimal security
- With accessory compartment
- High-quality workmanship with birch multiplex 7 mm, black, laminated
- Interior with felt cover
- Aluminum profile frames 30mm with rounded edges
- 3 hinged, chromium plated case handles
- 3 chrome tip-over locks
- 2 high-quality butterfly locks
- Rubber feet
- Branded hardware
- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

---

Weight: 30,89 kg

---

### EUROLITE LED Super Strobe ABL

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	95 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, F 2 A Fuse replaceable
LED:	216 x 0,5 W SMD 5730 cold white (CW) 144 x SMD 5050 3in1 TCL RGB (homogenous color mix)
DMX channels:	7; 13; 22; 148
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	Master/slave function; DMX; stand-alone; Sound to light
Preprogrammed in:	LED PC-Control 512; EASY SHOW 1; Light Captain
Projection:	Flicker-free
Beam angle (1/2 peak):	120°
Illuminance in Lux (lx):	Red (R) 1m: 29 lx, 3m: 5 lx, 6m: 2 lx Green (G) 1m: 66 lx, 3m: 12 lx, 6m: 4 lx Blue (B) 1m: 15 lx, 3m: 3 lx, 6m: 1 lx Cold white (CW) 1m: 1627 lx, 3m: 246 lx, 6m: 71 lx All 1m: 1683 lx, 3m: 252 lx, 6m: 72 lx
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Diameter mounting holes:	2 x Ø5mm; 6 x Ø9mm
Dimensions:	Width: 45,5 cm Depth: 8,5 cm

	Height: 25,5 cm
Weight:	4,26 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Power cord	
Cable construction:	3 x 1,0 mm <sup>2</sup> H05RN-F
Cable length:	Approx. 1,5 m
Mounting bracket	
Diameter mounting holes:	3 x Ø11mm; 2 x Ø8mm
Material:	Metal, 2 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

### **ROADINGER Flightcase 4x LED Super Strobe**

Maximum load:	50 kg
Aluminum profile frames:	30 mm
Case handle:	3 pc/pcs
Stop hinge:	3 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	Rubber feet
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Black, laminated; dark brown, laminated
Inside dimensions:	60 cm x 40,5 cm x 31 cm
Device compartment:	9 cm x 47 cm x 31 cm
Accessory compartment:	12 cm x 40 cm x 31 cm
Dimensions:	Width: 64,5 cm Depth: 45 cm Height: 34,5 cm
Weight:	13,85 kg