

EUROLITE Set 2x LED THA-150F + Case

2x fresnel spot with 170 W warm white/amber LED including PRO flightcase

Art. No.: 20000680

GTIN: 4026397360950



List price: 2259.81 €

incl. 19% VAT.

Features:

EUROLITE LED THA-150F Theater Spot

Fresnel spotlight, dim to warm, 170 W warm white/amber LED, CRI >90, quiet, DMX

- New LED technology that simulates the color temperature curve of a halogen lamp when dimming
- Rugged metal housing
- 1 powerful LED 170 W COB (chip-on-board) Dim to warm (homogenous color mix)
- Exact 16 bit resolution at Dimmer
- Zoom motor driven
- Color blend stepless; Dimmer electronic; Dimmer speed (step response) adjustable; dimmer curves adjustable
- Strobe effect
- The device is cooled by temperature-controlled fan
- Control via RDM; DMX
- Preprogrammed in Light'J; Light Captain
- Flicker-free
- With a beam angle of 8° - 55°
- Very high color rendering index (CRI)
- With mounting bracket
- LCD display
- Rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Trade fair and shop fitting; installation; stage; theater
- Application possibility: Suspended; on stand

Package contents

- 1 x spotlight, 1 x power cord, 1 x barn door, 1 x filter frame, 1 x user manual

Logistic

EAN / GTIN: 4026397360950

Weight: 40,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.45 m

Bulky product

ROADINGER Flightcase 2x LED THA-150F Theater Spot

Trunk case, PRO version

- With accessory compartment
- With 2 device compartments
- 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Branded hardware

Technical specifications:

Weight:	31,90 kg
---------	----------

EUROLITE LED THA-150F Theater Spot

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	150 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug included
Power output:	P-Con (gray), mounting version
LED type:	1 x 170 W COB (chip-on-board) Dim to warm (homogenous color mix)
Equipment:	Zoom motor driven
DMX channels:	2; 6; 7
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	RDM; DMX
Preprogrammed in:	Light J; Light Captain
Projection:	Flicker-free
Beam angle:	8° - 55°
Beam angle (1/2 peak):	8 - 39°
Beam angle (1/10 peak):	12 - 55°
Color rendering index (CRI):	96 Ra
Luminous flux:	5093 lm
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display

Transport aid:	Rubber feet
Material:	Aluminum casting; metal
Slot for spot length:	20 cm x 20 cm
Dimensions:	Length: 45,7 cm Width: 33,6 cm Height: 39,8 cm
Weight:	9,40 kg
Noise classification:	Class 2 (slight noise)
Energy efficiency class (A - G):	G
EPREL-Nr:	1243870
Mounting bracket	
Diameter mounting holes:	5 x Ø10mm
Material:	Aluminum casting, 6,5 mm
Power cord	
Cable construction:	3 x 1,5 mm² H05VV-F
Cable length:	Approx. 1,3 m
Barndoor	
Material:	Aluminum, 1,5 mm; metal, 1 mm
Ring diameter:	Outside: 198 mm Inside: 220 mm
Dimensions:	Width: 50,5 cm Depth: 4,2 cm Height: 50,5 cm
Filter frame	
Material:	Aluminum, 1 mm
Dimensions:	Width: 22,5 cm Height: 22,5 cm Diameter: Ø 18 cm

ROADINGER Flightcase 2x LED THA-150F Theater Spot

Maximum load:	50 kg
Aluminum profile frames:	25 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Use of brands:	Branded hardware
Color:	Dark brown, laminated
Device compartment:	38,5 cm x 40 cm x 23 cm
Accessory compartment:	10 cm x 48 cm x 23 cm
Inside dimensions:	87 cm x 48 cm x 23 cm
Material thickness:	7 mm
Dimensions:	Width: 92 cm Depth: 37 cm Height: 52 cm
Weight:	13,10 kg