

EUROLITE Set 2x LED THA-150F + Case

2x fresnel spot with 170 W warm white/amber LED including PRO flightcase

Art. No.: 2000680

GTIN: 4026397360950



List price: 2259.81 €

incl. 19% VAT.

Features:

EUROLITE LED THA-150F Theater-Spot

Fresnel spotlight, dim to warm, 170 W warm white/amber LED, CRI >90, quiet, DMX

- New LED technology that simulates the color temperature curve of a halogen lamp when dimming
- Rugged metal housing
- 1 powerful LED 170 W COB (chip-on-board) Dim to warm (homogenous color mix)
- Zoom motor-driven
- The device is cooled by temperature-controlled fan
- Control via RDM; DMX
- Flicker-free
- With a beam angle of 8° - 55°
- Very high color rendering index (CRI)
- With Mounting bracket
- LCD display
- Exact 16 bit resolution at Dimmer
- Color blend stepless; Dimmer electronic; Dimmer speed (step response) adjustable; dimmer curves adjustable
- Strobe effect
- Preprogrammed in Light´J; Light Captain
- Rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Trade fair and shop fitting; Installation; Stage; theater
- Application possibility: Suspended; on stand

Package contents

- 1 x spotlight, 1 x power cord, 1 x barndoor, 1 x filter frame, 1 x user manual

Logistic

EAN / GTIN: 4026397360950

Weight: 40,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.45 m

Bulky product

ROADINGER Flightcase 2x LED THA-150F Theater-Spot

Trunk case, PRO version

- With accessory compartment
- With 2 Device compartments
- 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Branded hardware

Technical specifications:

Weight: 31,90 kg

EUROLITE LED THA-150F Theater-Spot

| | |
|------------------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 150 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug included |
| Power output: | P-Con (gray), mounting version |
| LED: | 1 x 170 W COB (chip-on-board) Dim to warm (homogenous color mix) |
| Equipment: | Zoom motor-driven |
| DMX channels: | 2; 6; 7 |
| DMX input: | 1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version |
| Cooling: | Temperature-controlled fan |
| Control: | RDM; DMX |
| Preprogrammed in: | Light J; Light Captain |
| Projection: | Flicker-free |
| Beam angle: | 8° - 55° |
| Beam angle (1/2 peak): | 8 - 39° |
| Beam angle (1/10 peak): | 12 - 55° |
| Color rendering index (CRI): | 96 Ra |
| Luminous flux: | 5093 lm |
| Housing color: | Black |
| Attachment system: | Mounting bracket |
| Display type: | LCD display |

| | |
|----------------------------------|--|
| Transport aid: | Rubber feet |
| Material: | Aluminum casting; metal |
| Slot for spot length: | 20 cm x 20 cm |
| Dimensions: | Length: 45,7 cm Width: 33,6 cm Height: 39,8 cm |
| Weight: | 9,40 kg |
| Noise classification: | Class 2 (slight noise) |
| Energy efficiency class (A - G): | G |
| Power cord | |
| Cable construction: | 3 x 1,5 mm ² H05VV-F |
| Cable length: | Approx. 1,3 m |
| Mounting bracket | |
| Diameter mounting holes: | 5 x Ø10mm |
| Material: | Aluminum casting, 6,5 mm |
| Barndoor | |
| Material: | Aluminum, 1,5 mm; metal, 1 mm |
| Ring diameter: | Outside: 198 mm Inside: 220 mm |
| Dimensions: | Width: 50,5 cm Depth: 4,2 cm Height: 50,5 cm |
| Filter frame | |
| Material: | Aluminum, 1 mm |
| Dimensions: | Width: 22,5 cm Height: 22,5 cm Diameter: Ø 18 cm |

ROADINGER Flightcase 2x LED THA-150F Theater-Spot

| | |
|--------------------------|---|
| Maximum load: | 50 kg |
| Aluminum profile frames: | 25 mm |
| Case handle: | 2 pc/pcs |
| Stop hinge: | 2 pc/pcs |
| Lock: | Butterfly lock: 2 pc/pcs |
| Use of brands: | Branded hardware |
| Color: | Dark brown, laminated |
| Device compartment: | 38,5 cm x 40 cm x 23 cm |
| Accessory compartment: | 10 cm x 48 cm x 23 cm |
| Inside dimensions: | 87 cm x 48 cm x 23 cm |
| Material thickness: | 7 mm |
| Dimensions: | Width: 92 cm Depth: 37 cm Height: 52 cm |
| Weight: | 13,10 kg |