

# EUROLITE Set 4x PAR-16 Spot bk dim2warm + EDX-4 DMX RDM LED Dimmer pack000694

GTIN: 4026397366587



**List price: 320.11 €** 

incl. 19% VAT.

## Features:

## **EUROLITE PAR-16 Spot GU-10 black**

PAR-16 housing with GU10 socket (with plug + cable)

- Mini-spot for GU-10 lamp
- Color-filters attachable
- Control via plug and play
- For PAR 16

#### Package contents

1 x spotlight, 1 x filter frame, 1 x user manual

#### OMNILUX GU-10 230V COB 5W LED 1800-3000K dim2warm

LED lamp with modern dim-to-warm feature

- Dimming behavior comparable with incandescent and halogen lamps (dim-to-warm)
- Changes the light color from 3000 K (warm white) to 1800 K (extra warm white) when dimming
- Creates particularly cosy atmospheres
- Easy lamp replacement
- Energy-saving
- Dimmable
- Variable color temperature 1800 K 3000 K
- Easy installation
- With a beam angle of 24°
- Very high color rendering index (CRI)

#### **EUROLITE EDX-4 DMX RDM LED Dimmer Pack**

4-channel dimmer for LED lights with 230 V operation

## Logistic

EAN / GTIN: 4026397366587

Weight: 5,00 kg Length: 0.61 m Width: 0.31 m Heigth: 0.42 m

- Trailing edge dimmer with 4 channels
- Max. channel load 200 watts
- Independent DMX addressing per channel possible
- Dimmer or switch operation
- 4 channel faders for control on the device
- Note: Only suitable for LED not for conventional light bulbs
- 16 integrated show programs
- Control via RDM; stand-alone; Sound to light via Microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- With rigging points
- LCD display
- For application areas such as: Trade fair and shop fitting; theater; Rental; video and photography; restaurants, bars and hotels
- Silent operation
- Application possibility: Wall mounting

#### Package contents

- 1 x device, 1 x user manual, 1 x power cord

# **Technical specifications:**

Weight:	3,91 kg
Energy efficiency class (A - G):	F

## **EUROLITE PAR-16 Spot GU-10 black**

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 75 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable construction:	3 x 0,75 mm² H05SS-F
Cable length:	Approx. 0,4 m
Base:	GU10
Lamp type:	Selectable
Color generation:	Via color filter frame
Control:	Plug and play
Construction:	PAR-16
Housing color:	Black
Material:	Aluminum, 1 mm
Slot for spot length:	7,8 cm x 7,8 cm
Dimensions:	Length: 17 cm
	Width: 11 cm
	Height: 13 cm
Weight:	280 g
Mounting bracket	
Diameter mounting holes:	2 x Ø10mm
Material:	Aluminum, 3 mm
Filter frame	

Shape:	Octagonal
Material:	Aluminum, 0,5 mm
Dimensions:	Length: 7,7 cm
	Width: 7,7 cm
	Diameter: Ø 5,3 cm
Weight:	10 g

# OMNILUX GU-10 230V COB 5W LED 1800-3000K dim2warm

Voltage (lamps):	230 V
Nominal wattage:	5 W
Base:	GU10
Lamp type:	LED lamp
Lamp specification:	Dimmable
Color of light:	White
Color temperature:	1800K - 3000K adjustable
Measurand (Pst LM):	0,0
Setup:	Easy installation
Beam angle:	24°
Beam angle (1/2 peak):	24°
Beam angle (1/10 peak):	60°
Color rendering index (CRI):	90 Ra
Luminous flux maintenance:	13
MacAdam Color consistency:	3
Operating temperature max.:	40° C
Operating temperature min.:	20° C
Lamp life:	15000 h
Luminous flux:	400 lm
Luminous flux maintenance:	0,97
Wavelength:	640 nm
Material:	Aluminum casting
Dimensions:	Width: 5 cm
	Depth: 5 cm
	Height: 5 cm
Weight:	40 g
Energy efficiency class (A - G):	F

## **EUROLITE EDX-4 DMX RDM LED Dimmer Pack**

Power supply:	230 V AC, 50 Hz
Output power:	Max. 200 W per channal Max. 800 W
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Power output:	4 x Safety contact (F), hinged lid mounting version

	1 x P-Con (gray), mounting version Bypass
DMX channels:	1; 4; 6
DMX input:	3-pin XLR (M)
DMX output:	3-pin XLR (F)
Control:	RDM; stand-alone; Sound to light via Microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Control channels:	4
Flying points:	2 x M10 thread
Display type:	LCD display
Status LED:	Chanal level meter
Color:	Black
Dimensions:	Width: 21 cm
	Depth: 29 cm
	Height: 9 cm
Weight:	2,63 kg
Noise classification:	Class 0 (no noise at all)