



**List price: 422.45 €**

incl. 19% VAT.

### Features:

#### EUROLITE PAR-30 Spot black

PAR-30 housing with E27 socket (with plug + cable)

- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Strong clamps with extension springs for safe hold and for quick opening of the rear housing cover
- Blackened tube for precise light output
- Suitable for different spot angles
- Small lighting-systems can also be realized with a small budget
- Control via plug and play
- With Mounting bracket
- For PAR 30
- For application areas such as: Advertisement/Shop window; Decoration; Clubs/dancing school

#### Package contents

- 1 x spotlight, 1 x mounting bracket, 1 x filter frame, 1 x user manual

### Logistic

EAN / GTIN: 4026397366600

Weight: 7,00 kg

Length: 0.61 m

Width: 0.31 m

Height: 0.42 m

#### OMNILUX PAR-30 230V COB 12W E-27 LED 1800k-3000k dim2warm

PAR-30 LED lamp with modern dim-to-warm feature

- Dimming behavior comparable with incandescent and halogen lamps (dim-to-warm)
- Changes the light color from 3000 K (warm white) to 1800 K (extra warm white) when dimming
- Creates particularly cosy atmospheres
- Easy lamp replacement
- Energy-saving
- Dimmable
- Variable color temperature 1800 K - 3000 K

- Easy installation
- Very high color rendering index (CRI)

### EUROLITE EDX-4 DMX RDM LED Dimmer Pack

4-channel dimmer for LED lights with 230 V operation

- Trailing edge dimmer with 4 channels
  - Max. channel load 200 watts
  - Independent DMX addressing per channel possible
  - Dimmer or switch operation
  - 4 channel faders for control on the device
  - Note: Only suitable for LED - not for conventional light bulbs
  - 16 integrated show programs
  - Control via RDM; stand-alone; Sound to light via Microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
  - With rigging points
  - LCD display
  - For application areas such as: Trade fair and shop fitting; theater; Rental; video and photography; restaurants, bars and hotels
  - Silent operation
  - Application possibility: Wall mounting
- Package contents**
- 1 x device, 1 x user manual, 1 x power cord

### Technical specifications:

|                                  |         |
|----------------------------------|---------|
| Weight:                          | 5,30 kg |
| Energy efficiency class (A - G): | F       |

### EUROLITE PAR-30 Spot black

|                       |  |
|-----------------------|--|
| Power supply:         | 230 V AC, 50 Hz                          |
| Power consumption:    | Max. 100 W                               |
| IP classification:    | IP20                                     |
| Protection class:     | Protection class I                       |
| Suitable lamp:        | Max. 230 V/100 W E27                     |
| Power connection:     | Fixed power supply cord with safety plug |
| Cable construction:   | 3 x 0,75 mm <sup>2</sup> H05SS-F         |
| Cable length:         | Approx. 0,4 m                            |
| Base:                 | E27                                      |
| Lamp type:            | Selectable                               |
| Color generation:     | Via color filter frame                   |
| Control:              | Plug and play                            |
| Construction:         | PAR-30                                   |
| Housing color:        | Black                                    |
| Attachment system:    | Mounting bracket                         |
| Material:             | Aluminum                                 |
| Slot for spot length: | 12,8 cm x 12,8 cm                        |
| Dimensions:           | Length: 23,5 cm                          |

Width: 14,5 cm  
Height: 21 cm

|                          |   |
|--------------------------|---|
| Weight:                  | 530 g   |
| Mounting bracket         |   |
| Diameter mounting holes: | 2 x Ø10mm   |
| Material:                | Aluminum, 3 mm  |
| Color:                   | Black   |
| Filter frame             |   |
| Shape:                   | Octagonal   |
| Material:                | Aluminum, 0,5 mm  |
| Color:                   | Black   |
| Dimensions:              | Length: 12,6 cm<br>Width: 12,6 cm<br>Diameter: Ø 9,4 cm |
| Weight:                  | 22 g  |

#### **OMNILUX PAR-30 230V COB 12W E-27 LED 1800k-3000k dim2warm**

|                                  |                          |
|----------------------------------|--------------------------|
| Voltage (lamps):                 | 230 V                    |
| Nominal wattage:                 | 12 W                     |
| Base:                            | E27                      |
| Lamp type:                       | LED lamp                 |
| Lamp specification:              | Dimmable                 |
| Beam angle:                      | 24°                      |
| Color of light:                  | White                    |
| Color temperature:               | 1800K - 3000K adjustable |
| Setup:                           | Easy installation        |
| Color rendering index (CRI):     | 96 Ra                    |
| Construction:                    | PAR-30                   |
| Operating temperature max.:      | 40° C                    |
| Operating temperature min.:      | 20° C                    |
| Lamp life:                       | 15000 h                  |
| Luminous flux:                   | 960 lm                   |
| Wavelength:                      | 640 nm                   |
| Weight:                          | 140 g                    |
| Photobiological safety:          | Risk Group 1             |
| Energy efficiency class (A - G): | F                        |

#### **EUROLITE EDX-4 DMX RDM LED Dimmer Pack**

|                   |  |
|-------------------|--|
| Power supply:     | 230 V AC, 50 Hz  |
| Output power:     | Max. 200 W per channel<br>Max. 800 W   |
| Power connection: | Mains input via P-Con (blue), mounting version<br>power supply cord with safety plug |

|                       |   |
|-----------------------|---|
| Power output:         | 4 x Safety contact (F), hinged lid mounting version<br>1 x P-Con (gray), mounting version Bypass  |
| DMX channels:         | 1; 4; 6   |
| DMX input:            | 3-pin XLR (M)   |
| DMX output:           | 3-pin XLR (F)   |
| Control:              | RDM; stand-alone; Sound to light via Microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Control channels:     | 4   |
| Flying points:        | 2 x M10 thread  |
| Display type:         | LCD display   |
| Status LED:           | Chanal level meter  |
| Color:                | Black   |
| Dimensions:           | Width: 21 cm<br>Depth: 29 cm<br>Height: 9 cm  |
| Weight:               | 2,63 kg   |
| Noise classification: | Class 0 (no noise at all)   |