



List price: 498.61 €

incl. 19% VAT.

Features:

EUROLITE PAR-38 Spot bk

PAR-38 housing with E27 socket (with plug + cable)

- Heat-resistant fixing screw
- Precise light output
- Strong cable tension relief
- Control via plug and play
- With Mounting bracket
- For PAR 38

Package contents

- 1 x spotlight, 1 x filter frame, 1 x user manual

Logistic

EAN / GTIN: 4026397366785

Weight: 9,00 kg

Length: 0.70 m

Width: 0.27 m

Height: 0.52 m

OMNILUX PAR-38 230V COB 18W E-27 LED 1800k-3000k dim2warm

PAR-38 LED lamp with modern dim-to-warm feature

- Dimming behavior comparable with incandescent and halogen lamps (dim-to-warm)
- Changes the light color from 3000 K (warm white) to 1800 K (extra warm white) when dimming
- Creates particularly cosy atmospheres
- Easy lamp replacement
- Energy-saving
- Dimmable
- Variable color temperature 1800 K - 3000 K
- Easy installation
- Very high color rendering index (CRI)

EUROLITE EDX-4 DMX RDM LED Dimmer Pack

4-channel dimmer for LED lights with 230 V operation

- Trailing edge dimmer with 4 channels
 - Max. channel load 200 watts
 - Independent DMX addressing per channel possible
 - Dimmer or switch operation
 - 4 channel faders for control on the device
 - Note: Only suitable for LED - not for conventional light bulbs
 - 16 integrated show programs
 - Control via RDM; stand-alone; Sound to light via Microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
 - With rigging points
 - LCD display
 - For application areas such as: Trade fair and shop fitting; theater; Rental; video and photography; restaurants, bars and hotels
 - Silent operation
 - Application possibility: Wall mounting
- Package contents**
- 1 x device, 1 x user manual, 1 x power cord

Technical specifications:

Weight: 6,96 kg

Energy efficiency class (A - G): F

EUROLITE PAR-38 Spot bk

Power supply: 230 V AC, 50 Hz

Power consumption: Max. 85 W

IP classification: IP20

Protection class: Protection class I

Power connection: Fixed power supply cord with safety plug

Cable construction: 3 x 0,75 mm² H05SS-F

Cable length: Approx. 0,9 m

Base: E27

Lamp type: Selectable

Color generation: Via color filter frame

Control: Plug and play

Construction: PAR-38

Housing color: Black

Attachment system: Mounting bracket

Material: Aluminum; metal

Slot for spot length: 17,2 cm x 17,2 cm

Dimensions: Width: 19 cm

Depth: 19 cm

Height: 21,5 cm

Weight: 700 g

Mounting bracket	
Diameter mounting holes:	2 x Ø12mm
Material:	Metal, 2 mm
Filter frame	
Diameter mounting holes:	2 x Ø8mm
Material:	Metal
Dimensions:	Length: 17 cm Width: 17 cm Diameter: Ø 14 cm
Weight:	120 g

OMNILUX PAR-38 230V COB 18W E-27 LED 1800k-3000k dim2warm

Operating voltage:	230 V, 220 - 240 V
Nominal wattage:	18 W
Base:	E27
Lamp type:	LED lamp
Lamp specification:	Dimmable
Beam angle:	38°
Color of light:	White
Color temperature:	1800K - 3000K adjustable
Setup:	Easy installation
Color rendering index (CRI):	96 Ra
Construction:	PAR-38
Operating temperature max.:	40° C
Operating temperature min.:	20° C
Lamp life:	15000 h
Luminous flux:	1440 lm
Wavelength:	630 nm
Weight:	380 g
Energy efficiency class (A - G):	F

EUROLITE EDX-4 DMX RDM LED Dimmer Pack

Power supply:	230 V AC, 50 Hz
Output power:	Max. 200 W per channel Max. 800 W
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Power output:	4 x Safety contact (F), hinged lid mounting version 1 x P-Con (gray), mounting version Bypass
DMX channels:	1; 4; 6
DMX input:	3-pin XLR (M)
DMX output:	3-pin XLR (F)

Control:	RDM; stand-alone; Sound to light via Microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Control channels:	4
Flying points:	2 x M10 thread
Display type:	LCD display
Status LED:	Chanal level meter
Color:	Black
Dimensions:	Width: 21 cm Depth: 29 cm Height: 9 cm
Weight:	2,63 kg
Noise classification:	Class 0 (no noise at all)