



The article is no longer in our assortment.

Features:

OMNITRONIC WMT-2M UHF Transmitter, mono

Wireless mono audio transmission system, 823-832 MHz + 863-865 MHz

- Wireless audio transmission system with UHF PLL technology
- For wireless transmission of audio line and microphone signals with one transmitter and one or more receivers
- Compatible with wireless modules and microphones of the MOM and DAD series
- 16 channels selectable
- Supports operation and simultaneous charging
- Robust metal fixing clip
- WM-2M camera tripod optional
- Up to 4 transmitters can be operated in parallel without interference

transmitter

- UHF 863 - 865 MHz License-free and approved in Europe
- UHF 823 - 832 MHz License-free and approved in large parts of Europe
- Operating range up to 50m
- Battery pack tool-free replacement
- Integrated automatic charging of the battery and status indicator
- Powered by a battery/battery pack

Package contents

- 1 x transmitter, 1 x microphone, 1 x USB cable, 1 x jack cable, 1 x adapter, 1 x user manual, 1 x declaration of conformity

Logistic

EAN / GTIN: 4026397177961

Weight: 0,50 kg

Length: 0.30 m

Width: 0.22 m

Height: 0.21 m

OMNITRONIC WMR-2M UHF Receiver, mono

Wireless mono audio transmission system, 823-832 MHz + 863-865 MHz

- Wireless audio transmission system with UHF PLL technology
- For wireless transmission of audio line and microphone signals with one transmitter and one or more receivers
- Compatible with wireless modules and microphones of the MOM and DAD series
- 16 channels selectable
- Audio line output and earphone connection via 3.5 mm jack
- Supports operation and simultaneous charging
- Robust metal fixing clip
- WM-2M camera tripod optional
- UHF 823 - 832 MHz License-free and approved in large parts of Europe
- UHF 863 - 865 MHz License-free and approved in Europe
- Operating range up to 50m
- Battery pack tool-free replacement
- Integrated automatic charging of the battery and status indicator
- Powered by a battery/battery pack
- Up to 4 transmitters can be operated in parallel without interference

Package contents

- 1 x receiver, 1 x jack cable, 1 x uSB cable, 1 x adapter, 1 x user manual, 1 x declaration of conformity

Technical specifications:

Weight: 420 g

OMNITRONIC WMT-2M UHF Transmitter, mono

| | |
|----------------------|--|
| Type: | Bodypack with microphone |
| Parallel mode: | Max. 4 transmitter |
| Control elements: | Level control |
| Weight: | 150 g |
| Transmitter | |
| Type: | Pocket transmitter |
| Power supply: | Or 5 V DC 3 V DC |
| Power connection: | Mains input via micro USB (F) mounting version power supply cord for USB A mains connection (provided) Battery/battery pack |
| Battery: | 2 x Mignon (AA) (not included) |
| S/N ratio: | >90 dB |
| Range: | Range up to 50m |
| Frequency band: | UHF 863 - 865 MHz; UHF 823 - 832 MHz |
| Frequency stability: | ± 0,01 % |
| RF power output: | 10 mW |
| Modulation: | FM |
| Frequency selection: | Switchable frequencies |
| Pilot frequency: | 32,768 khz |
| Connections: | Input: Microphone via 1 x Mini XLR (M) 3-pin mounting version |

Input: line via 1 x 3.5 mm jack (stereo) mounting version

| | |
|-------------------|---|
| Switch: | On/off switch |
| Material: | Plastic |
| Color: | Black |
| Dimensions: | Width: 6,7 cm Depth: 3,0 cm Height: 11,2 cm |
| Weight: | 80 g |
| Microphone | |
| Type: | Lavalier microphone |
| Power connection: | Via Mini XLR (F) 3-pin |
| Capsule type: | Condenser |

OMNITRONIC WMR-2M UHF Receiver, mono

| | |
|----------------------|---|
| Type: | Audio transmission |
| Power supply: | 3 V DC Or 5 V DC |
| Power connection: | Battery/battery pack Mains input via micro USB (F) mounting version power supply cord for USB A mains connection (provided) |
| Battery: | 2 x Mignon (AA) (not included) |
| S/N ratio: | >80 dB |
| Range: | Range up to 50m |
| Frequency band: | UHF 823 - 832 MHz; UHF 863 - 865 MHz |
| Frequency stability: | ± 0,01 % |
| Parallel mode: | Max. 4 transmitter |
| Modulation: | FM |
| Frequency selection: | 16 Switchable frequencies |
| Pilot frequency: | 32,768 khz |
| Control elements: | , frequency selector switch, level control |
| Status LED: | Power, signal |
| Connections: | Output: line via 1 x 3.5 mm jack (mono) mounting version 0,75 V Output: headphones via 1 x 3.5 mm jack (mono) mounting version 1 V |
| Switch: | On/off switch |
| Material: | Plastic |
| Color: | Black |
| Dimensions: | Width: 6,7 cm Depth: 3,0 cm Height: 11,2 cm |
| Weight: | 130 g |
| Receiver | |
| Weight: | 80 g |