

EUROLITE Set LED KLS-902 + Controller + STV-40S-WOT Steel stand

KLS incl. DMX lighting desk, DMX transmitter, miniature DMX transceiver and steel stand

Art. No.: 20000720

GTIN: 4026397340846



The article is no longer in our assortment.

Features:

EUROLITE LED KLS-902 Next Compact Light Set

Bar with 4 powerful RGB/WW spots, QuickDMX support, IR remote control and carrying bag

- 5 powerful LEDs 7 W high-power 4in1 QCL RGB/WW (homogenous color mix)
 spots controlled separately
- Crossbar with integrated DMX control unit and TV spigot for tripod installation
- With a beam angle of 16°
- 20 integrated show programs
- Color blend stepless; Dimmer electronic; program selection
- Mounting points and power outlets for additional fixtures
- Control via DMX; stand-alone; Sound to light via Microphone; IR remote control; Wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- For application areas such as: Mobile use; Stage; mobile djs / entertainer; small rental; Rental
- Preprogrammed in EASY SHOW 1; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; Light J; EASY SHOW 3
- Mains input and output for power linking up to 8 units
- Very quiet working noise
- Application possibility: Suspended; on stand

Package contents

- 1 x light effect, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery, 2 x omega bracket, 1 x declaration of conformity, 4 x knurled screw, 1 x bag

Logistic

EAN / GTIN: 4026397340846

Weight: 23,50 kg

Length: 1.35 m

Width: 0.21 m

Height: 0.58 m

Bulky product

EUROLITE DMX LED Color Chief Controller

DMX lighting desk with innovative control concept for LED spotlights

- Easy control of LED spotlights with up to 6 colors, light bars as well as simple lighting effects
- For 8 devices or device groups, each with up to 4 segments
- Quick and easy programming
- Additional fixtures can be configured manually
- 8 color effects directly selectable
- 3 additional channels available per fixture (e.g. for rotations)
- Color wheel selection and simulation
- 24 memory spaces for scenes and chases
- Several chases and scenes can be run simultaneously
- USB port for storing program data
- Sound control via audio signal or TAP button
- Master dimming, fade time and run time easily adjustable
- Programmable 24 scenes/chases distributed over 1 page(s)
- Can transmit up to 240 DMX channels
- Control via DMX; Sound to light via RCA (F) mounting version; Sound to light via Microphone
- (19") 48.3 cm rack installation 3 U
- Desktop console housing
- For application areas such as: Clubs/dancing school; Party room; Trade fair and shop fitting; mobile djs / entertainer; restaurants, bars and hotels
- Silent operation
- Firmware can be updated

Package contents

- 1 x controller, 1 x user manual, 1 x external mains adapter

EUROLITE QuickDMX Wireless Transmitter

Compact wireless DMX transmitter 2.4 GHz

- User-friendly 3-pin XLR adapter (male) with swivel antenna
- Wireless DMX eliminates extensive cabling between DMX controller and the DMX-controlled units in lighting installations
- Due to GFSK modulation with 78 channels, interference-free operation also alongside other QuickDMX transceiver and wireless devices in the 2.4 GHz band (e.g. Wi-Fi and Bluetooth)
- 1 to 512 QuickDMX receivers can be controlled by each transmitter
- LED indication for functions
- Transceiver, to be used as transmitter or receiver
- Can transmit up to 512 DMX channels
- Control via QuickDMX; DMX; plug and play
- Operating range up to 400m
- Up to 6 transmitters can be operated in parallel without interference

Package contents

- 1 x device, 1 x user manual, 1 x declaration of conformity, 1 x external mains adapter, 1 x USB cable

EUROLITE QuickDMX USB Wireless Transmitter/Receiver

Wireless miniature DMX transceiver 2.4 GHz, phantom powered

- User-friendly USB plug with swivel antenna
- Wireless DMX eliminates extensive cabling between DMX controller and the DMX-controlled units in lighting installations
- Due to GFSK modulation with 78 channels, interference-free operation also alongside other QuickDMX transceiver and wireless devices in the 2.4 GHz band (e.g. Wi-Fi and Bluetooth)
- LED indication for functions
- Transceiver, to be used as transmitter or receiver
- Requires 5 V phantom power for operation
- Can receive and process up to 512 DMX channels
- Can transmit up to 512 DMX channels
- Control via DMX; QuickDMX; plug and play
- Operating range up to 400m with line-of-sight
- Up to 6 transmitters can be operated in parallel without interference

Package contents

- 1 x device, 1 x user manual, 1 x declaration of conformity

EUROLITE STV-40S-WOT Steel Stand

Steel lighting stand without crossbar, max. load 18 kg, max. height 340 cm

- Stable lighting stand for mobile use
 - The telescopic tube is additionally fixed with a safety pin
 - TV spigot
 - Complies with DIN 15560-27 and DIN EN ISO 12100-2
 - Adjustable height
- Package contents**
- 1 x stand, 1 x user manual

Technical specifications:

Weight: 20,41 kg

EUROLITE LED KLS-902 Next Compact Light Set

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	125 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Cable length:	3 m
Power output:	2 x IEC connector (F) mounting version 1 x P-Con (gray), mounting version
Device fuse:	5 x 20 mm, T 2 A Fuse replaceable
Power output fuse per channel:	5 x 20 mm, T 5 A Fuse replaceable
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Lamp type:	LED lamp
LED:	5 x 7 W high-power 4in1 QCL RGB/WW (homogenous color mix)
DMX channels:	3; 4; 6; 8; 16; 20; 18
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; Sound to light via Microphone; IR remote control; Wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	EASY SHOW 1; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; Light J; EASY SHOW 3
Beam angle:	16°
Beam angle (1/2 peak):	16°
Beam angle (1/10 peak):	32°
Housing color:	Black
Attachment system:	TV spigot Ø 28mm Omega bracket
Dimensions:	Width: 1,08 m

	Depth: 6 cm Height: 28 cm
Weight:	9,80 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE DMX LED Color Chief Controller

Power supply:	100-240 V AC, 50/60 Hz 9 V DC 800 mA
Power consumption:	10 W
IP classification:	IP20
Power connection:	Mains input via Coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Programs:	Programmable 24 scenes/chases distributed over 1 page(s)
DMX channels:	Output 240
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	DMX; Sound to light via RCA (F) mounting version; Sound to light via Microphone
Housing color:	Black
Available storage media:	USB devices (FAT 32)
USB port:	Typ A
Color:	Black
PC connect:	, firmware can be updated
Housing design:	(19") 48.3 cm rack installation 3 U Desktop console housing
Dimensions:	Width: 48,3 cm Depth: 13,35 cm Height: 8,5 cm
Weight:	2,25 kg
Noise classification:	Class 0 (no noise at all)

EUROLITE QuickDMX Wireless Transmitter

Power supply:	100-240 V AC, 50/60 Hz 5 V DC 1 A
IP classification:	IP20
Power connection:	Mains input via Coaxial power connector (M) mounting version power supply cord for USB A mains connection (provided)
DMX channels:	Output 512
DMX input:	1 x 3-pin XLR (M)
Control:	QuickDMX; DMX; plug and play

Range:	Range up to 400m
Carrier frequency:	2,4 GHz
Parallel mode:	Max. 6 transmitter
Modulation:	GFSK
Color:	Silver
Dimensions:	Length: 21,2 cm Diameter: Ø 1,8 cm
Weight:	150 g

EUROLITE QuickDMX USB Wireless Transmitter/Receiver

Power supply:	5 V DC
IP classification:	IP20
Power connection:	Mains input via USB A (M) connectable version
DMX channels:	Input 512 Output 512
DMX output:	1 x USB, type A
Control:	DMX; QuickDMX; plug and play
Range:	Range up to 400m with line-of-sight
Carrier frequency:	2,4 GHz
Parallel mode:	Max. 6 transmitter
Modulation:	GFSK
Color:	Black
Dimensions:	Width: 8,6 cm Depth: 4 cm Height: 1,1 cm
Weight:	10 g

EUROLITE STV-40S-WOT Steel Stand

Maximum carrying capacity:	18 kg
Standard:	DIN 15560-27, DIN EN ISO 12100-2
Height:	Maximum: 340 cm above 2 sections Minimum: 150 cm
Attachment system:	TV spigot Ø 28mm
Type (general stands):	Light stand/manual
Color:	Black
Transport dimensions:	1,59 m x 18 cm x 15 cm
Base area:	Ø 1,2 m
Weight:	8,20 kg