

## EUROLITE Set LED KLS-902 + STV-40S-WOT Steel stand

Bar with 4 powerful RGB/WW spots, QuickDMX, remote control and bag incl. steel stand

Art. No.: 2000721

GTIN: 4026397340853



**List price: 653.31 €**

incl. 19% VAT.

### Features:

#### EUROLITE LED KLS-902 Next Compact Light Set

Bar with 4 powerful RGB/WW spots, QuickDMX support, IR remote control and carrying bag

- 5 powerful LEDs 7 W high-power 4in1 QCL RGB/WW (homogenous color mix) spots controlled separately
- Crossbar with integrated DMX control unit and TV spigot for tripod installation
- With a beam angle of 16°
- 20 integrated show programs
- Color blend stepless; Dimmer electronic; program selection
- Mounting points and power outlets for additional fixtures
- Control via DMX; stand-alone; Sound to light via Microphone; IR remote control; Wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRM by LumenRadio via USB (optional)
- For application areas such as: Mobile use; Stage; mobile djs / entertainer; small rental; Rental
- Preprogrammed in EASY SHOW 1; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; Light J; EASY SHOW 3
- Mains input and output for power linking up to 8 units
- Very quiet working noise
- Application possibility: Suspended; on stand

#### Package contents

- 1 x light effect, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery, 2 x omega bracket, 1 x declaration of conformity, 4 x knurled screw, 1 x bag

#### EUROLITE STV-40S-WOT Steel Stand

Steel lighting stand without crossbar, max. load 18 kg, max. height 340 cm

### Logistic

EAN / GTIN: 4026397340853

Weight: 20,50 kg

Length: 1.35 m

Width: 0.21 m

Height: 0.58 m

Bulky product

- Stable lighting stand for mobile use
- The telescopic tube is additionally fixed with a safety pin
- TV spigot
- Complies with DIN 15560-27 and DIN EN ISO 12100-2
- Adjustable height

**Package contents**

- 1 x stand, 1 x user manual

**Technical specifications:**

---

Weight: 18,00 kg

---

**EUROLITE LED KLS-902 Next Compact Light Set**

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	125 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Cable length:	3 m
Power output:	2 x IEC connector (F) mounting version 1 x P-Con (gray), mounting version
Device fuse:	5 x 20 mm, T 2 A Fuse replaceable
Power output fuse per channel:	5 x 20 mm, T 5 A Fuse replaceable
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Lamp type:	LED lamp
LED:	5 x 7 W high-power 4in1 QCL RGB/WW (homogenous color mix)
DMX channels:	3; 4; 6; 8; 16; 20; 18
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; Sound to light via Microphone; IR remote control; Wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	EASY SHOW 1; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; Light J; EASY SHOW 3
Beam angle:	16°
Beam angle (1/2 peak):	16°
Beam angle (1/10 peak):	32°
Housing color:	Black
Attachment system:	TV spigot Ø 28mm Omega bracket
Dimensions:	Width: 1,08 m

	Depth: 6 cm Height: 28 cm
Weight:	9,80 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### **EUROLITE STV-40S-WOT Steel Stand**

Maximum carrying capacity:	18 kg
Standard:	DIN 15560-27, DIN EN ISO 12100-2
Height:	Maximum: 340 cm above 2 sections Minimum: 150 cm
Attachment system:	TV spigot Ø 28mm
Type (general stands):	Light stand/manual
Color:	Black
Transport dimensions:	1,59 m x 18 cm x 15 cm
Base area:	Ø 1,2 m
Weight:	8,20 kg