

EUROLITE Set 4x LED TMH-S90 + Case

4x Led moving head spot including flightcase with wheels

Art. No.: 20000742

GTIN: 4026397681796













List price: 2854.81 €

incl. 19% VAT.

Features:

4x Led moving head spot including flightcase with wheels

- Positioning within

EUROLITE LED TMH-S90 Moving Head Spot

LED moving head spot with color wheel, static and rotating gobo wheel, prism and focus

- Rotating 3-facet prism with variable speed
- 1 powerful LED 90 W COB (chip-on-board) cold white (CW)
- Positioning within 540° PAN, 200° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Prism 3-fold; gobo wheel with rotating gobos; gobo wheel with static gobos; focus motor-driven; color wheel
- Dimmer electronic
- Color wheel with 7 dichroic filters plus open
half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 7 gobos and open
shake effect
- Gobo wheel with rotating gobos, 5 gobos,1 multi color gobo and open
shake effect
- Gobos changeable
- Slot-in gobo system for easy gobo replacement
- Integrated show programs
- The device is cooled by cooling fan

Logistic

EAN / GTIN: 4026397681796

Weight: 50,00 kg Length: 1.20 m Width: 0.80 m Heigth: 0.37 m Bulky product

- Control via DMX; sound to light via microphone; stand-alone; master/slave function; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional)
- Preprogrammed in EASY SHOW 1; Light Captain; EASY SHOW 3
- Flicker-free
- With a beam angle of 12°
- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; mobile djs / entertainer
- Application possibility: Standing; suspended

Package contents

- 1 x moving light, 1 x user manual, 1 x power cord, 1 x omega bracket, 1 x safety eyelet

ROADINGER Flightcase 4x TMH-S90/H90/B90

Trunk case with castors

- For optimal security
- With 4 device compartments
- High-quality workmanship with plywood multi-layer glued 7 mm, black, laminated
- Interior with foam padding
cover with foam padding
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Castors

Technical specifications:

Weight: 43,80 kg

EUROLITE LED TMH-S90 Moving Head Spot

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	140 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 2 A
Lamp type:	LED lamp
LED type:	1 x 90 W COB (chip-on-board) cold white (CW)
Max. TILT movement:	200° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	1,5 - 15 Hz
Equipment:	Prism 3-fold; gobo wheel with rotating gobos; gobo wheel with static gobos; focus motor-driven; color wheel
Color generation:	Color wheel with 7 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions

DMX channels: DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: Control: DMX; sound to light via microphone; stand-alone; master/slave function; QuickDMX via USB (optional); W-DMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional) Preprogrammed in: EASY SHOW 1; Light Captain; EASY SHOW 3 Projection: Flicker-free PWM frequency: 15600 Hz Beam angle: 12° Beam angle (1/2 peak): Illuminance in Lux (lx): Cold white (CW) 1m: 52772 lx, 3m: 6198 lx, 6m: 1543 lx Housing color: Dimensions: Width: 25,0 cm Depth: 20,5 cm Height: 35,0 cm Weight: 6,20 kg Noise classification: Class 3 (clearly perceptible sounds) Photobiological safety: Legal specifications Special product: Not designed for household room illumination Intended use: Show effect lighting	Gobos:	Gobo wheel with static gobos, 7 gobos and open Shake effect Gobo wheel with rotating gobos, 5 gobos,1 multi color gobo and open Outside diameter 21,8mm Image diameter 16mm Shake effect Gobos changeable Slot-in gobo system for easy gobo replacement
DMX output: Cooling: Cooling fan Control: DMX; sound to light via microphone; stand-alone; master/slave function; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional) Preprogrammed in: EASY SHOW 1; Light Captain; EASY SHOW 3 Projection: Flicker-free PWM frequency: 15600 Hz Beam angle: 12° Beam angle: 12° Beam angle: 12° Black Uidth: 25,0 cm Depth: 20,5 cm Height: 35,0 cm Weight: 6,20 kg Noise classification: Class 3 (clearly perceptible sounds) Photobiological safety: Risk Group 0 Legal specifications Special product: Not designed for household room illumination	DMX channels:	15
Cooling: Cooling: Cooling fan DMX; sound to light via microphone; stand-alone; master/slave function; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional) Preprogrammed in: EASY SHOW 1; Light Captain; EASY SHOW 3 Projection: Flicker-free PWM frequency: 15600 Hz Beam angle: 12° Beam angle: 12° Beam angle (1/2 peak): 12° Cold white (CW) 1m: 52772 lx, 3m: 6198 lx, 6m: 1543 lx Housing color: Black Dimensions: Width: 25,0 cm Depth: 20,5 cm Height: 35,0 cm Weight: 6,20 kg Noise classification: Class 3 (clearly perceptible sounds) Photobiological safety: Risk Group 0 Legal specifications Special product: Not designed for household room illumination	DMX input:	3-pin XLR (M) mounting version
Control: DMX; sound to light via microphone; stand-alone; master/slave function; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional) Preprogrammed in: EASY SHOW 1; Light Captain; EASY SHOW 3 Projection: Flicker-free PWM frequency: Beam angle: 12° Beam angle (1/2 peak): Illuminance in Lux (lx): Cold white (CW) 1m: 52772 lx, 3m: 6198 lx, 6m: 1543 lx Housing color: Black Dimensions: Width: 25,0 cm Depth: 20,5 cm Height: 35,0 cm Weight: 6,20 kg Noise classification: Class 3 (clearly perceptible sounds) Photobiological safety: Legal specifications Special product: Not designed for household room illumination	DMX output:	3-pin XLR (F) mounting version
master/slave function; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional) Preprogrammed in: EASY SHOW 1; Light Captain; EASY SHOW 3 Projection: Flicker-free PWM frequency: 15600 Hz Beam angle: 12° Beam angle (1/2 peak): 12° Cold white (CW) 1m: 52772 lx, 3m: 6198 lx, 6m: 1543 lx Housing color: Black Dimensions: Width: 25,0 cm Depth: 20,5 cm Height: 35,0 cm Weight: 6,20 kg Noise classification: Class 3 (clearly perceptible sounds) Photobiological safety: Legal specifications Special product: Not designed for household room illumination	Cooling:	Cooling fan
Projection: PWM frequency: 15600 Hz Beam angle: 12° Beam angle (1/2 peak): Illuminance in Lux (lx): Cold white (CW) 1m: 52772 lx, 3m: 6198 lx, 6m: 1543 lx Housing color: Black Dimensions: Width: 25,0 cm Depth: 20,5 cm Height: 35,0 cm Weight: 6,20 kg Noise classification: Class 3 (clearly perceptible sounds) Photobiological safety: Risk Group 0 Legal specifications Special product: Not designed for household room illumination	Control:	master/slave function; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB
PWM frequency: Beam angle: 12° Beam angle (1/2 peak): Illuminance in Lux (lx): Cold white (CW) 1m: 52772 lx, 3m: 6198 lx, 6m: 1543 lx Housing color: Black Dimensions: Width: 25,0 cm Depth: 20,5 cm Height: 35,0 cm Weight: 6,20 kg Noise classification: Class 3 (clearly perceptible sounds) Photobiological safety: Risk Group 0 Legal specifications Special product: Not designed for household room illumination	Preprogrammed in:	EASY SHOW 1; Light Captain; EASY SHOW 3
Beam angle: 12° Beam angle (1/2 peak): 12° Illuminance in Lux (lx): Cold white (CW) 1m: 52772 lx, 3m: 6198 lx, 6m: 1543 lx Housing color: Black Dimensions: Width: 25,0 cm	Projection:	Flicker-free
Beam angle (1/2 peak): Illuminance in Lux (lx): Cold white (CW) 1m: 52772 lx, 3m: 6198 lx, 6m: 1543 lx Housing color: Black Dimensions: Width: 25,0 cm Depth: 20,5 cm Height: 35,0 cm Weight: 6,20 kg Noise classification: Class 3 (clearly perceptible sounds) Photobiological safety: Risk Group 0 Legal specifications Special product: Not designed for household room illumination	PWM frequency:	15600 Hz
Illuminance in Lux (lx): Cold white (CW) 1m: 52772 lx, 3m: 6198 lx, 6m: 1543 lx Housing color: Black Dimensions: Width: 25,0 cm Depth: 20,5 cm Height: 35,0 cm Weight: 6,20 kg Noise classification: Class 3 (clearly perceptible sounds) Photobiological safety: Risk Group 0 Legal specifications Special product: Not designed for household room illumination	Beam angle:	12°
Housing color: Black Dimensions: Width: 25,0 cm Depth: 20,5 cm Height: 35,0 cm Weight: 6,20 kg Noise classification: Class 3 (clearly perceptible sounds) Photobiological safety: Risk Group 0 Legal specifications Special product: Not designed for household room illumination	Beam angle (1/2 peak):	12°
Dimensions: Width: 25,0 cm Depth: 20,5 cm Height: 35,0 cm Weight: 6,20 kg Noise classification: Class 3 (clearly perceptible sounds) Photobiological safety: Risk Group 0 Legal specifications Special product: Not designed for household room illumination	Illuminance in Lux (lx):	• •
Depth: 20,5 cm Height: 35,0 cm Weight: 6,20 kg Noise classification: Class 3 (clearly perceptible sounds) Photobiological safety: Risk Group 0 Legal specifications Special product: Not designed for household room illumination	Housing color:	Black
Noise classification: Class 3 (clearly perceptible sounds) Photobiological safety: Risk Group 0 Legal specifications Special product: Not designed for household room illumination	Dimensions:	Depth: 20,5 cm
Photobiological safety: Legal specifications Special product: Not designed for household room illumination	Weight:	6,20 kg
Legal specifications Special product: Not designed for household room illumination	Noise classification:	Class 3 (clearly perceptible sounds)
Special product: Not designed for household room illumination	Photobiological safety:	Risk Group 0
	Legal specifications	
Intended use: Show effect lighting	Special product:	Not designed for household room illumination
	Intended use:	Show effect lighting

ROADINGER Flightcase 4x TMH-S90/H90/B90

Maximum load:	100 kg
Aluminum profile frames:	30 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	Castors
Material:	Plywood multi-layer glued, 7 mm
Color:	Black, laminated
Device compartment:	26 cm x 20 cm x 37 cm
Accessory compartment:	26 cm x 9 cm x 37 cm

Dimensions: Width: 58 cm
Depth: 57 cm

Height: 54 cm

Weight: 19,00 kg