

## EUROLITE Set LED SL-400 DMX + STV-250

Follow spot with 300 W warm white LED including follow stand

Art. No.: 20000750

GTIN: 4026397682441



### Features:

- Manual control via control panel with buttons and faders
- 1 LED 300 W COB (chip-on-board) warm white (WW)
- Focus manual; iris stepless
- Dimmer electronic
- Strobe effect
- Color wheel with 5 dichroic filters plus open<BR>half colors selectable
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX
- Fixtures available for LED PC-Control 512; Light Captain
- Flicker-free
- With a beam angle of 7° - 17°
- Direct color temperature selection for 4 preset values
- Good color rendering index (CRI)
- With mounting bracket
- 4 digit 7-segment LED display
- Built with SEETRONIC connector
- Suitable for a range of use from 25 to 50 meters
- For application areas such as: Wedding/gala/events; stage; theater; rental
- Application possibility: Suspended; on stand
- <p>EUROLITE STV-250 Follow Spot Stand, black
- <h2 class="featureSatz">PRO follow stand for mobile lighting systems</h2>Heavy-duty stainless steel version for extra stability and safety
- Tripod legs made of stainless steel
- Tripod legs with optional slant for uneven surfaces
- Easy handling
- Safety ring for height adjustment

### Logistic

EAN / GTIN: 4026397682441

Weight: 24,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

- Extra-big, rubberized star knob screw
- Adjustable height
- With Multi-angle ball head bracket with stainless steel rod

## Technical specifications:

|         |          |
|---------|----------|
| Weight: | 20.80 kg |
|---------|----------|

### EUROLITE LED SL-400 DMX Search Light

|                              |                                                                                              |
|------------------------------|----------------------------------------------------------------------------------------------|
| Power supply:                | 100-240 V AC, 50/60 Hz                                                                       |
| Power consumption:           | 440 W                                                                                        |
| IP classification:           | IP20                                                                                         |
| Power connection:            | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Lamp type:                   | LED lamp                                                                                     |
| LED type:                    | 1 x 300 W COB (chip-on-board) warm white (WW)                                                |
| Flash rate:                  | 0.8 - 16 Hz                                                                                  |
| Equipment:                   | Focus manual; iris stepless                                                                  |
| Color generation:            | Color wheel with 5 dichroic filters plus open Half colors selectable                         |
| DMX channels:                | 6                                                                                            |
| DMX input:                   | 3-pin XLR (M) mounting version                                                               |
| DMX output:                  | 3-pin XLR (F) mounting version                                                               |
| Cooling:                     | Temperature-controlled fan                                                                   |
| Control:                     | Stand-alone; DMX                                                                             |
| Fixtures available for:      | LED PC-Control 512; Light Captain                                                            |
| Projection:                  | Flicker-free                                                                                 |
| PWM frequency:               | 26600 Hz                                                                                     |
| Beam angle:                  | 7° - 17°                                                                                     |
| Beam angle (1/2 peak):       | 7 - 13°                                                                                      |
| Beam angle (1/10 peak):      | 3 - 17°                                                                                      |
| Color temperature:           | 3500K                                                                                        |
| Color rendering index (CRI): | 80 Ra                                                                                        |
| Housing color:               | Black                                                                                        |
| Attachment system:           | Mounting bracket                                                                             |
| Display type:                | 4 digit 7-segment LED display                                                                |
| Use of brands:               | Built with SEETRONIC connector                                                               |
| Range of use:                | 25m - 50m                                                                                    |
| Dimensions:                  | Length: 77 cm<br>Width: 27 cm<br>Height: 29 cm                                               |
| Weight:                      | 12.35 kg                                                                                     |
| Noise classification:        | Class 2 (slight noise)                                                                       |

|                  |                                              |
|------------------|----------------------------------------------|
| Special product: | Not designed for household room illumination |
| Intended use:    | Show effect lighting                         |

#### **EUROLITE STV-250 Follow Spot Stand, black**

|                            |                                                                      |
|----------------------------|----------------------------------------------------------------------|
| Maximum carrying capacity: | 50 kg                                                                |
| Height:                    | Maximum: 170 cm<br>Minimum: 95 cm                                    |
| Attachment system:         | M10 thread<br>Multi-angle ball head bracket with stainless steel rod |
| Type (general stands):     | Light stand/manual                                                   |
| Material:                  | Aluminum; stainless steel                                            |
| Color:                     | Black                                                                |
| Base area:                 | Ø 1.12 cm                                                            |
| Transport dimensions:      | 13 cm x 14 cm x 105 cm                                               |
| Weight:                    | 8.45 kg                                                              |

#### **Scope of delivery:**

##### **1 x EUROLITE LED SL-400 DMX Search Light**

1 x spotlight  
1 x user manual  
1 x power cord  
1 x XLR cable  
1 x mounting bracket  
1 x hex key

##### **1 x EUROLITE STV-250 Follow Spot Stand, black**

1 x stand  
1 x user manual