

OMNITRONIC Set MOLLY-12A Subwoofer active + 4x MOLLY-6 Top 8 Ohm, Apria ok 20000757


Active 12" subwoofer with DSP and Bluetooth incl. 4x 6.5" satellite speakers with bracket

GTIN: 4026397684384









incl. 19% VAT.

Features:

OMNITRONIC MOLLY-12A Subwoofer active black

Active 12" subwoofer with DSP and Bluetooth

- 12" bassreflex subwoofer with DSP and 700 watts RMS power
- Flexibly extendable with MOLLY-6 satellites for 2.1 and 4.1 configurations
- DSP-controlled class D amplifier (500 W + 2 x 100 W)
- Separate volume control for subwoofer and satellites
- Stereo/mono selection
- Digital signal processor
- The device is cooled by temperature-controlled fan
- Control via Bluetooth
- For application areas such as: Mobile djs / entertainer; Trade fair and shop fitting; Installation; home entertainment; restaurants, bars and hotels; product presentations and lectures
- 2 Rugged carrying handles
- Black metal grille with acoustic foam
- DSP presets: FLAT; DJ; LIVE; VOICE
- Package contents
- 1 x user manual, 1 x power cord, 1 x declaration of conformity, 1 x bass, 2 x speaker cable

OMNITRONIC MOLLY-6 Top black 2x

6.5" satellite speakers with bracket

- 8-ohm speaker pair with 6.5" woofer and 1" tweeter
- For use with MOLLY-12A subwoofers for 2.1 and 4.1 configurations
- Optional stand adaptor required for stand mounting
- Extension U-bracket and cable available for connecting 2 satellite speakers

Logistic

EAN / GTIN: 4026397684384 Weight: 41,00 kg Length: 1.20 m Width: 0.80 m Heigth: 0.50 m Bulky product

- With Mounting bracket

- With rigging points
- Black metal grille with acoustic foam
- 2 pieces per set
- For application areas such as: Mobile djs / entertainer; Trade fair and shop fitting; Installation; home entertainment; restaurants, bars and hotels; product presentations and lectures

Package contents

- 2 x top, 2 x mounting bracket, 4 x knurled screw, 2 x screw plug-in terminal

Technical specifications:

Weight:

39,90 kg

OMNITRONIC MOLLY-12A Subwoofer active black

| Power supply: | 230 V AC, 50 Hz |
|------------------------|--|
| Power consumption: | 1000 W |
| Protection class: | Protection class I |
| Output power: | 1 x 500 W RMS 2 x 100 W RMS (8 ohms) 2 x 200 W RMS (4 ohms) |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Frequency range: | 40 - 160 Hz |
| Sensitivity: | 103 dB |
| Max. SPL: | 128 dB |
| DSP: | Digital signal processor |
| DSP presets: | FLAT; DJ; LIVE; VOICE |
| Cooling: | Temperature-controlled fan |
| Control: | Bluetooth |
| Bluetooth device name: | Omnitronic |
| Attachment system: | Flange: M20 thread |
| Circuitry: | Class D |
| Control elements: | Phase reversal switch, level control per channel, power switch, connect |
| Controls: | Softstart; short-circuit; limiter; Overvoltage; overheat |
| Status LED: | Signal, power, limit, fault, DSP presets |
| Connections: | Input: line via 2 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) |
| | Input: line via 1 x 3.5 mm jack (stereo) mounting version |
| | Input: line via 1 x stereo RCA |
| | Output: line via 2 x 3-pin XLR |
| | Output: Top via 2 x speaker built-in socket (F) |
| Input channels: | 1 x stereo via Combination socket or RCA or Bluetooth, channel control via Rotary dial |
| Speaker: | 1 x woofer 12" |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

| | Voice coil lows 3" |
|-----------------------|----------------------------------|
| Type of speaker: | Subwoofer |
| Type of construction: | Vented |
| Carrying handle: | 2 pc/pcs |
| Material: | Birch multiplex |
| Color: | Black, textured coating, painted |
| Dimensions: | Width: 47 cm |
| | Depth: 57 cm |
| | Height: 40 cm |
| Weight: | 22,10 kg |

OMNITRONIC MOLLY-6 Top black 2x

| Power: | Program: 260W |
|--------------------|---|
| | Rated: 130W RMS |
| Frequency range: | 150 - 20000 Hz |
| Sensitivity: | 95 dB (1W/1m) |
| Max. SPL: | 119 dB |
| Impedance: | 8 ohms |
| Attachment system: | 2x Mounting bracket |
| Flying points: | 2 x M8 thread |
| Connections: | 1 x speaker built-in socket (F) |
| | 1 x screw plug-in terminal |
| Speaker: | 1 x woofer 6,5" |
| | Basket material: Steel |
| | Voice coil lows 1" |
| | 1 x Tweeter 1" |
| Type of speaker: | On-ceiling/on-wall speaker; Coaxial speaker |
| Material: | MDF (Medium-density fiberboard) |
| Color: | Black, textured coating, painted |
| Dimensions: | Width: 18,3 cm |
| | Depth: 21,4 cm |
| | Height: 23 cm |
| Weight: | 8,90 kg |
| | |