

# PSSO Set WISE TWO + Dyn. wireless microphone + BP + Headset 823-832/8634865MHz1

License-free true diversity wireless receiver incl. wireless microphone, pocket transmitter and headset

GTIN: 4026397685664





List price: 1046.01 €

incl. 19% VAT.

## Features:

## PSSO WISE TWO 2-Channel True Diversity Receiver 823-832/863-865MHz

License-free true diversity wireless receiver with 2.4GHz iSync control management

- Professional multifrequency wireless receiver with true diversity reception for stage use
- High-grade components and intelligent features ensure best performance and high reliability
- Ideal for large multi-channel systems (parallel operation possible up to 26 systems)
- 45 preset channels in 5 channel groups
- 2.4 GHz iSync real-time synchronization and monitoring
- Automatic frequency setup
- Pilot frequency squelch technology delete wireless RF interference
- Multifunctional jogdial for menu settings
- Lock function for prevents undesired changes to settings
- Mic/line selector switch
- 2 detachable BNC antennas allow for use with external antenna divider
- 2 receivers can share a single power adapter
- Multicolor LCD display
- UHF 823 832 MHz License-free and approved in large parts of Europe
- UHF 863 865 MHz License-free and approved in Europe
- Operating range up to 60m with line-of-sight
- (19") 48.3 cm rack installation 1 U
- Firmware can be updated
- For application areas such as: Mobile use; Stage; theater; Rental; sports centres/gyms; concerts/FoH's

### Package contents

1 x receiver, 1 x external mains adapter, 1 x power cord, 3 x antenna, 2 x bNC cable, 1 x jack cable, 1 x adapter cable, 4 x foot, 2 x holder, 2 x windshield, 1 x user manual, 1 x declaration of conformity, 4 x battery

## Logistic

EAN / GTIN: 4026397685664

Weight: 4,00 kg Length: 0.61 m Width: 0.31 m Heigth: 0.42 m

#### PSSO WISE Dynamic Wireless Microphone 823-832/863-865MHz

Hand-held microphone with PLL multifrequency transmitter

- Dynamic hand-held microphone with UHF pilot tone technology (PLL)
- Rugged, ergonomic aluminum housing
- High-grade components and intelligent features ensure best performance and high reliability
- 2.4 GHz iSync real-time synchronization and monitoring
- Editable user name and user color
- RF output switchable
- Gain level adjustable
- Lock function for prevents undesired changes to settings
- Directly compatible with Shure's SM58 capsule
- Polar pattern: Cardioid
- Operating range up to 60m with line-of-sight
- UHF 863 865 MHz License-free and approved in Europe
- UHF 823 832 MHz License-free and approved in large parts of Europe
- Multicolor LCD display

#### Package contents

- 1 x microphone, 1 x bag, 1 x user manual, 1 x declaration of conformity

## PSSO WISE Bodypack 823-832/863-865MHz

Bodypack transmitter with PLL multifrequency transmitter

- 2.4 GHz iSync real-time synchronization and monitoring
- Editable user name and user color
- RF output switchable
- Gain level adjustable
- Lock function for prevents undesired changes to settings
- Operating range up to 60m with line-of-sight
- UHF 823 832 MHz License-free and approved in large parts of Europe
- UHF 863 865 MHz License-free and approved in Europe
- Multicolor LCD display

#### Package contents

- 1 x transmitter, 2 x antenna, 1 x user manual, 1 x declaration of conformity

## **PSSO WISE Headset for Bodypack**

Headset microphone for WISE bodypack transmitter

- Polar pattern: Omnidirectional

## Package contents

- 1 x microphone, 2 x windshield

## **Technical specifications:**

Weight: 3,50 kg

## PSSO WISE TWO 2-Channel True Diversity Receiver 823-832/863-865MHz

| Type:              | Receiver  |
|--------------------|---|
| Power supply:      | 100-240 V AC, 50/60 Hz  |
|                    | 12-15 V DC 1,5 A  |
| Power consumption: | 8 W   |
| Power connection:  | Mains input via Coaxial power connector (M) mounting version power supply cord with AC adapter (provided) |

| Number of channels:  | 2   |
|----------------------|---|
| Frequency range:     | 50 - 20000 Hz   |
| S/N ratio:           | >96 dB  |
| THD:                 | <0,1 % at 1 kHz   |
| Gain:                | Microphone -32 dB to +4 dB  |
|                      | Output: -32 dB to +4 dB   |
| Range:               | Range up to 60m with line-of-sight                                  |
| Frequency band:      | UHF 823 - 832 MHz; UHF 863 - 865 MHz                                |
| Diversity:           | True diversity  |
| Modulation:          | FM  |
| Frequency selection: | 45 Switchable frequencies   |
|                      | In 5 groups   |
|                      | Frequencies automatically scannable                                 |
| Display type:        | Multicolor LCD display  |
| Control elements:    | Power switch, groundlift selector, menu, encoder                    |
| Connections:         | Antenna via 2 x BNC (F) 12-15 V                                     |
|                      | Antenna via 1 x SMA (F) mounting version                            |
|                      | Output: mic/line via 2 x 3-pin XLR                                  |
|                      | Output: mic/line via 2 x 6.3 mm jack socket (mono) mounting version |
|                      | Output: for audio/data link via 2 x BNC (F)                         |
| Channels:            | Microphon chanal: 2 x mono with Mic-line switch via XLR or jack     |
| Switch:              | Low cut switch  |
| Material:            | Metal   |
| Color:               | Black   |
| PC connect:          | , firmware can be updated   |
| Housing design:      | (19") 48.3 cm rack installation 1 U                                 |
| Dimensions:          | Width: 48 cm  |
|                      | Depth: 27 cm  |
|                      | Height: 4,3 cm  |
| Weight:              | 2,9 kg  |
|                      |   |

# PSSO WISE Dynamic Wireless Microphone 823-832/863-865MHz

| 3 V DC                               |
|--------------------------------------|
|                                      |
| Battery/battery pack                 |
| Dynamic                              |
| Cardioid                             |
| 2 x Mignon (AA) (not included)       |
| 50 - 18000 Hz                        |
| -74 dB                               |
| -32 dB to +4 dB                      |
| Range up to 60m with line-of-sight   |
| UHF 863 - 865 MHz; UHF 823 - 832 MHz |
| 50 mW (HI); 10 mW (LO)               |
|                                      |

| Modulation:          | FM                                  |
|----------------------|-------------------------------------|
| Frequency selection: | Switchable frequencies              |
| Display type:        | Multicolor LCD display              |
| Control elements:    | Menu, navigation keys               |
| Color code:          | Color indicator and name adjustable |
| Switch:              | On/off/mute switch                  |
| Material:            | Aluminum                            |
| Dimensions:          | Length: 26,5 cm                     |
|                      | Diameter: Ø 5,2 cm                  |
| Weight:              | 390 g                               |

# PSSO WISE Bodypack 823-832/863-865MHz

| Pocket transmitter   |
|--|
| 3 V DC   |
| Battery/battery pack                                       |
| 2 x Mignon (AA) (not included)                             |
| 50 - 18000 Hz  |
| -32 dB to +4 dB  |
| Range up to 60m with line-of-sight                         |
| UHF 823 - 832 MHz; UHF 863 - 865 MHz                       |
| 50 mW (HI); 10 mW (LO)                                     |
| FM   |
| Switchable frequencies                                     |
| Multicolor LCD display                                     |
| Menu, navigation keys                                      |
| Microphone via 1 x Mini XLR (M) 3-pin mounting version 5 V |
| Color indicator and name adjustable                        |
| On/off switch; Mute control                                |
| Aluminum   |
| Grey   |
| Width: 7 cm  |
| Depth: 3 cm<br>Height: 13 cm                               |
| 190 g  |
|  |

# **PSSO WISE Headset for Bodypack**

| Headset microphone |
|--------------------|
| 2-10 V DC          |
| 1,5 m              |
| Electret           |
| Omnidirectional    |
| 100 - 20000 Hz     |
|                    |

| S/N ratio:   | >58 dB             |
|--------------|--------------------|
| Sensitivity: | -45 dB             |
| Impedance:   | 1 kOhm<br>1000 Ohm |
| Connections: | Mini XLR (F) 3-pin |
| Material:    | Metal              |
| Color:       | Skin-colored       |
| Dimensions:  | Diameter: Ø 3,5 mm |
| Weight:      | 20 g               |