

EUROLITE Set LED SLS-30 COB WW + Stand

LED floor spot with 30 W COB LED in WW including speaker stand and knob

Art. No.: 20000794

GTIN: 4026397687378



Features:

- DMX and power terminals intelligently designed for easy wiring
- 1 LED 30 W COB (chip-on-board) warm white (WW)
- Dimmer electronic
- Strobe effect
- Integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; master/slave function; IR remote control; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Fixtures available for Light´J; Light Captain; Colorchief
- Flicker-free
- With a beam angle of 18°
- Very high color rendering index (CRI)
- With double bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; decoration; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels
- Application possibility: Standing; suspended
- <p>OMNITRONIC Speaker Stand BOB System
- <h2 class="featureSatz">Speaker stand for BOB speakers, extendable up to 170 cm</h2>Tube diameter: Ø 30 mm
- Adjustable height
- Scratchproof and shockproof

Logistic

EAN / GTIN: 4026397687378

Weight: 4,00 kg

Length: 1.30 m

Width: 0.50 m

Height: 0.30 m

Bulky product

Technical specifications:

Weight:	3.26 kg
---------	---------

EUROLITE LED SLS-30 COB WW Floor

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	25 W
IP classification:	IP20
Protection class:	Protection class II
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug included
Power output:	Safety contact (F), mounting version
Device fuse:	T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 30 W COB (chip-on-board) warm white (WW)
Flash rate:	0 - 20 Hz
DMX channels:	1; 2; 4
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; master/slave function; IR remote control; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light´J; Light Captain; Colorchief
Projection:	Flicker-free
Beam angle:	18°
Beam angle (1/2 peak):	18°
Beam angle (1/10 peak):	65°
Color temperature:	3000K
Color rendering index (CRI):	97 Ra
Housing color:	Black
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
Material:	Plastic
Dimensions:	Width: 21.5 cm Depth: 12.7 cm Height: 22.85 cm
Weight:	1.10 kg
Noise classification:	Class 3 (clearly perceptible sounds); class 3 (clearly perceptible sounds)

Photobiological safety:	Risk Group 0
Diameter mounting holes:	1 x Ø11mm; 2 x Ø10mm
Material:	Metal, 1.5 mm
Cable construction:	3 x 0.75 mm² H05VV-F
Cable length:	Approx. 1.2 m
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

OMNITRONIC Speaker Stand BOB System

Maximum carrying capacity:	14 kg
Height:	Maximum: 195 cm Minimum: 107 cm Adjustable in 6 steps with locking pin
Attachment system:	M10 thread
Type (general stands):	Speaker stand/manual
Material:	Steel
Color:	Black, painted; , scratchproof and shockproof
Main pipe diameter:	Ø 3 cm
Extension tube diameter:	Ø 2.5 cm
Weight:	2.15 kg

Scope of delivery:

1 x EUROLITE LED SLS-30 COB WW Floor

1 x spotlight
1 x power cord
1 x remote control
1 x user manual

1 x OMNITRONIC Speaker Stand BOB System

1 x stand
1 x user manual