

## EUROLITE Set LED CBB-2 COB WW + Stand

LED light effect bar with WW COB LEDs including speaker stand and knob

Art. No.: 20000795

GTIN: 4026397687385



**List price: 172.55 €**

incl. 19% VAT.

### Features:

#### EUROLITE LED CBB-2 COB WW Bar

LED light effect bar with WW COB LEDs, incl. IR remote control

- 2 powerful LEDs 35 W COB (chip-on-board) warm white (WW)
- Dimmer electronic
- Strobe effect
- Integrated show programs
- The device is cooled by cooling fan
- Control via IR remote control; Sound to light via Microphone; DMX; stand-alone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 37°
- Very high color rendering index (CRI)
- With Mounting bracket
- 4 digit 7-segment LED display
- Preprogrammed in LED PC-Control 512; Light Captain; Light J
- Mains input and output for power linking up to 8 units
- For application areas such as: Trade fair and shop fitting; Stage; theater; video and photography
- Application possibility: Standing; suspended; on stand

#### Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

### Logistic

EAN / GTIN: 4026397687385

Weight: 6,00 kg

Length: 1.20 m

Width: 0.60 m

Height: 0.60 m

Bulky product

### OMNITRONIC Speaker Stand BOB System

Speaker stand for BOB speakers, extendable up to 170 cm

- Tube diameter: Ø 30 mm
- Adjustable height
- Scratchproof and shockproof

**Package contents**

- 1 x stand, 1 x user manual

**Technical specifications:**

Weight: 4,61 kg

**EUROLITE LED CBB-2 COB WW Bar**

|                              |  |
|------------------------------|--|
| Power supply:                | 100-240 V AC, 50/60 Hz   |
| Power consumption:           | 50 W   |
| IP classification:           | IP20   |
| Lamp type:                   | LED lamp   |
| LED:                         | 2 x 35 W COB (chip-on-board) warm white (WW)   |
| Color temperature:           | 2700K  |
| Flash rate:                  | 0 - 20 Hz  |
| DMX channels:                | 2; 3; 5  |
| DMX input:                   | 1 x 3-pin XLR (M) mounting version   |
| DMX output:                  | 1 x 3-pin XLR (F) mounting version   |
| Cooling:                     | Cooling fan  |
| Control:                     | IR remote control; Sound to light via Microphone; DMX; stand-alone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Preprogrammed in:            | LED PC-Control 512; Light Captain; Light´J   |
| Projection:                  | Flicker-free   |
| Beam angle:                  | 37°  |
| Beam angle (1/2 peak):       | 37°  |
| Beam angle (1/10 peak):      | 70°  |
| Color rendering index (CRI): | 91 Ra  |
| Housing color:               | Black  |
| Attachment system:           | Mounting bracket   |
| Display type:                | 4 digit 7-segment LED display  |
| Dimensions:                  | Width: 15,5 cm<br>Depth: 24 cm<br>Height: 17,5 cm  |
| Weight:                      | 2,45 kg  |
| Noise classification:        | Class 2 (slight noise)   |
| Photobiological safety:      | Risk Group 0   |
| Remote control               |  |
| Battery:                     | 1 x Button cell 3.0 V CR2025 lithium manganese built-in  |

Legal specifications

---

|                  |  |
|------------------|--|
| Special product: | Not designed for household room illumination |
| Intended use:    | Show effect lighting                         |

---

**OMNITRONIC Speaker Stand BOB System**

---

|                            |  |
|----------------------------|--|
| Maximum carrying capacity: | 14 kg  |
| Height:                    | Maximum: 195 cm<br>Minimum: 107 cm<br>Adjustable in 6 steps with locking pin |
| Attachment system:         | M10 thread   |
| Type (general stands):     | Speaker stand/manual   |
| Material:                  | Steel  |
| Color:                     | Black, painted; , scratchproof and shockproof                                |
| Main pipe diameter:        | Ø 3 cm   |
| Extension tube diameter:   | Ø 2,5 cm   |
| Weight:                    | 2,15 kg  |

---