

## EUROLITE Set LED THA-40PC TRC + Stand

Fanless PC spot with 57 W white light LED including speaker stand

Art. No.: 20000799

GTIN: 4026397687422



**List price: 296.31 €**

incl. 19% VAT.

### Features:

#### EUROLITE LED THA-40PC TRC Theater-Spot bk

Fanless PC spot with 57 W white light LED, color rendering index (CRI) >90

- Rugged metal housing
- 1 powerful LED 57 W COB (chip-on-board) warm white (WW)
- Dimmer electronic
- The device is cooled by passive convection cooling
- Control via stand-alone; Rotary dial for brightness; Dimmer
- Flicker-free
- With a beam angle of 12° - 47°
- Very high color rendering index (CRI)
- With Mounting bracket
- Silent operation
- For application areas such as: Trade fair and shop fitting; Wedding/gala/events; restaurants, bars and hotels; video and photography
- Rubber feet

#### Package contents

- 1 x spotlight, 1 x barndoor, 1 x filter frame, 1 x user manual

### Logistic

EAN / GTIN: 4026397687422

Weight: 7,00 kg

Length: 1.20 m

Width: 0.60 m

Height: 0.60 m

Bulky product

#### OMNITRONIC Speaker Stand BOB System

Speaker stand for BOB speakers, extendable up to 170 cm

- Tube diameter: Ø 30 mm
- Adjustable height
- Scratchproof and shockproof

#### Package contents

- 1 x stand, 1 x user manual

## Technical specifications:

---

Weight: 5,98 kg

---

### EUROLITE LED THA-40PC TRC Theater-Spot bk

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	40 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Fuse:	5 x 20 mm, T 1 A Fuse replaceable
LED:	1 x 57 W COB (chip-on-board) warm white (WW)
Color temperature:	3100K
Cooling:	Passive convection cooling
Control:	Stand-alone; Rotary dial for brightness; Dimmer
Projection:	Flicker-free
Beam angle:	12° - 47°
Beam angle (1/2 peak):	12 - 36°
Beam angle (1/10 peak):	18 - 47°
Color rendering index (CRI):	92 Ra
Illuminance in Lux (lx):	Narrow 3m: 2008 lx, 6m: 514 lx Wide 3m: 482 lx, 6m: 141 lx
Housing color:	Black
Attachment system:	Mounting bracket
Transport aid:	Rubber feet
Material:	Aluminum casting
Slot for spot length:	13,1 cm x 13,1 cm
Dimensions:	Length: 26 cm Width: 20 cm Depth: 25 cm
Weight:	3,82 kg
Noise classification:	Class 0 (no noise at all)
Power cord	
Cable construction:	3 x 0,75 mm <sup>2</sup> H05VV-F
Cable length:	Approx. 1 m
Mounting bracket	
Diameter mounting holes:	1 x Ø10mm; 2 x Ø6mm
Material:	Metal, 3 mm
Barndoor	
Material:	Aluminum, 1,5 mm; metal

Ring diameter:	Outside: 12,9 mm Inside: 10,9 mm
<b>Filter frame</b>	
Diameter mounting holes:	1 x Ø4mm
Shape:	Octagonal
Material:	Aluminum, 0,8 mm
Dimensions:	Width: 13 cm Height: 13 cm Diameter: Ø 10,5 cm
<b>Legal specifications</b>	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

### **OMNITRONIC Speaker Stand BOB System**

Maximum carrying capacity:	14 kg
Height:	Maximum: 195 cm Minimum: 107 cm Adjustable in 6 steps with locking pin
Attachment system:	M10 thread
Type (general stands):	Speaker stand/manual
Material:	Steel
Color:	Black, painted; , scratchproof and shockproof
Main pipe diameter:	Ø 3 cm
Extension tube diameter:	Ø 2,5 cm
Weight:	2,15 kg