eurolite®


EUROLITE Set 10x LED PR-100/32 Pixel DMX Rail bk + DMX Software

10x DMX-controllable pixel rail with RGB color mixing incl. USB interface and Art-Net interface

Art. No.: 20000806 GTIN: 4026397687934







incl. 19% VAT.

Features:

EUROLITE LED PR-100/32 Pixel DMX rail bk

DMX controlled pixel tube with RGB color mixing

- DMX and power terminals intelligently designed for easy wiring
- Front cover: black
- 96 powerful LEDs SMD 5050 3in1 TCL RGB (homogenous color mix)
32 segments controlled separately
- Color blend stepless; color change adjustable; colors preset; Dimmer electronic
- 12 integrated show programs
- Direct color selection for 17 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone
- Preprogrammed in Light Captain
- With a beam angle of 120°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; Trade fair and shop fitting; stage; restaurants, bars and hotels
- Silent operation
- Application possibility: Suspended; wall mounting
- Package contents
- 1 x light effect, 1 x user manual, 1 x power cord

EUROLITE USB Interface 2x512 DMX/Artnet incl. 64x DMX512 Control Software

USB interface for 2 DMX universes with 3 lighting control softwares

Logistic

EAN / GTIN: 4026397687934 Weight: 29,00 kg Length: 1.20 m Width: 0.60 m Heigth: 0.40 m Bulky product

- LED PC Control (architectural lighting)
- DMX Control (show lighting)
- Pixel Control (pixel mapping and video mixing)
- 64 Art-Net universes with 512 channels each on Ethernet
- 32,768 individual channels or 10,922 RGB pixels
- High DVI resolution output (1024 x 768 pixels)
- Supports touch screen controls
- Can transmit up to 1024 DMX channels
- Control via DMX
- The device can be connected via USB to the PC
- For application areas such as: Clubs/dancing school; Trade fair and shop fitting; installation; restaurants, bars and hotels

Package contents

- 1 x device, 1 x USB cable

EUROLITE Art-Net/DMX Node 8 MK2

Art-Net interface for output of 8 universes on XLR

- Parallel DMX input possible (1024 channels)
- 8 optically isolated XLR plugs (3-pin) for DMX output
- 2 XLR jacks (3-pin) for DMX input
- Variable data routing capabilities for all DMX outputs
- User-friendly configuration directly at the front panel via 4 operating buttons and alphanumeric LCD screen (2 x 16 characters)
- LED indication for functions
- Splitter operation possible
- Can transmit up to 4096 DMX channels
- Control via Art-Net
- The device can be connected via RJ-45 (F) mounting version to the PC
- (19") 48.3 cm rack installation
- Package contents
- 1 x device, 1 x user manual, 1 x power cord

Technical specifications:

Weight:

22,68 kg

EUROLITE LED PR-100/32 Pixel DMX rail bk

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	30 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version
Lamp type:	LED lamp
LED type:	96 x SMD 5050 3in1 TCL RGB (homogenous color mix)
Flash rate:	0,25 - 10 Hz
DMX channels:	3; 5; 8; 48; 96
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version

Passive convection cooling
Stand-alone; DMX; sound to light via microphone
Light Captain
120°
120°
Black
Mounting bracket
4 digit 7-segment LED display
Length: 99,9 cm Width: 5,95 cm Height: 13,2 cm
2,01 kg
Class 0 (no noise at all)
Not designed for household room illumination
Show effect lighting

EUROLITE USB Interface 2x512 DMX/Artnet incl. 64x DMX512 Control Software

5V DC 1000 mA Mains input via micro USB (F) mounting version power supply cord for USB A mains connection (provided)
power supply cord for USB A mains connection
W /
Output 1024
2 x 3-pin XLR (F) mounting version
DMX
USB 2.0, type mini USB (F) mounting version
Black
Via USB
Width: 7 cm
Depth: 9 cm
Height: 4,5 cm
,

EUROLITE Art-Net/DMX Node 8 MK2

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	5 W
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
DMX channels:	Output 4096
DMX input:	2 x 3-pin XLR (M) mounting version
DMX output:	8 x 3-pin XLR (F) mounting version
Network connection:	Protocol: Art-Net 3 via 2x RJ-45 (F) mounting version
Control:	Art-Net

Connections:	2 x RJ-45 E-Con (F) mounting version
PC connect:	Via RJ-45 (F) mounting version
Housing design:	(19") 48.3 cm rack installation
Dimensions:	Width: 48,3 cm
	Depth: 17,5 cm
	Height: 4,45 cm
Weight:	2,40 kg