

EUROLITE Set 2x LED CBB-2 COB RGB Bar + Case

2x LED light effect bar with RGB color mixing including PRO flightcase

Art. No.: 2000808

GTIN: 4026397687958



List price: 593.81 €

incl. 19% VAT.

Features:

EUROLITE LED CBB-2 COB RGB Bar

LED light effect bar with RGB color mixing, incl. IR remote control

- 2 powerful LEDs 30 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Integrated show programs
- Direct color selection for 18 preset colors
- The device is cooled by cooling fan
- Control via IR remote control; Sound to light via Microphone; stand-alone; Master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional)
- Flicker-free
- With a beam angle of 38°
- With Mounting bracket
- 4 digit 7-segment LED display
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; Stage; theater; mobile djs / entertainer
- Application possibility: Standing; suspended; on stand

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

Logistic

EAN / GTIN: 4026397687958

Weight: 12,00 kg

Length: 0.82 m

Width: 0.41 m

Height: 0.52 m

ROADINGER Flightcase 2 x LED CBB-2 COB Bar

Trunk case, PRO version

- For optimal security
- With accessory compartment
- High-quality workmanship with birch multiplex 6,5 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 20mm with rounded edges
- Hinged, chromium plated case handle
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- Branded hardware

Technical specifications:

Weight: 9,75 kg

EUROLITE LED CBB-2 COB RGB Bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	50 W
IP classification:	IP20
Lamp type:	LED lamp
LED:	2 x 30 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 4; 5; 6; 11
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	IR remote control; Sound to light via Microphone; stand-alone; Master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional)
Preprogrammed in:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	38°
Beam angle (1/2 peak):	38°
Beam angle (1/10 peak):	70°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 15,5 cm Depth: 24 cm Height: 17,5 cm
Weight:	2,45 kg
Noise classification:	Class 2 (slight noise)
Photobiological safety:	Risk Group 0

Legal specifications

Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 2 x LED CBB-2 COB Bar

Maximum load:	25 kg
Aluminum profile frames:	20 mm
Case handle:	1 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 6,5 mm, laminated; birch multiplex, 7 mm
Color:	Dark brown, laminated
Device compartment:	12 cm x 26 cm x 19,5 cm
Middle compartment:	10,5 cm x 26 cm x 19,5 cm
Inside dimensions:	34,5 cm x 26 cm x 19,5 cm
Dimensions:	Width: 30 cm Depth: 41 cm Height: 30 cm
Weight:	4,85 kg
