

EUROLITE Set 2x LED CBB-2 COB RGB Bar + Case

2x LED light effect bar with RGB color mixing including PRO flightcase

Art. No.: 2000808

GTIN: 4026397687958



Features:

- 2 LEDs 30 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Integrated show programs
- Direct color selection for 18 preset colors
- The device is cooled by cooling fan
- Control via IR remote control; sound to light via microphone; stand-alone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional)
- Fixtures available for LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- With a beam angle of 38°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; stage; decoration; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Standing; suspended; on stand
- <p>ROADINGER Flightcase 2 x LED CBB-2 COB Bar
- <h2 class="featureSatz">Trunk case, PRO version</h2>For optimal security
- With accessory compartment
- High-quality workmanship with birch multiplex 6.5 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 20mm with rounded edges
- Hinged, chromium plated case handle

Logistic

EAN / GTIN: 4026397687958

Weight: 12,00 kg

Length: 0.82 m

Width: 0.41 m

Height: 0.52 m

- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- Branded hardware

Technical specifications:

Weight: 9.63 kg

EUROLITE LED CBB-2 COB RGB Bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	50 W
IP classification:	IP20
Lamp type:	LED lamp
LED type:	2 x 30 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
Flash rate:	0.5 - 24 Hz
DMX channels:	3; 4; 5; 6; 11
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	IR remote control; sound to light via microphone; stand-alone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional)
Fixtures available for:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
PWM frequency:	2900 Hz
Beam angle:	38°
Beam angle (1/2 peak):	38°
Beam angle (1/10 peak):	70°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Material:	Metal
Dimensions:	Width: 15.5 cm Depth: 24 cm Height: 17.5 cm
Weight:	2.39 kg
Noise classification:	Class 2 (slight noise)
Photobiological safety:	Risk Group 0
Diameter mounting holes:	3 x Ø11mm; 4 x Ø7mm
Material:	Metal, 2 mm

Battery:	1 x button cell CR2025
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 2 x LED CBB-2 COB Bar

Maximum load:	25 kg
Aluminum profile frames:	20 mm
Case handle:	1 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 6.5 mm, laminated; birch multiplex, 7 mm
Color:	Dark brown, laminated
Device compartment:	12 cm x 26 cm x 19.5 cm
Middle compartment:	10.5 cm x 26 cm x 19.5 cm
Inside dimensions:	34.5 cm x 26 cm x 19.5 cm
Dimensions:	Width: 30 cm Depth: 41 cm Height: 30 cm
Weight:	4.85 kg

Scope of delivery:

- 1 x spotlight
- 1 x power cord
- 1 x remote control
- 1 x battery
- 1 x user manual