

## EUROLITE Set 2x LED CBB-2 COB WW Bar + Case

2x LED light effect bar with WW COB Leds including PRO flightcase

Art. No.: 20000810

GTIN: 4026397687972



**List price: 570.01 €**

incl. 19% VAT.

### Features:

#### EUROLITE LED CBB-2 COB WW Bar

LED light effect bar with WW COB LEDs, incl. IR remote control

- 2 powerful LEDs 35 W COB (chip-on-board) warm white (WW)
- Dimmer electronic
- Strobe effect
- Integrated show programs
- The device is cooled by cooling fan
- Control via IR remote control; Sound to light via Microphone; DMX; stand-alone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 37°
- Very high color rendering index (CRI)
- With Mounting bracket
- 4 digit 7-segment LED display
- Preprogrammed in LED PC-Control 512; Light Captain; Light J
- Mains input and output for power linking up to 8 units
- For application areas such as: Trade fair and shop fitting; Stage; theater; video and photography
- Application possibility: Standing; suspended; on stand

#### Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

### Logistic

EAN / GTIN: 4026397687972

Weight: 12,00 kg

Length: 0.82 m

Width: 0.41 m

Height: 0.52 m

#### ROADINGER Flightcase 2 x LED CBB-2 COB Bar

Trunk case, PRO version

- For optimal security
- With accessory compartment
- High-quality workmanship with birch multiplex 6,5 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 20mm with rounded edges
- Hinged, chromium plated case handle
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- Branded hardware

## Technical specifications:

---

Weight: 9,75 kg

---

### EUROLITE LED CBB-2 COB WW Bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	50 W
IP classification:	IP20
Lamp type:	LED lamp
LED:	2 x 35 W COB (chip-on-board) warm white (WW)
Color temperature:	2700K
Flash rate:	0 - 20 Hz
DMX channels:	2; 3; 5
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	IR remote control; Sound to light via Microphone; DMX; stand-alone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	LED PC-Control 512; Light Captain; Light J
Projection:	Flicker-free
Beam angle:	37°
Beam angle (1/2 peak):	37°
Beam angle (1/10 peak):	70°
Color rendering index (CRI):	91 Ra
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 15,5 cm Depth: 24 cm Height: 17,5 cm
Weight:	2,45 kg
Noise classification:	Class 2 (slight noise)
Photobiological safety:	Risk Group 0

Remote control

---

Battery: 1 x Button cell 3.0 V CR2025 lithium manganese built-in

---

Legal specifications

---

Special product: Not designed for household room illumination

---

Intended use: Show effect lighting

---

**ROADINGER Flightcase 2 x LED CBB-2 COB Bar**

---

Maximum load: 25 kg

---

Aluminum profile frames: 20 mm

---

Case handle: 1 pc/pcs

---

Stop hinge: 2 pc/pcs

---

Lock: Butterfly lock: 1 pc/pcs

---

Use of brands: Branded hardware

---

Material: Birch multiplex, 6,5 mm, laminated; birch multiplex, 7 mm

---

Color: Dark brown, laminated

---

Device compartment: 12 cm x 26 cm x 19,5 cm

---

Middle compartment: 10,5 cm x 26 cm x 19,5 cm

---

Inside dimensions: 34,5 cm x 26 cm x 19,5 cm

---

Dimensions: Width: 30 cm  
Depth: 41 cm  
Height: 30 cm

---

Weight: 4,85 kg

---