

EUROLITE Set 4x LED CBB-2 COB WW Bar + Case

4x LED light effect bar with WW COB Leds including PRO flightcase

Art. No.: 20000811 GTIN: 4026397687989







List price: 927.01 €

incl. 19% VAT.

Features:

EUROLITE LED CBB-2 COB WW Bar

LED light effect bar with WW COB LEDs, incl. IR remote control

- 2 powerful LEDs 35 W COB (chip-on-board) warm white (WW)
- Dimmer electronic
- Strobe effect
- Integrated show programs
- The device is cooled by cooling fan
- Control via IR remote control; Sound to light via Microphone; DMX; stand-alone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 37°
- Very high color rendering index (CRI)
- With Mounting bracket
- 4 digit 7-segment LED display
- Preprogrammed in LED PC-Control 512; Light Captain; Light'J
- Mains input and output for power linking up to 8 units
- For application areas such as: Trade fair and shop fitting; Stage; theater; video and photography
- Application possibility: Standing; suspended; on stand

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

ROADINGER Flightcase 4 x LED CBB-2 COB Bar

Trunk case, PRO version

Logistic

EAN / GTIN: 4026397687989

Weight: 20,00 kg Length: 1.20 m Width: 0.41 m Heigth: 0.30 m Bulky product

- For optimal security
- With accessory compartment
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 20mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Branded hardware

Technical specifications:

Weight: 17,65 kg

EUROLITE LED CBB-2 COB WW Bar

| Power supply: | 100-240 V AC, 50/60 Hz |
|------------------------------|--|
| Power consumption: | 50 W |
| IP classification: | IP20 |
| Lamp type: | LED lamp |
| LED: | 2 x 35 W COB (chip-on-board) warm white (WW) |
| Color temperature: | 2700K |
| Flash rate: | 0 - 20 Hz |
| DMX channels: | 2; 3; 5 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | Cooling fan |
| Control: | IR remote control; Sound to light via Microphone; DMX; stand-alone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Preprogrammed in: | LED PC-Control 512; Light Captain; Light'J |
| Projection: | Flicker-free |
| Beam angle: | 37° |
| Beam angle (1/2 peak): | 37° |
| Beam angle (1/10 peak): | 70° |
| Color rendering index (CRI): | 91 Ra |
| Housing color: | Black |
| Attachment system: | Mounting bracket |
| Display type: | 4 digit 7-segment LED display |
| Dimensions: | Width: 15,5 cm Depth: 24 cm Height: 17,5 cm |
| Weight: | 2,45 kg |
| Noise classification: | Class 2 (slight noise) |
| Photobiological safety: | Risk Group 0 |
| | |

| Battery: | 1 x Button cell 3.0 V CR2025 lithium manganese built-in |
|----------------------|---|
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Flightcase 4 x LED CBB-2 COB Bar

| Maximum load: | 50 kg |
|--------------------------|---|
| Aluminum profile frames: | 20 mm |
| Case handle: | 2 pc/pcs |
| Stop hinge: | 2 pc/pcs |
| Lock: | Butterfly lock: 2 pc/pcs |
| Use of brands: | Branded hardware |
| Material: | Birch multiplex, 7 mm, laminated; birch multiplex |
| Color: | Dark brown, laminated |
| Device compartment: | 25 cm x 12 cm x 25 cm |
| Accessory compartment: | 10 cm x 27 cm x 25 cm |
| Inside dimensions: | 63,5 cm x 27 cm x 25 cm |
| Dimensions: | Width: 68 cm |
| | Depth: 31 cm |
| | Height: 29 cm |
| Weight: | 7,85 kg |