

EUROLITE Set 4x Audience Blinder 2x100W LED COB WW + Case

4x audience blinder with 2x 100 W COB LED in warm white including flightcase

Art. No.: 20000813

GTIN: 4026397688344



The article is no longer in our assortment.

Features:

EUROLITE Audience Blinder 2x100W LED COB WW

Audience blinder with 2x 100 W COB LED, warm white

- DMX and power terminals intelligently designed for easy wiring
- 2 powerful LEDs 100 W COB (chip-on-board) warm white (WW)
 LEDs controlled separately
- Strobe effect
- 9 integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Preprogrammed in Light Captain; Light´J
- Flicker-free
- With a beam angle of 70°
- Very high color rendering index (CRI)
- With mounting bracket
- LCD display
- Mains input and output for power linking up to 8 units
- For application areas such as: Mobile use; stage; rental
- Application possibility: Suspended; on stand

Package contents

- 1 x spotlight, 1 x power cord, 1 x user manual

Logistic

EAN / GTIN: 4026397688344

Weight: 42,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.75 m

Bulky product

ROADINGER Flightcase 4x Audience Blinder 2x100W with wheels

Hood case with castors, PRO version

- High-quality workmanship with birch multiplex 7 mm, black, laminated
- Castors
- Branded hardware

Technical specifications:

Weight:	38,38 kg
---------	----------

EUROLITE Audience Blinder 2x100W LED COB WW

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	200 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 3 A fuse replaceable
Lamp type:	LED lamp
LED type:	2 x 100 W COB (chip-on-board) warm white (WW)
Flash rate:	0 - 20 Hz
DMX channels:	2; 4; 6
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light Captain; Light J
Projection:	Flicker-free
Beam angle:	70°
Beam angle (1/2 peak):	70°
Color temperature:	3100K
Color rendering index (CRI):	97 Ra
Wavelength:	632 nm
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Material:	Metal
Dimensions:	Width: 41 cm Depth: 15,3 cm Height: 22,4 cm
Weight:	5,22 kg
Noise classification:	Class 2 (slight noise)

Photobiological safety:	Risk Group 0
Cable construction:	3 x 1,0 mm² H05VV-F
Cable length:	Approx. 1,2 m
Diameter mounting holes:	3 x Ø11mm
Material:	Metal, 4 mm
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x Audience Blinder 2x100W with wheels

Maximum load:	50 kg
Transport aid:	Castors
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Black, laminated
Device compartment:	16,5 cm x 40 cm x 20 cm
Accessory compartment:	10,5 cm x 44 cm x 21 cm
Dimensions:	Width: 93 cm Depth: 48 cm Height: 43 cm
Weight:	17,50 kg