

## EUROLITE Set 4x Audience Blinder 2x100W LED COB WW + Case

4x audience blinder with 2x 100 W COB LED in warm white including flightcase

Art. No.: 20000813

GTIN: 4026397688344



### Features:

- DMX and power terminals intelligently designed for easy wiring
- 2 LEDs 100 W COB (chip-on-board) warm white (WW)<BR> LEDs controlled separately
- Strobe effect
- 9 integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Fixtures available for Light Captain; Light´J
- Flicker-free
- With a beam angle of 70°
- Very high color rendering index (CRI)
- With mounting bracket
- LCD display
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; theater; rental
- Application possibility: Suspended; on stand
- <p>ROADINGER Flightcase 4x Audience Blinder 2x100W with wheels
- <h2 class="featureSatz">Hood case with castors, PRO version</h2>High-quality workmanship with birch multiplex 7 mm, black, laminated
- Castors
- Branded hardware

### Logistic

EAN / GTIN: 4026397688344

Weight: 42,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.75 m

Bulky product

## Technical specifications:

|         |          |
|---------|----------|
| Weight: | 38.38 kg |
|---------|----------|

### EUROLITE Audience Blinder 2x100W LED COB WW

|                              |                                                                                                                                           |
|------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:                | 100-240 V AC, 50/60 Hz                                                                                                                    |
| Power consumption:           | 200 W                                                                                                                                     |
| IP classification:           | IP20                                                                                                                                      |
| Protection class:            | Protection class I                                                                                                                        |
| Power connection:            | Mains input via P-Con (blue), mounting version<br>power supply cord with safety plug (provided)                                           |
| Power output:                | 1 x P-Con (gray), mounting version                                                                                                        |
| Fuse:                        | 5 x 20 mm, T 3 A fuse replaceable                                                                                                         |
| Lamp type:                   | LED lamp                                                                                                                                  |
| LED type:                    | 2 x 100 W COB (chip-on-board) warm white (WW)                                                                                             |
| Flash rate:                  | 0 - 20 Hz                                                                                                                                 |
| DMX channels:                | 2; 4; 6                                                                                                                                   |
| DMX input:                   | 1 x 3-pin XLR (M) mounting version                                                                                                        |
| DMX output:                  | 1 x 3-pin XLR (F) mounting version                                                                                                        |
| Cooling:                     | Cooling fan                                                                                                                               |
| Control:                     | Stand-alone; DMX; QuickDMX via USB (optional);<br>W-DMX by wireless solution via USB (optional);<br>CRMX by LumenRadio via USB (optional) |
| Fixtures available for:      | Light Captain; Light J                                                                                                                    |
| Projection:                  | Flicker-free                                                                                                                              |
| Beam angle:                  | 70°                                                                                                                                       |
| Beam angle (1/2 peak):       | 70°                                                                                                                                       |
| Color temperature:           | 3100K                                                                                                                                     |
| Color rendering index (CRI): | 97 Ra                                                                                                                                     |
| Wavelength:                  | 632 nm                                                                                                                                    |
| Housing color:               | Black                                                                                                                                     |
| Attachment system:           | Mounting bracket                                                                                                                          |
| Display type:                | LCD display                                                                                                                               |
| Material:                    | Metal                                                                                                                                     |
| Dimensions:                  | Width: 41 cm<br>Depth: 15.3 cm<br>Height: 22.4 cm                                                                                         |
| Weight:                      | 5.22 kg                                                                                                                                   |
| Noise classification:        | Class 2 (slight noise)                                                                                                                    |
| Photobiological safety:      | Risk Group 0                                                                                                                              |
| Cable construction:          | 3 x 1.0 mm² H05VV-F                                                                                                                       |

|                          |                                              |
|--------------------------|----------------------------------------------|
| Cable length:            | Approx. 1.2 m                                |
| Diameter mounting holes: | 3 x Ø11mm                                    |
| Material:                | Metal, 4 mm                                  |
| Special product:         | Not designed for household room illumination |
| Intended use:            | Show effect lighting                         |

#### **ROADINGER Flightcase 4x Audience Blinder 2x100W with wheels**

|                        |                                               |
|------------------------|-----------------------------------------------|
| Maximum load:          | 50 kg                                         |
| Transport aid:         | Castors                                       |
| Use of brands:         | Branded hardware                              |
| Material:              | Birch multiplex, 7 mm                         |
| Color:                 | Black, laminated                              |
| Device compartment:    | 16.5 cm x 40 cm x 20 cm                       |
| Accessory compartment: | 10.5 cm x 44 cm x 21 cm                       |
| Dimensions:            | Width: 93 cm<br>Depth: 48 cm<br>Height: 43 cm |
| Weight:                | 17.50 kg                                      |

#### **Scope of delivery:**

1 x spotlight  
1 x power cord  
1 x user manual