



List price: 677.11 €

incl. 19% VAT.

Features:

EUROLITE LED KLS Laser Bar Next FX Light Set

Bar with powerful spots, UV strobe LEDs, laser (RG, 2M), QuickDMX port and carrying bag

- 2 laser diodes project hundreds of red and green laser beams
 - 2 rotating derbies for mirror ball effects
 - Compact lightweight
 - Crossbar with integrated DMX control unit and TV spigot for tripod installation
 - For application areas such as: Wedding/gala/events; Clubs/dancing school; mobile djs / entertainer; small rental
 - When fog is used, this effect becomes especially attractive
 - 26 integrated show programs
 - Dimmer electronic; color blend stepless; program selection
 - Control via DMX; stand-alone; Sound to light via Microphone; IR remote control; QuickDMX via USB (optional); Wireless footswitch (optional)
 - TV spigot
 - With Mounting bracket
 - Mains input and output for power linking up to 8 units
 - Preprogrammed in Light Captain; EASY SHOW 2; EASY SHOW 3
 - Application possibility: On stand
- laser**
- Laser class 2M
 does not require additional protective measures or appointment of a laser safety officer
- spotlight**
- 3 powerful LEDs 4 W high-power 4in1 QCL RGB/WW (homogenous color mix)
4 spots controlled separately
 - With a beam angle of 7°
- light effect**

Logistic

EAN / GTIN: 4026397689075

Weight: 20,00 kg

Length: 1.36 m

Width: 0.34 m

Height: 0.06 m

Bulky product

- 4 powerful LEDs 3 W high-power R/G/B/WW
 lighting effects controlled separately
- Multi beam effect; fan effect; flower effect

bar

- 4 powerful LEDs 1,5 W high-power ultra violet (UV)
 LEDs controlled separately
- UV effect; Strobe effect

Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x bag, 1 x declaration of conformity, 1 x remote control, 2 x mounting bracket, 2 x knurled screw, 2 x washer, 1 x terminating plug (power)

OMNITRONIC M-4 Speaker-System Stand

Aluminum speaker stand, height adjustable 140-345 cm, maximum load 18 kg

- Durable aluminum version
- Tube diameter: Ø 35 mm
- Adjustable height

Package contents

- 1 x user manual

EUROLITE STV-3529 Adapter long

Massive adapter for 35 mm tube, 28 mm TV spigot, maximum load WLL 100 kg

- For stands with telescopic tube 35 mm
- Connection element for cross beam with 28 mm TV spigot
- With M6 and M8 fixation screw
- Heavy version for highest stability
- TV spigot

Package contents

- 1 x device, 1 x user manual, 2 x knurled screw

Technical specifications:

Weight: 15,30 kg

EUROLITE LED KLS Laser Bar Next FX Light Set

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	90 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Cable length:	3 m
Power output:	1 x P-Con (gray), mounting version
Fuse:	T 1 A Fuse replaceable
Lamp type:	LED lamp
DMX channels:	6; 8; 11; 21; 25; 29
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; stand-alone; Sound to light via Microphone; IR remote control; QuickDMX via USB (optional); Wireless footswitch (optional)

Preprogrammed in:	Light Captain; EASY SHOW 2; EASY SHOW 3
Housing color:	Black
Attachment system:	TV spigot Ø 28mm 2x Mounting bracket
Display type:	3 digit 7-segment LED display
Dimensions:	Width: 1,11 m Depth: 15 cm Height: 41 cm
Weight:	10,50 kg
Noise classification:	Class 2 (slight noise)
Laser	
Laser class:	2M
Laser color:	R/G
Laser module:	Red (R) 100 mW 650nm Green (G) 30 mW 532nm
Spotlight	
LED:	3 x 4 W high-power 4in1 QCL RGB/WW (homogenous color mix)
Beam angle:	7°
Beam angle (1/2 peak):	Spot 7°
Beam angle (1/10 peak):	Spot 20°
Light effect	
LED:	4 x 3 W high-power R/G/B/WW
Bar	
LED:	4 x 1,5 W high-power ultra violet (UV)
Flash rate:	0 - 30 Hz
Remote control	
Battery:	Button cell 3.0 V CR2025 lithium manganese built-in

OMNITRONIC M-4 Speaker-System Stand

Maximum carrying capacity:	18 kg
Tube diameter sector:	38 - 35 mm
Height:	Maximum: 345 cm Minimum: 140 cm Adjustable in 10 steps with locking pin
Attachment system:	Ø 35mm
Type (general stands):	Speaker stand/manual
Material:	Aluminum
Color:	Black
Transport dimensions:	1,4 m x 13,5 cm
Weight:	3,30 kg

EUROLITE STV-3529 Adapter long

Maximum load BGV C1 (8-fold):	50 kg
Max. load WLL (4-fold):	100 kg
Attachment system:	TV spigot Ø 28mm Ø 35mm
Type (general stands):	Accessory
Material:	Steel, 6 mm, powder-coated
Dimensions:	Width: 8,50 cm Depth: 5 cm Height: 19,50 cm
Weight:	1,50 kg