

EUROLITE Set LED KLS-902 + M-4 Speaker System Stand

Art. No.: 20000817

GTIN: 4026397689099



Features:

EUROLITE LED KLS-902 Next Compact Light Set

Bar with 4 powerful 4in1 QCL RGB/WW spots, QuickDMX support, IR remote control and carrying bag

- Crossbar with integrated DMX control unit and TV spigot for tripod installation
- Mounting points and power outlets for additional fixtures
- 5 LEDs 7 W SMD 9080 4in1 QCL RGB/WW (homogenous color mix)
 spots controlled separately
- Color blend stepless; Dimmer electronic; program selection
- 20 integrated show programs
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; sound to light via microphone; IR remote control; wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Fixtures available for EASY SHOW 1; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; Light J; EASY SHOW 3; Colorchief
- With a beam angle of 16°
- TV spigot
- With omega bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Mobile use; stage; mobile djs / entertainer; small rental; rental
- Very quiet working noise
- Application possibility: Suspended; on stand

Logistic

EAN / GTIN: 4026397689099

Weight: 20,00 kg

Length: 1.35 m

Width: 0.21 m

Height: 0.58 m

Bulky product

OMNITRONIC M-4 Speaker-System Stand

Aluminum speaker stand, height adjustable 140-345 cm, maximum load 18 kg

- Durable aluminum version
- Tube diameter: Ø 35 mm
- Adjustable height

EUROLITE STV-3529 Adapter long

Massive adapter for 35 mm tube, 28 mm TV spigot, maximum load WLL 100 kg

- For stands with telescopic tube 35 mm
- Connection element for cross beam with 28 mm TV spigot
- With M6 and M8 fixation screw
- Heavy version for highest stability
- TV spigot

Technical specifications:

Weight:	14.60 kg
---------	----------

EUROLITE LED KLS-902 Next Compact Light Set

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	125 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Cable length:	3 m
Power output:	2 x IEC connector (F) mounting version 1 x P-Con (gray), mounting version
Device fuse:	5 x 20 mm, T 2 A fuse replaceable
Power output fuse per channel:	5 x 20 mm, T 5 A fuse replaceable
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Lamp type:	LED lamp
LED type:	5 x 7 W SMD 9080 4in1 QCL RGB/WW (homogenous color mix)
DMX channels:	3; 4; 6; 8; 16; 20; 18
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; sound to light via microphone; IR remote control; wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	EASY SHOW 1; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; Light J; EASY SHOW 3; Colorchief
Beam angle:	16°
Beam angle (1/2 peak):	16°
Beam angle (1/10 peak):	32°

Housing color:	Black
Attachment system:	TV spigot Ø 28mm Omega bracket
Dimensions:	Width: 108 cm Depth: 6 cm Height: 28 cm
Weight:	9.80 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

OMNITRONIC M-4 Speaker-System Stand

Maximum carrying capacity:	18 kg
Tube diameter sector:	38 - 35 mm
Height:	Maximum: 345 cm Minimum: 140 cm Adjustable in 10 steps with locking pin
Attachment system:	Ø 35mm
Type (general stands):	Speaker stand/manual
Material:	Aluminum
Color:	Black
Transport dimensions:	140 cm x 13.5 cm
Weight:	3.30 kg

EUROLITE STV-3529 Adapter long

Maximum load BGV C1 (8-fold):	50 kg
Maximum load WLL (4-fold):	100 kg
Attachment system:	TV spigot Ø 28mm Ø 35mm
Type (general stands):	Accessory
Material:	Steel, 6 mm, powder-coated
Dimensions:	Width: 8.50 cm Depth: 5 cm Height: 19.50 cm
Weight:	1.50 kg

Scope of delivery:

1 x EUROLITE LED KLS-902 Next Compact Light Set

1 x light effect
 1 x user manual
 1 x power cord
 1 x remote control
 1 x battery
 2 x omega bracket
 1 x declaration of conformity
 4 x knurled screw
 1 x bag

1 x OMNITRONIC M-4 Speaker-System Stand

1 x user manual

1 x EUROLITE STV-3529 Adapter long

1 x device

1 x user manual

2 x knurled screw