



### Features:

#### EUROLITE LED TSL-250 Scan COB

Handy scanner with 30 W COB LED, gobo and color wheel

- Compact design
- 1 LED 30 W COB (chip-on-board)
- Positioning within
- Color wheel; gobo wheel with rotating gobos; focus manual
- Dimmer electronic
- Color wheel with 7 dichroic filters plus open<BR>half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with rotating gobos, 7 gobos and open<BR>gobos changeable
- Slot-in gobo system for easy gobo replacement
- Shake effect
- Integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 9°
- LCD display
- Rubber feet
- For application areas such as: Clubs/dancing school; party room; mobile djs / entertainer
- Application possibility: Standing; suspended; on stand

### Logistic

EAN / GTIN: 4026397688863

Weight: 20,00 kg

Length: 0.82 m

Width: 0.41 m

Heigh: 0.52 m

## ROADINGER Flightcase 2x LED TSL-150

PRO flightcase for 2 x LED TSL-150

- For optimal security
- With accessory compartment
- With 2 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 high-quality butterfly locks
- Rubber feet
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

---

Weight: 16.32 kg

---

## EUROLITE LED TSL-250 Scan COB

Power supply: 100-240 V AC, 50/60 Hz

---

Power consumption: 65 W

---

Protection class: Protection class I

---

Power connection: Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)

---

Device fuse: 5 x 20 mm, T 1 A fuse replaceable

---

Lamp type: LED lamp

---

LED type: 1 x 30 W COB (chip-on-board)

---

Equipment: Color wheel; gobo wheel with rotating gobos; focus manual

---

Color generation: Color wheel with 7 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions

---

Gobos: Gobo wheel with rotating gobos, 7 gobos and open  
Outside diameter 14mm  
Image diameter 10mm  
Gobos changeable  
Slot-in gobo system for easy gobo replacement  
Shake effect

---

DMX channels: 10

---

DMX input: 3-pin XLR (M) mounting version

---

DMX output: 3-pin XLR (F) mounting version

---

Cooling: Cooling fan

---

Control:	Stand-alone; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light J; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle (1/2 peak):	9°
Illuminance in Lux (lx):	Cold white (CW) 1m: 9123 lx, 3m: 955 lx, 6m: 149 lx
Housing color:	Black
Display type:	LCD display
Transport aid:	Rubber feet
Dimensions:	Width: 16.0 cm Depth: 15.0 cm Height: 33.0 cm
Weight:	3.16 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### **ROADINGER Flightcase 2x LED TSL-150**

Maximum load:	50 kg
Aluminum profile frames:	30 mm
Case handle:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	Rubber feet
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Device compartment:	21.5 cm x 24.5 cm x 27 cm
Accessory compartment:	11.5 cm x 24.5 cm x
Inside dimensions:	54.5 cm x 24.5 cm x
Dimensions:	Width: 61 cm Depth: 29 cm Height: 42.5 cm
Weight:	10.00 kg

#### **Scope of delivery:**

1 x device  
1 x user manual  
1 x power cord  
1 x mounting bracket  
2 x screw