



Features:

EUROLITE AKKU IP PAR 14 HCL QuickDMX

IP65 battery-powered spotlight with RGBWA+UV LEDs, QuickDMX, frost filter and IR remote control

- Integrated QuickDMX transceiver for wireless DMX control
- Battery operation up to 26h depending on program used
- 14 LEDs 10 W 6in1 RGBWA/UV (homogenous color mix)
- Frost filter
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable
- Strobe effect
- Integrated show programs
- Direct color selection for 27 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; IR remote control; master/slave function; QuickDMX
- Flicker-free
- With a beam angle of 15°
- Variable color temperature 2700 K - 8000 K
- With double bracket
- LCD display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use
- For application areas such as: Architecture; stage; wedding/gala/events; rental; video and photography
- Silent operation
- Application possibility: Standing; suspended; on stand
- **battery pack**
- Cordless, flexible and versatile

Logistic

EAN / GTIN: 4026397689235

Weight: 60,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.60 m

Bulky product

ROADINGER Flightcase 4x TMH-30/TMH-40/TMH-60 with wheels

Trunk case with castors, PRO version

- For optimal security
- With 4 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 51.60 kg

EUROLITE AKKU IP PAR 14 HCL QuickDMX

| | |
|-------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| IP classification: | IP65 |
| Protection class: | Protection class I |
| Power connection: | Battery/battery pack built-in Via IP T-Con (M) mounting version power supply cord with safety plug (provided) |
| Power output: | IP T-Con (F) mounting version |
| Battery pack: | Battery operation up to 26h depending on program used Recharging time 3h |
| Lamp type: | LED lamp |
| LED type: | 14 x 10 W 6in1 RGBWA/UV (homogenous color mix) |
| Flash rate: | 0 - 20 Hz |
| Equipment: | Frost filter |
| DMX channels: | 2; 3; 6-1; 6-2; 12 |
| DMX input: | 3-pin XLR (M) mounting version IP |
| DMX output: | 3-pin XLR (F) mounting version IP |
| Cooling: | Passive convection cooling |
| Control: | DMX; stand-alone; IR remote control; master/slave function; QuickDMX |
| Fixtures available for: | LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Light J; Colorchief |
| Projection: | Flicker-free |

| | |
|--------------------------|---|
| Carrier frequency: | 2.4 GHz |
| Beam angle (1/2 peak): | 15° 27° 30° 60° |
| Color temperature: | 2700K - 8000K adjustable |
| Housing color: | Black |
| Attachment system: | Double bracket |
| Display type: | LCD display |
| Material: | Aluminum casting |
| Dimensions: | Width: 31.7 cm Depth: 22.7 cm Height: 37.0 cm |
| Weight: | 7.85 kg |
| Noise classification: | Class 0 (no noise at all) |
| Battery pack type: | 1 x lithium ion 22.2 V, 4400 mAh, 97.68 Wh |
| Diameter mounting holes: | 3 x Ø11mm |
| Material: | Metal, 3 mm |
| Cable construction: | 3 x 1.0 mm ² H05RN-F |
| Cable length: | Approx. 1.2 m |
| Cable length: | Approx. 1.5 m |
| Plug A: | 1 x 3-pin XLR (M) |
| Plug B: | 1 x 3-pin XLR (F) |
| Diameter mounting holes: | 2 x Ø4mm |
| Material: | Plastic, 2 mm |
| Dimensions: | Diameter: Ø 20.5 cm |
| Battery: | 1 x button cell 3.0 V CR2032 lithium manganese built-in |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Flightcase 4x TMH-30/TMH-40/TMH-60 with wheels

| | |
|--------------------------|---|
| Maximum load: | 100 kg |
| Aluminum profile frames: | 30 mm |
| Case handle: | 4 pc/pcs |
| Stop hinge: | 2 pc/pcs |
| Lock: | Butterfly lock: 2 pc/pcs |
| Transport aid: | 4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover |
| Use of brands: | Branded hardware |
| Material: | Birch multiplex, 7 mm |
| Color: | Dark brown, laminated |
| Device compartment: | 27 cm x 27 cm x 28 cm |
| Accessory compartment: | 10 cm x 56 cm x 28 cm |
| Inside dimensions: | 65 cm x 55 cm x 30.5 cm |

Dimensions: Length: 71 cm
Width: 60 cm
Height: 53 cm

Weight: 20.20 kg

Scope of delivery:

1 x spotlight
1 x power cord
1 x XLR cable
3 x frost filter
1 x remote control
2 x screw
1 x user manual