

## EUROLITE Set 2x LED SLS-7 HCL Floor + LED QDF-Bar RGBAW Light set Art. No.: 2000833

2x flat spotlight with RGBAW+UV color mixing incl. spotlight bar with 4 LED heads

GTIN: 4026397689341



**The article is no longer in our assortment.**

### Features:

#### EUROLITE LED SLS-7 HCL Floor

Flat LED spotlight with RGBWA+UV color mixing, incl. IR remote control

- Slim design for space-saving applications
- Enjoy perfect solid and pastel colors plus ultra violet thanks to 6-color mixing
- DMX and power terminals intelligently designed for easy wiring
- 7 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect; UV effect
- 2 integrated show programs
- Direct color selection for 19 preset colors
- The device is cooled by cooling fan
- Control via stand-alone; DMX; Sound to light via Microphone; Master/slave function; IR remote control
- Flicker-free
- With a beam angle of 17°
- With double bracket
- Monochrome 4 digit 7-segment LED display
- Available in various colors
- Preprogrammed in Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
- Rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; Wedding/gala/events; Party room; mobile djs / entertainer
- Application possibility: Standing; suspended; on stand

#### Package contents

### Logistic

EAN / GTIN: 4026397689341

Weight: 10,40 kg

Length: 1.30 m

Width: 0.50 m

Height: 0.30 m

Bulky product

- 1 x light effect, 1 x power cord, 1 x remote control, 1 x user manual

### EUROLITE LED QDF-Bar RGBAW Light Set

LED bar with 4 LED heads, LEDs in RGBWA and DMX

- Crossbar with integrated DMX control unit and stand sleeve
- Ultra-light ideally suited for mobile use
- Ideal for bands, stages or solo entertainers
- Suited for installation on a speaker stand (not included) or truss
- Comes pre-assembled with practical transport bag
- Equipped with 240 LEDs (5 mm) in the colors red, green, blue, amber and white
- Movable and tiltable spotlights
- Via DMX, each spot can be individually controlled
- DMX-controlled operation or stand-alone operation
- DMX512 control via any commercial DMX controller (occupies 23 channels)
- Functions: Effect/color presets, built-in programs, strobe effect with variable speed, Master/Slave operation
- Addressing and setting via control panel with 4-digit LED display
- Additional controlling possibility via the EUROLITE IR-7 remote control, included in delivery
- Black lacquered metal version
- IEC terminals for power linking up to 8 units
- Switch-mode power supply for operation between 100 and 240 volts
- 240 powerful LEDs 5 mm R/G/B/W/A<BR> LEDs controlled separately
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; Sound to light via Microphone
- Preprogrammed in Light J; LED PC-Control 512
- Flicker-free
- Silent operation

#### Package contents

- 1 x spotlight, 1 x remote control

### Technical specifications:

---

Weight: 8,11 kg

---

### EUROLITE LED SLS-7 HCL Floor

|                    |  |
|--------------------|--|
| Power supply:      | 100-240 V AC, 50/60 Hz   |
| Power consumption: | 20 W   |
| IP classification: | IP20   |
| Protection class:  | Protection class I   |
| Power connection:  | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Power output:      | 1 x IEC connector (F) mounting version   |
| Fuse:              | 5 x 20 mm, T 0,5 A Fuse replaceable  |
| Lamp type:         | LED lamp   |
| LED:               | 7 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)                                     |
| Flash rate:        | 0 - 20 Hz  |
| DMX channels:      | 2; 3; 4; 6; 10   |
| DMX input:         | 3-pin XLR (M) mounting version   |
| DMX output:        | 3-pin XLR (F) mounting version   |

|                          |  |
|--------------------------|--|
| Cooling:                 | 1 x cooling fan  |
| Control:                 | Stand-alone; DMX; Sound to light via Microphone; Master/slave function; IR remote control  |
| Preprogrammed in:        | Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3 |
| Projection:              | Flicker-free   |
| Beam angle:              | 17°  |
| Beam angle (1/2 peak):   | 17°  |
| Beam angle (1/10 peak):  | 39°  |
| Wavelength:              | Ultra violet (UV) 400 nm   |
| Housing color:           | Black  |
| Attachment system:       | Double bracket   |
| Display type:            | Monochrome 4 digit 7-segment LED display   |
| Transport aid:           | Rubber feet  |
| Material:                | Plastic; metal; ABS Acrylonitrile butadiene styrene  |
| Dimensions:              | Width: 22 cm<br>Depth: 11 cm<br>Height: 21 cm  |
| Weight:                  | 1,38 kg  |
| Noise classification:    | Class 2 (slight noise)   |
| Photobiological safety:  | Risk Group 0   |
| Power cord               |  |
| Cable construction:      | 3 x 0,75 mm <sup>2</sup> H05VV-F   |
| Cable length:            | Approx. 1,2 m  |
| Mounting bracket         |  |
| Diameter mounting holes: | 5 x Ø11mm  |
| Material:                | Metal, 2 mm  |
| Color:                   | Black  |
| Remote control           |  |
| Battery:                 | 1 x Button cell 3.0 V CR2025 lithium manganese built-in  |

#### **EUROLITE LED QDF-Bar RGBAW Light Set**

|                    |  |
|--------------------|--|
| Power supply:      | 100-240 V AC, 50/60 Hz   |
| Power consumption: | 20 W   |
| IP classification: | IP20   |
| Power connection:  | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Power output:      | 1 x IEC connector (F) mounting version   |
| Fuse:              | F 1 A Fuse replaceable   |
| Lamp type:         | LED lamp   |

|                       |   |
|-----------------------|---|
| LED:                  | 240 x 5 mm R/G/B/W/A                                    |
| Flash rate:           | 0 - 20 Hz   |
| DMX channels:         | 4; 7; 23  |
| DMX input:            | 1 x 3-pin XLR (M) mounting version                      |
| DMX output:           | 1 x 3-pin XLR (F) mounting version                      |
| Cooling:              | Passive convection cooling                              |
| Control:              | Stand-alone; DMX; Sound to light via Microphone         |
| Preprogrammed in:     | Light J; LED PC-Control 512                             |
| Projection:           | Flicker-free  |
| Housing color:        | Black   |
| Dimensions:           | Width: 85 cm<br>Depth: 11 cm<br>Height: 36 cm           |
| Weight:               | 4,5 kg  |
| Noise classification: | Class 0 (no noise at all)                               |
| Remote control        |   |
| Battery:              | 1 x Button cell 3.0 V CR2025 lithium manganese built-in |
| Legal specifications  |   |
| Special product:      | Not designed for household room illumination            |
| Intended use:         | Show effect lighting                                    |