



List price: 1188.81 €

incl. 19% VAT.

Features:

EUROLITE AKKU Dot 1 RGB/WW QuickDMX bk

Battery-powered pinspot with magnetic base, 15 W 4in1 LED, QuickDMX, frost filter and IR remote control

- Integrated QuickDMX transceiver for wireless DMX control
- Magnetic base affixes to metal surfaces
- Additional frost filter provides a wide, soft and homogeneous light
- Battery operation up to 18h depending on program used
- 1 powerful LED 15 W high-power 4in1 QCL RGB/WW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; white balance adjustable; Dimmer speed (step response) adjustable
- Strobe effect
- 36 integrated show programs
- Direct color selection for 15 preset colors
- The device is cooled by passive convection cooling
- Control via IR remote control; stand-alone; Sound to light via Microphone; QuickDMX; Master/slave function; DMX
- Flicker-free
- With a beam angle of 9°
- With Mounting bracket
- Monochrome OLED display
- With a KENSINGTON LOCK theft protection
- For application areas such as: Small rental; Wedding/gala/events; mobile djs / entertainer
- Preprogrammed in LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light J; Light Captain; EASY SHOW 2; EASY SHOW 3
- Silent operation
- Cordless, flexible and versatile
- Integrated automatic charging of the battery and status indicator

Logistic

EAN / GTIN: 4026397689617

Weight: 14,00 kg

Length: 0.70 m

Width: 0.27 m

Height: 0.52 m

- Application possibility: Standing; suspended

Package contents

- 1 x spotlight, 1 x user manual, 1 x external mains adapter, 1 x declaration of conformity, 1 x diffusor cover, 1 x remote control, 1 x battery, 1 x power cord

ROADINGER Flightcase 4x AKKU Dot 1 RGB/WW QuickDMX

Trunk case

- Cable bushing allows loading the devices inside
- With accessory compartment
- Interior with foam padding
- Aluminum profile frames 20mm with rounded edges
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Rubber feet
- Hinged, chromium plated case handle

EUROLITE Charger 4x Akku Flat Light Series

Power supply with cable for simultaneous charging of 4 x Akku Flat Light 1/3

- 1 x charger, 1 x power cord, 1 x adapter cable

Technical specifications:

Weight: 11,68 kg

EUROLITE AKKU Dot 1 RGB/WW QuickDMX bk

Power supply:	100-240 V AC, 50/60 Hz 12,6 V DC 200 mA
Power consumption:	25 W
IP classification:	IP20
Protection class:	Protection class III
Power connection:	Battery/battery pack built-in Mains input via Coaxial power connector (M) mounting version
Battery pack type:	1 x lithium ion 11,1 V, 5200 mAh, 57,72 Wh
Battery pack:	Battery operation up to 18h depending on program used Recharging time 3,5h
Lamp type:	LED lamp
LED:	1 x 15 W high-power 4in1 QCL RGB/WW (homogenous color mix)
Flash rate:	1 - 23 Hz
DMX channels:	3; 4; 6; 8; 11
Cooling:	Passive convection cooling
Control:	IR remote control; stand-alone; Sound to light via Microphone; QuickDMX; Master/slave function; DMX

Preprogrammed in:	LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light J; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Carrier frequency:	2,4 GHz
Beam angle:	9°
Beam angle (1/2 peak):	9°
Beam angle (1/10 peak):	18°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	Monochrome OLED display
Theft protection:	KENSINGTON LOCK
Dimensions:	Width: 11,1 cm Depth: 7,8 cm Height: 17,5 cm
Weight:	1,35 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x Button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x AKKU Dot 1 RGB/WW QuickDMX

Aluminum profile frames:	20 mm
Case handle:	1 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	Rubber feet
Material:	Birch multiplex
Color:	Black; dark brown, laminated
Accessory compartment:	9,8 cm x 25,5 cm x 7 cm
Inside dimensions:	30,5 cm x 52 cm x 15 cm
Device compartment:	14,5 cm x 11,5 cm x 12 cm
Material thickness:	7 mm
Dimensions:	Width: 33,2 cm Depth: 55 cm Height: 22 cm
Weight:	5,80 kg

EUROLITE Charger 4x Akku Flat Light Series

Power supply:	100-240 V AC, 50/60 Hz 12,6 V DC 6 A
---------------	---

Power connection:	Mains input power supply cord with Euro plug (provided)
Power output:	4 x Coaxial power connector (F)
Weight:	490 g