

# OMNITRONIC Set MOLLY 2.1 Active System Sub + 2x Top + Accessories, blacko: 20000836

GTIN: 4026397689976



List price: 986.51 €

incl. 19% VAT.

### Features:

#### **OMNITRONIC MOLLY-12A Subwoofer active black**

Active 12" subwoofer with DSP and Bluetooth

- 12" bassreflex subwoofer with DSP and 700 watts RMS power
- Flexibly extendable with MOLLY-6 satellites for 2.1 and 4.1 configurations
- DSP-controlled class D amplifier (500 W + 2 x 100 W)
- Separate volume control for subwoofer and satellites
- Stereo/mono selection
- Digital signal processor
- DSP presets: FLAT; DJ; LIVE; VOICE
- The device is cooled by temperature-controlled fan
- Control via Bluetooth
- Operating range up to 10m
- Black metal grille with acoustic foam
- 2 Rugged carrying handles
- For application areas such as: Mobile djs / entertainer; Trade fair and shop fitting; installation; home entertainment; restaurants, bars and hotels; product presentations and lectures

#### Package contents

- 1 x bass, 1 x power cord, 2 x speaker cable, 1 x user manual, 1 x declaration of conformity

#### **OMNITRONIC MOLLY-6 Top black 2x**

6.5" satellite speakers with bracket

- 8-ohm speaker pair with 6.5" woofer and 1" tweeter
- For use with MOLLY-12A subwoofers for 2.1 and 4.1 configurations
- Optional stand adaptor required for stand mounting

### Logistic

EAN / GTIN: 4026397689976

Weight: 45,00 kg Length: 1.20 m Width: 0.80 m Heigth: 0.60 m Bulky product

- Extension U-bracket and cable available for connecting 2 satellite speakers
- With mounting bracket
- With rigging points
- Black metal grille with acoustic foam
- 2 pieces per set
- For application areas such as: Mobile djs / entertainer; Trade fair and shop fitting; installation; home entertainment; restaurants, bars and hotels; product presentations and lectures

#### Package contents

- 2 x top, 2 x mounting bracket, 4 x knurled screw, 2 x screw plug-in terminal

### **OMNITRONIC BOB-4 Stand Adaptor black 2x**

Adapter with stand sleeve for 35 mm tube, M8 threadPackage contents

- 2 x holder

#### **OMNITRONIC Speaker Stand BOB System**

Speaker stand for BOB speakers, extendable up to 170 cm

- Tube diameter: Ø 30 mm
- Adjustable height
- Scratchproof and shockproof

#### Package contents

- 1 x stand, 1 x user manual

#### **OMNITRONIC BOB Transport Bag for Tripod/Distance Tube**

Accessory for the BOB series

- Suitable for stands and distance tubes
- Made of easy-care artificial black textile
- High-quality workmanship with textile, black

#### Package contents

- 1 x bag

## OMNITRONIC Speaker Cable Speaker 2x1.5 5m bkPackage contents

- 1 x speaker cable

**Technical specifications:** 

Weight:	36,81 kg

### **OMNITRONIC MOLLY-12A Subwoofer active black**

Power supply:	230 V AC, 50 Hz
Power consumption:	1000 W
Protection class:	Protection class I
Output power:	1 x 500 W RMS
	2 x 100 W RMS (8 ohms)
	2 x 200 W RMS (4 ohms)
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Device fuse:	5 x 20 mm, T 5 A fuse replaceable

Frequency range:	40 - 160 Hz
Sensitivity:	103 dB
Max. SPL:	128 dB
DSP:	Digital signal processor
DSP presets:	FLAT; DJ; LIVE; VOICE
Cooling:	Temperature-controlled fan
Control:	Bluetooth
Bluetooth device name:	Omnitronic
Range:	Range up to 10m
Attachment system:	Flange: M20 thread
Circuitry:	Class D
Control elements:	Phase reversal switch, level control per channel, power switch, connect
Controls:	Softstart; short-circuit; limiter; Overvoltage; overheat
Status LED:	Signal, power, limit, fault, DSP presets
Connections:	Input: line via 2 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version)
	Input: line via 1 x 3.5 mm jack (stereo) mounting version
	Input: line via 1 x stereo RCA Output: line via 2 x 3-pin XLR
	Output: top via 2 x speaker built-in socket (F)
Input channels:	1 x stereo via combination socket or RCA or Bluetooth, channel control via rotary dial
Speaker:	1 x woofer 12"
	Basket material: steel
	Conematerial: cardboard/paper Voice coil lows 3"
Type of anadker:	
Type of speaker:	Subwoofer Vented
Type of construction:  Carrying handle:	2 pc/pcs
Material:	<u> </u>
	Birch multiplex
Color:	Black, textured coating, painted
Dimensions:	Width: 47 cm
	Depth: 57 cm Height: 40 cm
Weight:	22,10 kg
Speaker cable	, . v ng
Cable length:	3 m
Capic Ichigui.	<u> </u>

## OMNITRONIC MOLLY-6 Top black 2x

Power:	Program: 260W Rated: 130W RMS
Frequency range:	150 - 20000 Hz
Sensitivity:	95 dB (1W/1m)
Max. SPL:	119 dB

Impedance:	8 ohms
Attachment system:	2x mounting bracket
Flying points:	2 x M8 thread
Connections:	1 x speaker built-in socket (F)
	1 x screw plug-in terminal
Speaker:	1 x woofer 6,5"
	Basket material: steel
	Voice coil lows 1"
	1 x tweeter 1"
Type of speaker:	On ceiling/on wall speaker; coaxial speaker
Material:	MDF (medium density fiberboard)
Color:	Black, textured coating, painted
Dimensions:	Width: 18,3 cm
	Depth: 21,4 cm
	Height: 23 cm
Weight:	8,90 kg

## OMNITRONIC BOB-4 Stand Adaptor black 2x

Maximum carrying capacity:	30 kg	
Type (general stands):	Accessory	
Material:	Steel (powder-coated)	
Color:	Black	
Weight:	0,38 kg	

## OMNITRONIC Speaker Stand BOB System

Maximum carrying capacity:	14 kg
Height:	Maximum: 195 cm
	Minimum: 107 cm
	Adjustable in 6 steps with locking pin
Attachment system:	M10 thread
Type (general stands):	Speaker stand/manual
Material:	Steel
Color:	Black, painted; , scratchproof and shockproof
Main pipe diameter:	Ø 3 cm
Extension tube diameter:	Ø 2,5 cm
Weight:	2,15 kg

## **OMNITRONIC BOB Transport Bag for Tripod/Distance Tube**

Material:	Textile
Color:	Black
Dimensions:	Length: 106 cm
	Width: 9 cm
	Depth: 7 cm

Weight: 0,19 kg

### OMNITRONIC Speaker Cable Speaker 2x1.5 5m bk

Cable construction:	2 x 1,5 mm² speaker cable
Cable length:	5 m
Plug A:	1 x 2-pin speaker (M)
Plug B:	1 x 2-pin speaker (M)
Color:	Black
Weight:	0,37 kg