



The article is no longer in our assortment.

Features:

EUROLITE LED IP T-PIX 8 QCL Bar

Weather-proof (IP65) bar with RGBW color mixing and segment control

- DMX and power terminals intelligently designed for easy wiring
- 384 powerful LEDs 0,4 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
8 segments controlled separately
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; dimmer curves with adjustable response
- Strobe effect
- Direct color selection for 32 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; Master/slave function; Sound to light via Microphone
- Flicker-free
- With a beam angle of 120°
- With Mounting bracket; with Omega bracket
- Suitable for outdoor use
- Preprogrammed in Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
- Silent operation

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x xLR cable, 2 x omega bracket

Logistic

EAN / GTIN: 4026397690583

Weight: 64,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 1.00 m

Bulky product

ROADINGER Flightcase 4x LED IP T-PIX 8 QCL/T-PIX 12 HCL with wheels

Trunk case with castors, PRO version

- ,
- Interior with foam padding

- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 3 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 castors with 2 locking brakes
- Branded hardware
- European engineering
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 57,60 kg

EUROLITE LED IP T-PIX 8 QCL Bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	130 W
IP classification:	IP65
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Power output:	IP T-Con (F) mounting version
Lamp type:	LED lamp
LED:	384 x 0,4 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
Flash rate:	1 - 25 Hz
DMX channels:	4; 9; 16; 37
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; Master/slave function; Sound to light via Microphone
Preprogrammed in:	Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	120°
Beam angle (1/2 peak):	120°
Housing color:	Black
Attachment system:	2x Mounting bracket Omega bracket
Dimensions:	Length: 99,0 cm Depth: 16,0 cm Height: 14,0 cm
Weight:	8,20 kg
Noise classification:	Class 0 (no noise at all)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x LED IP T-PIX 8 QCL/T-PIX 12 HCL with wheels

Maximum load:	100 kg
Aluminum profile frames:	25 mm
Case handle:	4 pc/pcs
Stop hinge:	3 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes
Use of brands:	Branded hardware
Device compartment:	1 m x 12 cm x 17 cm
Accessory compartment:	1,02 m x 10,5 cm x 17 cm
Dimensions:	Length: 1,06 m Width: 74 cm Height: 40 cm
Weight:	24,80 kg