



Features:

EUROLITE LED 7C-7 Silent Slim Spot

Silent 7in1 LED PAR spotlight in a space-saving design

- Flat version requires minimal space when mounting
- 7 LEDs 9 W high-power 7in1 SCL RGB/CW/WW/A/UV (homogenous color mix)
- Color blend stepless; Dimmer electronic
- Strobe effect
- Integrated show programs
- Direct color selection for 27 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Fixtures available for LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
- Flicker-free
- With a beam angle of 15°
- Very high color rendering index (CRI)
- With double bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels; theater; rental; advertisement/Shop window
- Silent operation
- Application possibility: Standing; suspended; on stand

Logistic

EAN / GTIN: 4026397691009

Weight: 21,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.60 m

Bulky product

EUROLITE QuickDMX USB Wireless Transmitter/Receiver

Wireless miniature DMX transceiver 2.4 GHz, phantom powered

- User-friendly USB plug with swivel antenna
- Wireless DMX eliminates extensive cabling between DMX controller and the DMX-controlled units in lighting installations
- Due to GFSK modulation with 78 channels, interference-free operation also alongside other QuickDMX transceiver and wireless devices in the 2.4 GHz band (e.g. Wi-Fi and Bluetooth)
- LED indication for functions
- Transceiver, to be used as transmitter or receiver
- Requires 5 V phantom power for operation
- Can receive and process up to 512 DMX channels
- Can transmit up to 512 DMX channels
- Control via DMX; QuickDMX; plug and play
- Operating range up to 400m with line-of-sight
- Up to 6 transmitters can be operated in parallel without interference

ROADINGER Flightcase 4x SLS Size M

Trunk case, PRO version

- Individually adjustable and removable dividers for universal use
- With 4 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- Hinged, chromium plated case handle
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 18.11 kg

EUROLITE LED 7C-7 Silent Slim Spot

| | |
|--------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 45 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x P-Con (gray), mounting version |
| Fuse: | 5 x 20 mm, T 1 A fuse replaceable |
| Lamp type: | LED lamp |
| LED type: | 7 x 9 W high-power 7in1 SCL RGB/CW/WW/A/UV (homogenous color mix) |
| Flash rate: | 0 - 20 Hz |
| DMX channels: | 3; 4-1; 4-2; 4-3; 4-4; 5; 6; 7; 9; 12 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |

| | |
|------------------------------|--|
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Fixtures available for: | LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3 |
| Projection: | Flicker-free |
| Beam angle: | 15° |
| Beam angle (1/2 peak): | 15° |
| Beam angle (1/10 peak): | 33° |
| Color rendering index (CRI): | 92 Ra |
| Housing color: | Black matte |
| Attachment system: | Double bracket |
| Display type: | 4 digit 7-segment LED display |
| USB port: | Type A |
| Material: | Aluminum casting; metal |
| Dimensions: | Width: 22 cm Depth: 11 cm Height: 25.5 cm |
| Weight: | 2.60 kg |
| Noise classification: | Class 0 (no noise at all) |
| Photobiological safety: | Risk Group 0 |
| Diameter mounting holes: | 1 x Ø11mm |
| Material: | Metal, 2.5 mm |
| Cable construction: | 3 x 1.0 mm ² H05VV-F |
| Cable length: | Approx. 1.2 m |
| Battery: | 1 x button cell 3.0 V CR2025 lithium manganese built-in |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

EUROLITE QuickDMX USB Wireless Transmitter/Receiver

| | |
|--------------------|---|
| Power supply: | 5V DC |
| IP classification: | IP20 |
| Power connection: | Mains input via USB A (M) connectable version |
| DMX channels: | Input 512 Output 512 |
| DMX output: | 1 x USB, type A |
| Control: | DMX; QuickDMX; plug and play |
| Range: | Range up to 400m with line-of-sight |
| Carrier frequency: | 2.4 GHz |
| Parallel mode: | Max. 6 transmitter |
| RF power output: | 19 dBm |

| | |
|-------------|--|
| Modulation: | GFSK |
| Color: | Black |
| Dimensions: | Width: 8.6 cm Depth: 4 cm Height: 1.1 cm |
| Weight: | 0.01 kg |

ROADINGER Flightcase 4x SLS Size M

| | |
|--------------------------|---|
| Maximum load: | 25 kg |
| Aluminum profile frames: | 30 mm |
| Case handle: | 1 pc/pcs |
| Stop hinge: | 2 pc/pcs |
| Lock: | Butterfly lock: 1 pc/pcs |
| Use of brands: | Branded hardware |
| Material: | Birch multiplex, 7 mm |
| Color: | Dark brown, laminated |
| Compartment dimensions: | 12 cm x 25 cm x 35.5 cm |
| Inside dimensions: | 49.5 cm x 25 cm x 35.5 cm |
| Dimensions: | Width: 52.5 cm Depth: 28.5 cm Height: 44.5 cm |
| Weight: | 7.65 kg |

Scope of delivery:

4 x EUROLITE LED 7C-7 Silent Slim Spot

- 1 x light effect
- 1 x power cord
- 1 x remote control
- 1 x user manual

4 x EUROLITE QuickDMX USB Wireless Transmitter/Receiver

- 1 x device
- 1 x user manual
- 1 x declaration of conformity