

RELACART Set MIPASSPORT Wireless Cameramount Microphone System + Lavalier

Art. No. MIP0016
GTIN: 4026397674361



Features:

RELACART MIPASSPORT Wireless Cameramount Microphone System

Wireless audio transmission system for cameras

- Portable transmitter and receiver with attachment clip
- Perfect video sound for cameras, smartphones, camcorders, etc.
- Easy attachment to clothing, the camera's hot shoe, etc.
- Ultra-compact and lightweight design
- Rechargeable lithium batteries
- Charging via USB-C socket
- Transmitter with integrated omnidirectional condenser microphone
- 3.5 mm TRS jack for an external lavalier microphone (optional)
- Receiver with 3.5 mm TRS jack for your recording device and 4-stage gain control (0 dB, -3 dB, -6 dB, -9 dB)
- Automatic pairing in 2 seconds
- Works with iOS and Android devices
- Operating range up to 40m with line-of-sight
- 2.4 GHz license-free worldwide
- Up to 6 transmitters can be operated in parallel without interference
- OLED display
- For application areas such as: Trade fair and shop fitting; mobile use; mobile djs / entertainer; homerecording and studios; video and photography

transmitter

- Polar pattern: Omnidirectional
- Cordless, flexible and versatile
- Battery operation up to 7h

receiver

- Cordless, flexible and versatile

Logistic

EAN / GTIN: 4026397674361

Weight: 0,55 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

- Battery operation up to 7h

RELACART LM-P01 Lavalier for MIPASSPORT System

Inconspicuous electret lavalier microphone

- Provides high-quality voice pickup
- For attaching to the user's tie, shirt or collar
- Polar pattern: Omnidirectional

Technical specifications:

Weight:	0.13 kg
---------	---------

RELACART MIPASSPORT Wireless Cameramount Microphone System

Type:	Wireless set
Power supply:	5V DC 500 mA
Power connection:	Battery/battery pack Mains input via USB C (W) mounting version power supply cord for USB A mains connection (provided)
Number of channels:	1
Frequency range:	100 - 20000 Hz
S/N ratio:	>93 dB
Max. SPL:	97 dB
Range:	Range up to 40m with line-of-sight
Frequency band:	2.4 GHz
Parallel mode:	Max. 6 transmitter
Display type:	OLED display
Switch:	On/off switch
Material:	Plastic
Color:	Black
Dimensions:	Width: 4.4 cm Depth: 1.9 cm Height: 5 cm
Weight:	0.12 kg
Capsule type:	Electret
Polar pattern:	Omnidirectional
Battery pack type:	1 x lithium ion 3.7 V, 435 mAh, 1.61 Wh
Battery pack:	Battery operation up to 7h
RF power output:	10 dBm
Connections:	Input: microphone via 3.5 mm jack (mono) mounting version 2.5 V
Weight:	0.032 kg
Battery pack type:	1 x lithium ion 3.7 V, 435 mAh, 1.61 Wh
Battery pack:	Battery operation up to 7h

Connections:	Output: 3.5 mm jack (mono) mounting version
Weight:	0.032 kg

RELACART LM-P01 Lavalier for MIPASSPORT System

Type:	Lavalier microphone
Power supply:	1.5-9V DC
Power connection:	Via 3.5 mm jack (mono)
Cable length:	1.2 m
Capsule type:	Electret Size: Ø 8 mm x 18 mm
Polar pattern:	Omnidirectional
Frequency range:	50 - 20000 Hz
S/N ratio:	>65 dB
Sensitivity:	-39 dB
Impedance:	2200 Ohm
Switch:	Without
Material:	Aluminum
Color:	Black
Weight:	0.02 kg

Scope of delivery:

1 x RELACART MIPASSPORT Wireless Cameramount Microphone System

- 1 x transmitter
- 1 x receiver
- 2 x jack cable
- 1 x USB cable
- 1 x windshield
- 1 x user manual
- 1 x declaration of conformity

1 x RELACART LM-P01 Lavalier for MIPASSPORT System

- 1 x microphone
- 2 x windshield
- 1 x bag
- 1 x user manual