



List price: 5175.31 €

incl. 19% VAT.

Features:

EUROLITE LED IP T-Bar 16 QCL Bar

Weather-proof (IP65) bar with RGBW color mixing, incl. IR remote control

- 16 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Direct color selection for 19 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; Master/slave function; stand-alone; IR remote control
- Flicker-free
- With a beam angle of 20°
- With Mounting bracket
- 4 digit 7-segment LED display
- Suitable for outdoor use
- Silent operation
- Preprogrammed in Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
- Mains input and output for power linking up to 8 units
- For application areas such as: Installation; restaurants, bars and hotels; architecture
- Application possibility: Suspended; Wall mounting

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery, 2 x mounting bracket, 2 x screw, 2 x washer

Logistic

EAN / GTIN: 4026397694949

Weight: 120,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 1.00 m

Bulky product

ROADINGER Flightcase 12x LED Bar with wheels

Trunk case with castors, PRO version

- Universal modular system for LED bars up to 1 m length
- 3 stackable units accommodate 4 LED bars each
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Removable cover
- Aluminum profile frames 20mm with rounded edges
- 6 hinged, chromium plated case handles
- 12 high-quality butterfly locks
- 4 castors with 2 locking brakes
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 106,10 kg

EUROLITE LED IP T-Bar 16 QCL Bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	50 W
IP classification:	IP65
Power connection:	Mains input via IP T-Con (M) power supply cord with safety plug
Power output:	IP T-Con (F)
Lamp type:	LED lamp
LED:	16 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 4; 5; 6; 9
DMX input:	3-pin XLR (M) IP
DMX output:	3-pin XLR (F) IP
Cooling:	Passive convection cooling
Control:	DMX; Master/slave function; stand-alone; IR remote control
Preprogrammed in:	Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	20°
Beam angle (1/2 peak):	20°
Beam angle (1/10 peak):	35°
Housing color:	Black
Attachment system:	2x Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 1,065 m Depth: 10,00 cm Height: 12,65 cm
Weight:	5,95 kg

Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 12x LED Bar with wheels

Maximum load:	150 kg
Removable covers:	1 pc/pcs
Aluminum profile frames:	20 mm
Case handle:	6 pc/pcs
Lock:	Butterfly lock: 12 pc/pcs
Transport aid:	4 x castors with 2 locking brakes
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Compartment dimensions:	1,13 m x 8,5 cm x 9 cm
Inside dimensions:	1,13 m x 40,5 cm x 16 cm
Dimensions:	Width: 1,19 m Depth: 44 cm Height: 84 cm
Weight:	34,70 kg