



The article is no longer in our assortment.

Features:

EUROLITE AKKU UP-1 Glow QCL Flex Spot QuickDMX

LED Uplight with 15 W 4in1 LED, tiltable head, QuickDMX & mood light

- Integrated QuickDMX transceiver for wireless DMX control
- Milky front screen provides a pleasantly soft light with RGBW color mixing
- Interchangeable front lens for 9° or 15° beam angle
- Stepless color blend, color change, color fade, dimmer and strobe effect
- Dimmer speed (step response) adjustable
- Integrated automatic charging of the battery with indicator
- Cordless, flexible and versatile
- Battery operation up to 24h depending on program used
- 30 powerful LEDs 0,25 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
- 1 powerful LED 15 W high-power 4in1 QCL RGBW (homogenous color mix)
- Direct color selection for 30 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; QuickDMX; Sound to light via Microphone; IR remote control; Master/slave function
- Preprogrammed in Light´J; LED PC-Control 512; Light Captain
- Flicker-free
- With a beam angle of 9°
- With Mounting bracket
- With a KENSINGTON LOCK theft protection
- Silent operation
- For application areas such as: Small rental; Wedding/gala/events

Package contents

- 1 x spotlight, 1 x power cord, 1 x remote control, 1 x lens, 1 x user manual

Logistic

EAN / GTIN: 4026397694987

Weight: 22,00 kg

Length: 0.54 m

Width: 0.53 m

Height: 0.45 m

ROADINGER Flightcase EC-AU4 4x AKKU UP 4 QCL Spot QuickDMX

Trunk case

- Cable bushing allows loading the devices inside
- With 4 Device compartments
- High-quality workmanship with plywood multi-layer glued 6 mm, black, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- Hinged, chromium plated case handle
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 18,20 kg

EUROLITE AKKU UP-1 Glow QCL Flex Spot QuickDMX

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	40 W
IP classification:	IP20
Protection class:	Protection class III
Power connection:	Battery/battery pack Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Battery pack type:	1 x lithium ion 11,1 V, 10400 mAh, 115,44 Wh
Battery pack:	Battery operation up to 24h depending on program used Recharging time 4h
Lamp type:	LED lamp
LED:	30 x 0,25 W SMD 5050 4in1 QCL RGBW (homogenous color mix) 1 x 15 W high-power 4in1 QCL RGBW (homogenous color mix)
DMX channels:	3; 7; 8; 9; 11
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; QuickDMX; Sound to light via Microphone; IR remote control; Master/slave function
Preprogrammed in:	Light'J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
Carrier frequency:	2,4 GHz
Beam angle:	9°
Beam angle (1/2 peak):	9° 15°

Beam angle (1/10 peak):	18° 30°
Housing color:	Black
Attachment system:	Mounting bracket
Theft protection:	KENSINGTON LOCK
Dimensions:	Width: 13,8 cm Depth: 13,8 cm Height: 20 cm
Weight:	2,90 kg
Noise classification:	Class 0 (no noise at all); Class 0 (no noise at all)
Remote control	
Battery:	1 x Button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase EC-AU4 4x AKKU UP 4 QCL Spot QuickDMX

Maximum load:	25 kg
Aluminum profile frames:	30 mm
Case handle:	1 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Material:	Plywood multi-layer glued, 6 mm; plywood multi-layer glued
Color:	Black, laminated
Inside dimensions:	45 cm x 36 cm x 20 cm
Device compartment:	16 cm x 14,5 cm x 18 cm
Dimensions:	Width: 49 cm Depth: 40 cm Height: 27 cm
Weight:	6,60 kg