



List price: 1069.81 €

incl. 19% VAT.

Features:

OMNITRONIC TRM-422 4-Channel Rotary Mixer

4-channel rotary mixer with 3-band frequency isolator and filter section for DJs

- 3-band master frequency isolator with vintage ALPS potentiometers (Blue Velvet RK27)
- Kill cut feature allows DJs to completely remove low, mid and high frequencies for amazing mixing
- Filter section with resonance and sweep control for creative sound shaping
- 4 stereo input channels with gain control, clip LED, 3-way equalizer and phono/line switching
- 2 microphone input channels with gain control, 2-way equalizer on air switch
- High-grade components ensure long life and excellent sound quality
- 16-digit stereo LED level meter, switchable between master and booth outputs
- Booth output with separate 2-way equalizer and level control
- PFL section with 16-digit stereo LED level meter, level control, PFL/master mix control and cue mix/split option
- Fully assignable VCA crossfader with adjustable curve
- 2 effects send/return paths
- Direct outputs for Timecode applications
- Outputs: master and booth (XLR/RCA L/R), record (RCA L/R), master insert send/return (RCA L/R), FX in/out (stereo jack)
- Desktop console housing
- (19") 48.3 cm rack installation possible
- For application areas such as: Clubs/dancing school; mobile use; mobile djs / entertainer; homerecording and studios

Package contents

- 1 x mixer, 1 x power cord, 2 x mounting bracket, 6 x screw, 8 x rCA cable, 1 x user manual

Logistic

EAN / GTIN: 4026397695571

Weight: 11,20 kg

Length: 0.54 m

Width: 0.53 m

Height: 0.45 m

ROADINGER Flightcase TRM-422

Carrying case, PRO version

- High-quality workmanship with birch multiplex 6,5 mm, dark brown, laminated
- Interior with foam padding
cover with foam padding
- Removable cover
- Aluminum profile frames 22mm with rounded edges
- Rugged carrying handle
- 2 high-quality spring locks
- Rubber feet
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 10,39 kg

OMNITRONIC TRM-422 4-Channel Rotary Mixer

| | |
|--------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 24 W |
| Protection class: | Protection class I |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Frequency range: | 20 - 20000 Hz Microphone 20 - 20000 Hz line 40 - 18000 Hz phono |
| S/N ratio: | >97,2 dB line >91,7 dB Microphone |
| THD: | Line <0,04 % at 1 kHz Phono <0,13 % at 1 kHz Microphone <0,008 % at 1 kHz |
| Gain: | Microphone 44 dB Line -16,5 dB to +8,5 dB Phono -48,5 dB to +23,5 dB |
| DJ filter: | Routable: LPF, BPF, HPF |
| Isolators: | Master Gain:- ? bis +9 Low/mid 300 Hz, 18db/oct , Butterworth Mid/high 4000 Hz, 18db/oct , Butterworth |
| Crosstalk: | >-68 dB |
| Control elements: | Power switch, source selector, Crossfader, Crossfader selector switch, Crossfade curve switch; Cue mix split function, tone control |
| Status LED: | Power, master level meter, clip, CUE |
| Connections: | Input: line via 4 x stereo RCA Input: line/phono via 4 x stereo RCA Input: Microphone via 2 x 3-pin XLR |

Output: headphones via 1 x 6.3 mm jack socket (stereo) mounting version
 Output: headphones via 1 x 3.5 mm jack (stereo) mounting version
 Output: rec. via 1 x stereo RCA
 Output: booth via 2 x 3-pin XLR
 Output: booth via 1 x stereo RCA
 Output: master via 2 x 3-pin XLR
 Output: master via 1 x stereo RCA
 Output: AUX sends via 1 x 6.3 mm jack socket (stereo) mounting version
 Output: AUX returns via 1 x 6.3 mm jack socket (stereo) mounting version
 Output: Timecode via 4 x stereo RCA

| | |
|-----------------|--|
| Channels: | <p>Input channel: 4 x stereo with Line-Line/Phono switch via RCA, channel control via Rotary, 3-band tone control EQ, source selector, gain control, CUE switch, FX routing switch, Crossfader selector switch</p> <p>Microphon channel: 2 x mono via XLR, channel control via Rotary dial, ON AIR switch</p> <p>Master output: 2 x stereo via XLR, channel control via Rotary, Cue mix split function</p> <p>Booth output: 2 x stereo via XLR, channel control via Rotary</p> <p>Rec. output: 1 x stereo via RCA</p> <p>Headphones output: 1 x stereo via Jack, channel control via Rotary dial</p> |
| Max. level: | Output: +18 dBu |
| Material: | Metal |
| Housing design: | Desktop console housing (19") 48.3 cm rack installation possible |
| Dimensions: | Width: 41 cm Depth: 28,5 cm Height: 10,5 cm |
| Weight: | 5,74 kg |

ROADINGER Flightcase TRM-422

| | |
|--------------------------|---|
| Maximum load: | 25 kg |
| Removable covers: | 1 pc/pcs |
| Aluminum profile frames: | 22 mm |
| Carrying handle: | 1 pc/pcs |
| Lock: | Spring lock: 2 pc/pcs |
| Transport aid: | Rubber feet |
| Use of brands: | Branded hardware |
| Material: | Birch multiplex, 6,5 mm |
| Color: | Dark brown, laminated |
| Device compartment: | 41 cm x 27,5 cm x 10,5 cm |
| Dimensions: | Width: 48 cm Depth: 43 cm Height: 17,5 cm |
| Weight: | 4,65 kg |