



List price: 1724.31 €

incl. 19% VAT.

Features:

EUROLITE Audience Blinder 4x100W LED COB CW/WW

Audience blinder, wide beam 4 x 100 W COB LED (warm/cold white)

- Swivel lamp rows
- Energy-saving, durable and environmentally friendly
- 4 powerful LEDs 100 W COB (chip-on-board) 2in1 BCL CW/WW (homogenous color mix)
- Variable color temperature 3200 K - 6400 K
- Strobe effect
- 4 integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; Master/slave function
- Preprogrammed in Light'J; Light Captain
- Flicker-free
- With a beam angle of 45°
- With Mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Mobile use; Stage; Rental
- Application possibility: Suspended; on stand

Package contents

- 1 x device, 1 x power cord, 1 x user manual

Logistic

EAN / GTIN: 4026397697650

Weight: 28,50 kg

Length: 1.20 m

Width: 0.60 m

Height: 0.60 m

Bulky product

ROADINGER Flightcase 2x Audience Blinder 4x100W LED COB CW/WW

- Interior with foam padding
cover with foam padding

- Aluminum profile frames 20mm with rounded edges
- 2 hinged, chromium plated case handles
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 25,45 kg

EUROLITE Audience Blinder 4x100W LED COB CW/WW

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	350 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version
Fuse:	T 10 A Fuse fix on board
Lamp type:	LED lamp
LED:	4 x 100 W COB (chip-on-board) 2in1 BCL CW/WW (homogenous color mix)
Color temperature:	3200K - 6400K adjustable
Flash rate:	0 - 20 Hz
DMX channels:	2; 8; 12
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	6 x cooling fan
Control:	Stand-alone; DMX; Master/slave function
Preprogrammed in:	Light J; Light Captain
Projection:	Flicker-free
Beam angle:	45°
Beam angle (1/2 peak):	45°
Luminous flux:	16600 lm
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Material:	Metal, 1 mm
Dimensions:	Width: 42 cm Depth: 49,5 cm Height: 12,5 cm
Weight:	7,00 kg
Noise classification:	Class 2 (slight noise)
Energy efficiency class (A - G):	G

Power cord	
Cable length:	Approx. 1,4 m
Mounting bracket	
Diameter mounting holes:	3 x Ø13mm
Material:	Metal, 2 mm

ROADINGER Flightcase 2x Audience Blinder 4x100W LED COB CW/WW

Maximum load:	50 kg
Aluminum profile frames:	20 mm
Case handle:	2 pc/pcs
Use of brands:	Branded hardware
Color:	Dark brown, laminated
Inside dimensions:	43 cm x 42 cm x 50,5 cm
Accessory compartment:	43 cm x 10,5 cm x 50,5 cm
Device compartment:	42 cm x 14 cm x 50,5 cm
Material thickness:	7 mm
Dimensions:	Length: 46,5 cm Width: 45,5 cm Height: 59,5 cm
Weight:	11,45 kg