



Features:

EUROLITE LED KLS-3002 Next Compact Light Set

Bar with 4 powerful 6in1 RGBWA/UV spots, QuickDMX support, IR remote control and carrying bag

- Crossbar with integrated DMX control unit and TV spigot for tripod installation
- Mounting points and power outlets for additional fixtures
- 7 LEDs 10 W SMD 9090 6in1 RGBWA/UV (homogenous color mix) spots controlled separately
- Dimmer electronic; color blend stepless; color selection; program selection
- UV effect
- 20 integrated show programs
- Direct color selection for 21 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- With a beam angle of 19°
- TV spigot
- With omega bracket
- Monochrome 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels; rental
- Silent operation
- Application possibility: Suspended; on stand

Logistic

EAN / GTIN: 4026397700534

Weight: 36,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

EUROLITE LED Laser Derby MK2

DMX light effect with RG laser (2M), rotating LED derby, stroboscope and IR remote control

- 2 laser diodes project hundreds of red and green laser beams
 - Dimmer electronic; color macros adjustable
 - Laser; multi beam effect; strobe effect
 - 7 integrated show programs
 - The device is cooled by cooling fan
 - Control via IR remote control; stand-alone; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional)
 - With mounting bracket
 - 4 digit 7-segment LED display
 - For application areas such as: Clubs/dancing school; party room; mobile djs / entertainer; restaurants, bars and hotels
 - Application possibility: Suspended; on stand
- laser**
- Laser class 2M
 does not require additional protective measures or appointment of a laser safety officer
- light effect**
- 4 LEDs 10 W SMD 5050 R/G/B/W
- strobes**
- 16 LEDs 0.6 W SMD 2835 cold white (CW)

EUROLITE DMX LED Color Chief Controller

DMX lighting desk with innovative control concept for LED spotlights

- Easy control of LED spotlights with up to 6 colors, light bars as well as simple lighting effects
- For 8 devices or device groups, each with up to 4 segments
- Quick and easy programming
- Additional fixtures can be configured manually
- 8 color effects directly selectable
- 3 additional channels available per fixture (e.g. for rotations)
- Color wheel selection and simulation
- 24 memory spaces for scenes and chases
- Several chases and scenes can be run simultaneously
- USB port for storing program data
- Sound control via audio signal or TAP button
- Master dimming, fade time and run time easily adjustable
- Can transmit up to 240 DMX channels
- (19") 48.3 cm rack installation 3 U
- Programmable 24 scenes/chases distributed over 1 page/s
- Control via DMX; sound to light via RCA (F) mounting version; sound to light via microphone
- Firmware can be updated
- Desktop console housing
- For application areas such as: Clubs/dancing school; party room; Trade fair and shop fitting; mobile djs / entertainer; restaurants, bars and hotels
- Silent operation

EUROLITE STV-60-WOT EU Steel Stand black

Lighting stand, made in EU, maximum load 30 kg, height 150-315 cm

- Stable lighting stand for mobile use
- Adjustable height
- TV spigot
- Available in various colors
- Made in Europe

EUROLITE SB-4 Soft Bag L

Black soft bag for up to 4 devices, 320 x 320 x 200 mm

- Practical transport bag offers enough space for several lighting effects and accessories
- With dividers

- With 2 Outside pockets
- With 4 device compartments
- High-quality workmanship with nylon , black, water repellent
- Interior with foam padding
cover with foam padding
- 2 carrying straps

ROADINGER Mixer Case Pro MCA-19-N, 3U, black

Rack case

- Upward tilted profile rails for top-operated units
- 3 U
- High-quality workmanship with plywood multi-layer glued 7 mm, black, laminated
- Interior with foam padding
- Removable cover
- Aluminum profile frames 30mm with rounded edges
- Rugged carrying handle
- 2 high-quality butterfly locks
- Rubber feet
- With profile rails suitable for 19" units

EUROLITE QuickDMX USB Wireless Transmitter/Receiver

Wireless miniature DMX transceiver 2.4 GHz, phantom powered

- User-friendly USB plug with swivel antenna
- Wireless DMX eliminates extensive cabling between DMX controller and the DMX-controlled units in lighting installations
- Due to GFSK modulation with 78 channels, interference-free operation also alongside other QuickDMX transceiver and wireless devices in the 2.4 GHz band (e.g. Wi-Fi and Bluetooth)
- LED indication for functions
- Transceiver, to be used as transmitter or receiver
- Requires 5 V phantom power for operation
- Can receive and process up to 512 DMX channels
- Can transmit up to 512 DMX channels
- Control via DMX; QuickDMX; plug and play
- Operating range up to 400m with line-of-sight
- Up to 6 transmitters can be operated in parallel without interference

EUROLITE QuickDMX Wireless Transmitter

Compact wireless DMX transmitter 2.4 GHz

- User-friendly 3-pin XLR adapter (male) with swivel antenna
- Wireless DMX eliminates extensive cabling between DMX controller and the DMX-controlled units in lighting installations
- Due to GFSK modulation with 78 channels, interference-free operation also alongside other QuickDMX transceiver and wireless devices in the 2.4 GHz band (e.g. Wi-Fi and Bluetooth)
- 1 to 512 QuickDMX receivers can be controlled by each transmitter
- LED indication for functions
- Transceiver, to be used as transmitter or receiver
- Can transmit up to 512 DMX channels
- Control via QuickDMX; DMX; plug and play
- Operating range up to 400m
- Up to 6 transmitters can be operated in parallel without interference

Technical specifications:

Weight: 29.89 kg

EUROLITE LED KLS-3002 Next Compact Light Set

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	225 W
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Cable length:	3 m
Power output:	2 x IEC connector (F) mounting version fused 1 x P-Con (gray), mounting version Bypass
Device fuse:	5 x 20 mm, T 2.5 A fuse replaceable
Power output fuse per channel:	5 x 20 mm, T 5 A fuse replaceable
Lamp type:	LED lamp
LED type:	7 x 10 W SMD 9090 6in1 RGBWA/UV (homogenous color mix)
DMX channels:	2; 4; 6; 10; 24; 28
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone; wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	EASY SHOW 1; Light J; LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Beam angle (1/2 peak):	19°
Beam angle (1/10 peak):	35°
Housing color:	Black
Attachment system:	TV spigot Ø 28mm Omega bracket
Display type:	Monochrome 4 digit 7-segment LED display
Dimensions:	Width: 128 cm Depth: 8 cm Height: 29 cm
Weight:	11.14 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE LED Laser Derby MK2

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	60 W
Protection class:	Protection class I
Power connection:	Mains input via IEC (M) power supply cord with safety plug
Power output:	IEC connector (F) mounting version Bypass

Fuse:	5 x 20 mm, T 1.6 A fuse replaceable
Lamp type:	LED lamp
DMX channels:	2; 4; 5; 6; 8; 7; 9
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	IR remote control; stand-alone; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional)
Fixtures available for:	Light Captain; EASY SHOW 2; Colorchief
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Control elements:	Navigation keys, sensitivity rotary dial
Status LED:	DMX, slave mode, auto mode, sound mode
Dimensions:	Width: 26 cm Depth: 19 cm Height: 19 cm
Weight:	2.17 kg
Cable length:	1.5 m
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Laser class:	2M
Laser color:	R/G
Laser module:	Green (G) 35 mW 532nm Red (R) 100 mW 650nm
LED type:	4 x 10 W SMD 5050 R/G/B/W
LED type:	16 x 0.6 W SMD 2835 cold white (CW)

EUROLITE DMX LED Color Chief Controller

Power supply:	100-240 V AC, 50/60 Hz 9V DC 800 mA
Power consumption:	7.2 W
Protection class:	Protection class III
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Programs:	Programmable 24 scenes/chases distributed over 1 page/s
DMX channels:	Output 240
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	DMX; sound to light via RCA (F) mounting version; sound to light via microphone
Housing color:	Black
Available storage media:	USB devices (FAT 32)

USB port:	Type A
Color:	Black
PC connect:	, firmware can be updated
Housing design:	(19") 48.3 cm rack installation 3 U Desktop console housing
Dimensions:	Width: 48.3 cm Depth: 13.35 cm Height: 8.5 cm
Weight:	2.25 kg
Noise classification:	Class 0 (no noise at all)

EUROLITE STV-60-WOT EU Steel Stand black

Maximum carrying capacity:	30 kg
Height:	Maximum: 320 cm Minimum: 150 cm
Attachment system:	TV spigot Ø 28mm
Type (general stands):	Light stand/manual
Material:	Steel/magnesium
Color:	Black
Transport dimensions:	126 cm x 12 cm x 15 cm
Weight:	5.65 kg

EUROLITE SB-4 Soft Bag L

Maximum load:	25 kg
Carrying strap:	2 pc/pcs
Material:	Nylon
Color:	Black, water repellent
Compartment dimensions:	15 cm x 15 cm x 20 cm
Inside dimensions:	31 cm x 34 cm x 20 cm
Dimensions:	Width: 32 cm Depth: 41 cm Height: 20 cm
Weight:	0.52 kg

OMNITRONIC IEC Extension 3x0.75 0.6m bk

Cable construction:	3 x 0.75 mm ² power cable
Cable length:	0.6 m
Plug A:	1 x IEC (M)
Plug B:	1 x IEC (F)
Color:	Black
Weight:	0.08 kg

ROADINGER Mixer Case Pro MCA-19-N, 3U, black

Maximum load:	25 kg
Removable covers:	1 pc/pcs
Aluminum profile frames:	30 mm
Carrying handle:	1 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	Rubber feet
Material:	Plywood multi-layer glued, 7 mm
Color:	Black, laminated; dark brown, laminated
Inside dimensions:	45 cm x 20 cm x 10.5 cm
Front panel width:	19"
Mounting height:	Approx. 13.5 cm (3 U)
Mounting depth:	105 mm
Housing design:	3 U
Dimensions:	Width: 55 cm Depth: 24 cm Height: 23.5 cm
Weight:	5.10 kg

EUROLITE QuickDMX USB Wireless Transmitter/Receiver

Power supply:	5V DC
Power connection:	Mains input via USB A (M) connectable version
DMX channels:	Input 512 Output 512
DMX output:	1 x USB, type A
Control:	DMX; QuickDMX; plug and play
Range:	Range up to 400m with line-of-sight
Carrier frequency:	2.4 GHz
Parallel mode:	Max. 6 transmitter
RF power output:	19 dBm
Modulation:	GFSK
Color:	Black
Dimensions:	Width: 8.6 cm Depth: 4 cm Height: 1.1 cm
Weight:	0.01 kg

EUROLITE QuickDMX Wireless Transmitter

Power supply:	100-240 V AC, 50/60 Hz 5V DC 1000 mA
---------------	---

Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord for USB A mains connection (provided)
DMX channels:	Output 512
DMX input:	1 x 3-pin XLR (M)
Control:	QuickDMX; DMX; plug and play
Range:	Range up to 400m
Carrier frequency:	2.4 GHz
Parallel mode:	Max. 6 transmitter
RF power output:	19 dBm
Modulation:	GFSK
Color:	Silver
Dimensions:	Length: 21.2 cm Diameter: Ø 1.8 cm
Weight:	0.15 kg

Scope of delivery:

1 x EUROLITE LED KLS-3002 Next Compact Light Set

- 1 x device
- 1 x user manual
- 1 x declaration of conformity
- 1 x power cord
- 1 x remote control
- 1 x bag
- 2 x omega bracket
- 4 x knurled screw
- 4 x washer
- 1 x battery
- 1 x terminating plug (power)

2 x EUROLITE LED Laser Derby MK2

- 1 x device
- 1 x user manual
- 1 x power cord
- 1 x remote control
- 1 x battery
- 1 x mounting bracket
- 2 x knurled screw
- 2 x washer

1 x EUROLITE DMX LED Color Chief Controller

- 1 x controller
- 1 x user manual
- 1 x external mains adapter

1 x EUROLITE STV-60-WOT EU Steel Stand black

- 1 x stand
- 1 x user manual

2 x EUROLITE SB-4 Soft Bag L

- 1 x bag

2 x OMNITRONIC IEC Extension 3x0.75 0.6m bk

- 1 x network cable

1 x ROADINGER Mixer Case Pro MCA-19-N, 3U, black

1 x case

3 x EUROLITE QuickDMX USB Wireless Transmitter/Receiver

1 x device

1 x user manual

1 x declaration of conformity

1 x EUROLITE QuickDMX Wireless Transmitter

1 x device

1 x user manual

1 x declaration of conformity

1 x external mains adapter

1 x USB cable