

EUROLITE Set 4x Multiflood Pro IP RGBW Wash MK2 + Case

Art. No.: 20000917

GTIN: 4026397702033



List price: 5353.81 €

incl. 19% VAT.

Features:

EUROLITE Multiflood Pro IP RGBW Wash MK2

Bright outdoor spot with RGBW LEDs and W-DMX

- Integrated W-DMX transceiver for wireless DMX Control
- 36 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
4 segments controlled separately
- Wash effect; strobe effect
- Direct color selection for 27 preset colors
- The device is cooled by low-noise cooling fan
- Control via stand-alone; IR remote control; DMX; W-DMX by wireless solution; master/slave function; wired remote control
- Preprogrammed in Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Light´J; Colorchief
- With a beam angle of 14°
- With omega bracket
- OLED display
- Rubber feet
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use
- For application areas such as: Installation; stage; rental; architecture
- Very quiet working noise
- Application possibility: Standing; suspended

Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery, 1 x omega bracket

Logistic

EAN / GTIN: 4026397702033

Weight: 80,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 1.00 m

Bulky product

ROADINGER Flightcase 4x Multiflood Pro IP RGBW MK2 with wheels

Trunk case with castors, HIGHLINE version

- With 4 device compartments
- With 1 accessory compartment
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 x castors with 2 locking brakes
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	81,20 kg
---------	----------

EUROLITE Multiflood Pro IP RGBW Wash MK2

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	230 W
IP classification:	IP65
LED type:	36 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 4; 6; 9; 10; 16; 26
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Low-noise cooling fan
Control:	Stand-alone; IR remote control; DMX; W-DMX by wireless solution; master/slave function; wired remote control
Preprogrammed in:	Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Light´J; Colorchief
Carrier frequency:	2,4 GHz
Beam angle:	14°
Beam angle (1/2 peak):	14°
Beam angle (1/10 peak):	30
Housing color:	Black
Attachment system:	Omega bracket
Display type:	OLED display
Transport aid:	Rubber feet
Dimensions:	Length: 51,35 cm Depth: 18,10 cm Height: 33,90 cm

Weight:	12,75 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x Multiflood Pro IP RGBW MK2 with wheels

Maximum load:	100 kg
Aluminum profile frames:	25 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Device compartment:	51,5 cm x 16 cm x 27,5 cm
Dimensions:	Length: 92 cm Width: 57,5 cm Height: 54 cm
Weight:	30,20 kg